

HCLSoftware

HCL DRYiCE MyCloud

Configuration Guide – Provider Module (Part 2)

Version 10.8.2



The data contained in this document shall not be duplicated, used, or disclosed as a whole or in part for any purpose. If a contract is awarded to chosen parties because of or in connection with the submission of this data, the client or prospective client shall have the right to duplicate, use, or disclose this data to the extent provided in the contract. This restriction does not limit the client's or prospective client's right to use the information contained in the data if it is obtained from another source without restriction. The data subject to this restriction is contained in all marked sheets.

HCL has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the HCL website at www.hcltechsw.com.

Copyright © 2025 HCL Technologies Limited

Contents

1.	Preface	23
1.1	Intended Audience	23
1.2	About This Guide	23
1.3	Related Documents	23
1.4	Conventions	23
2.	MyCloud Configuration and Management	25
1.5	MyCloud Provider Module.....	25
1.5.1	Role Based Access Control (RBAC)	26
1.5.2	User Cost Model	44
1.5.3	Service Catalog	57
1.5.4	Manage Billing Configuration	90
1.5.5	Release /Reserve IP	95
1.5.6	Manage Public Cloud Advisory	99
1.5.7	Performance Configuration	102
1.5.8	Manage Email.....	105
1.5.9	Manage Custom Script	109
1.5.10	Manage Script Schedule	114
1.5.11	AWS Cost Explorer Configuration	120
1.5.12	Import Objects	123
1.5.13	My Reports	126
1.5.14	Cloud Calculator	154
1.5.15	Decommission Reminder	155
1.5.16	Manage Run Once	158
1.5.17	CI Column Configuration	161
1.5.18	My Schedules.....	162
1.5.19	Logs	168
1.5.20	Help	168
1.5.21	Key Vault Configuration	170
1.5.22	Object Naming Convention	174
1.5.23	Job Notification Details	179
1.5.24	Manage GIT Configuration.....	180
1.5.25	Public Cloud Size Allocation	183
1.5.26	Manage Private Cloud Sizes	186
1.6	Blueprint Module	190
1.6.1	Manage Blueprint.....	191
1.6.2	Deploy Blueprint.....	226
1.6.3	Re-Run Blueprint.....	230

1.6.4	Execution of Blueprint by Creating UI and Process Template.....	231
1.6.5	New Resource in Blueprint to Execute Terraform File from GIT Repository	246
3.	Support	250

Table of Figures

Figure 1 – RBAC.....	26
Figure 2 – RBAC Role Management	26
Figure 3 – View Roles	27
Figure 4 – Edit Role	28
Figure 5 – Success Message Role Management.....	28
Figure 6 – Confirm Message	28
Figure 7 – Success Message	29
Figure 8 – Configure Menu	29
Figure 9 – Configure Widgets	30
Figure 10 – Add Role	30
Figure 11 – Success Message.....	31
Figure 12 – Manage User	31
Figure 13 – Add User	32
Figure 14 – Add User (Cont.).....	33
Figure 15 – Success Message.....	33
Figure 16 – View Users	34
Figure 17 – Edit User	35
Figure 18 – Edit User (Cont.).....	35
Figure 19 – User Updated Successfully.....	35
Figure 20 – Import User	36
Figure 21 – Upload User Confirmation.....	36
Figure 22 – Group Management	36
Figure 23 – View Group	37
Figure 24 – Manage Group User Mapping (Cont.)	38
Figure 25 – Confirmation Message.....	38
Figure 26 – Group User Mapping.....	39
Figure 27 – Group Role Mapping	39
Figure 28 – Success Message	39
Figure 29 – View Group	40

Figure 30 - Confirmation Message	40
Figure 31 - Edit Group	40
Figure 32 - Success Message	41
Figure 33 - Confirmation Message.....	41
Figure 34 - Success Message.....	41
Figure 35 - Apply Tag(S).....	42
Figure 36 - Success Message	42
Figure 37 - Add Group.....	42
Figure 38 - Success Message	43
Figure 39 - Transfer Object Ownership.....	43
Figure 40 - List of Objects	44
Figure 41 - Select Owner to Transfer Object	44
Figure 42 - Success Message	44
Figure 43 - User Cost Model	45
Figure 44 - Create Service Plan.....	45
Figure 45 - Confirmation Message	45
Figure 46 - Service Plan	46
Figure 47 - Edit Service Plan (Cont.).....	46
Figure 48 - Confirmation Message	46
Figure 49 - Confirmation Query.....	47
Figure 50 - Confirmation Message	47
Figure 51 - View Service Plan	47
Figure 52 - Manage Services.....	48
Figure 53 - Add Cost Model	49
Figure 54 - Add Cost Model (Cont.).....	50
Figure 55 - Assign Cost to The Cost Model	50
Figure 56 - Assign Cost to The Cost Model (Cont.).....	51
Figure 57 - Assign Cost to The Cost Model (Cont.)	51
Figure 58 - Assign Cost to The Cost Model (Cont.).....	51
Figure 59 - Assign Cost to The Cost Model (Cont.).....	51

Figure 60 – View Cost Model	52
Figure 61 – Copy Cost Model.....	53
Figure 62 – Copy Cost Model (Cont.).....	53
Figure 63 – Confirmation Message	54
Figure 64 – Catalog	54
Figure 65 – Edit Cost Model.....	55
Figure 66 – Edit Cost Model (Cont.)	55
Figure 67 – Confirmation Message	55
Figure 68 – Confirmation Cost Model.....	56
Figure 69 – Cost Model Mapping.....	56
Figure 70 – Cost Model Mapping (Cont.)	56
Figure 71 – Delete Cost Model Mapping.....	57
Figure 72 – Delete Cost Model Mapping (Cont.)	57
Figure 73 – Service Catalog	58
Figure 74 – Create Catalog	58
Figure 75 – Create Catalog Success Message.....	59
Figure 76 – View Catalog	59
Figure 77 – Edit Catalog.....	60
Figure 78 – Edit Catalog (Cont.)	60
Figure 79 – Edit Catalog Success Message.....	60
Figure 80 – Delete Catalog	61
Figure 81 – Delete Catalog (Cont.).....	61
Figure 82 – Delete Catalog Success Message	61
Figure 83 – Create Service Catalog	62
Figure 84 – Publish Service Catalog Confirmation Message	63
Figure 85 – View Published Service Catalog.....	64
Figure 86 – Edit Published Service Catalog	65
Figure 87 – Edit Public Service Catalog (Cont.)	65
Figure 88 – Edit Catalog Confirmation Message	65
Figure 89 – Publish Service Catalog Export.....	66

Figure 90 – Publish Service Catalog Import	66
Figure 91 – Publish Service Catalog Import.....	67
Figure 92 – Publish Service Catalog Import.....	68
Figure 93 – Publish Service Catalog Import.....	68
Figure 94 – Publish Service Catalog Import	69
Figure 95 – Publish Service Catalog Import.....	69
Figure 96 – Publish Service Catalog Import	70
Figure 97 – Preview and Submit	70
Figure 98 – Confirmation Message	70
Figure 99 – Delete Published Service Catalog.....	71
Figure 100 – Delete Published Service Catalog	71
Figure 101 – Confirmation Message	71
Figure 102 – Copy Service Catalog to Other Region.....	72
Figure 103 – Success Message	72
Figure 104 – Copy Published Service Catalog to Other Endpoint.....	72
Figure 105 – Success Message	73
Figure 106 – Service Catalog Library.....	73
Figure 107 – List of Existing Service Catalog Library	73
Figure 108 – Import Service Catalog by Existing Service Catalog Library.....	74
Figure 109 – Import Service Catalog by Existing Service Catalog Library	74
Figure 110 – Publish Action.....	75
Figure 111 – Add Publish Action (Cont.)	75
Figure 112 – View Action	76
Figure 113 – Edit Action (Cont.).....	76
Figure 114 – Confirmation Message	77
Figure 115 – Delete Object Action	77
Figure 116 – Delete Object Action.....	77
Figure 117 – Confirmation Message.....	77
Figure 118 – Publish Action	78
Figure 119 – Publish Action Export.....	78

Figure 120 – Configure Conflict Action.....	79
Figure 121 – Configure Conflict Action (Cont.).....	79
Figure 122 – Upload File.....	80
Figure 123 – Organization Not Selected.....	80
Figure 124 – Platform Not Selected.....	80
Figure 125 – Invalid Zip File.....	81
Figure 126 – Incorrect Zip File/Content.....	81
Figure 127 – Platform Name does Not Match.....	81
Figure 128 – Validation Message.....	82
Figure 129 – Approval Definition.....	82
Figure 130 – UI Template.....	83
Figure 131 – Process Template.....	83
Figure 132 – Action.....	84
Figure 133 – Publish Action.....	84
Figure 134 – Upload Custom Table.....	85
Figure 135 – Preview and Summary.....	86
Figure 136 – Success Message.....	86
Figure 137 – Add Action.....	87
Figure 138 – Confirmation Message.....	87
Figure 139 – Edit Action.....	88
Figure 140 – Edit Action (Cont.).....	88
Figure 141 – Edit Action (Cont.).....	89
Figure 142 – Action Object Mapping (Cont.).....	89
Figure 143 – Action Mapping (Cont.).....	89
Figure 144 – Action Mapping (Cont.).....	90
Figure 145 – Change Action Status.....	90
Figure 146 – Confirmation Message.....	90
Figure 147 – Add Mapping.....	91
Figure 148 – Add Mapping (Cont.).....	91
Figure 149 – View Mapping.....	92

Figure 150 - Edit Mapping	92
Figure 151 - Edit Mapping (Cont.)	93
Figure 152 - Delete Mapping	93
Figure 153 - Delete Mapping (Cont.)	93
Figure 154 - Delete Mapping (Cont.)	94
Figure 155 - View Mapping	94
Figure 156 - Tag Mapping	94
Figure 157 - Tag Mapping (Cont.)	95
Figure 158 - Tag Mapping (Cont.)	95
Figure 159 - Release IP Home Screen	96
Figure 160 - Release IP Home Screen for Cisco Intersight.....	96
Figure 161 - Release IP Details	97
Figure 163 - Confirmation of Release IP.....	97
Figure 164 - Success Message	98
Figure 166 - Popup Box For Reserve IP	98
Figure 167 - Confirmation for Reserve IP	98
Figure 168 - Success Message For Reserve IP.....	99
Figure 169 - Success Message for Bulk IP Release	99
Figure 170 - Success Message for Bulk IP Release	99
Figure 171 - Manage Public Cloud Advisory	100
Figure 172 - Add New Configuration.....	100
Figure 173 - Confirmation Message	100
Figure 174 - Edit Configuration	101
Figure 175 - Edit Configuration Cont.....	101
Figure 176 - Confirmation Message	102
Figure 177 - Add Mapping	102
Figure 178 - Add Mapping (Cont.).....	103
Figure 179 - View Mapping	103
Figure 180 - Edit Mapping.....	104
Figure 181 - Reinitiate Mapping	104

Figure 182 – Schedule Mapping	105
Figure 183 – Success Message.....	105
Figure 184 – Manage Email.....	105
Figure 185 – View Email	106
Figure 186 – View Email (Cont.).....	107
Figure 187 – Confirmation Message (Resend Mail).....	108
Figure 188 – Success Message (Resend Mail)	108
Figure 189 – History Manage Email.....	108
Figure 190 – History Manage Email (Cont.).....	109
Figure 191 – Detailed Log History (Cont.)	109
Figure 192 – Manage Custom Script	110
Figure 193 – Manage Custom Script	110
Figure 194 – Manage Custom Script (Cont.).....	110
Figure 195 – Edit Manage Custom Script.....	111
Figure 194 – Success Message Manage Custom Script	111
Figure 197 – Confirmation Message	112
Figure 196 – Confirmation Message.....	112
Figure 200 – Success Message	112
Figure 201 – Export JSON.....	113
Figure 202 – Create Custom Script.....	113
Figure 203 – Success Message Create Script.....	114
Figure 204 – Manage Script Schedule.....	114
Figure 205 – Manage Script Schedule.....	115
Figure 206 – Manage Script Schedule (Cont.)	115
Figure 207 – Manage Script Schedule (Edit.)	116
Figure 208 – Success Message Script Schedule (Edit.)	116
Figure 209 – Confirmation Message Script Schedule (Delete.)	117
Figure 210 – Success Message Script Schedule (Delete.)	117
Figure 211 – History	117
Figure 212 – History	118

Figure 213 - Manage Script Schedule	118
Figure 214 - Create Schedule	119
Figure 215 - Success Schedule.....	120
Figure 216 - Add Configuration.....	120
Figure 217 - Add Configuration (Cont.)	121
Figure 218 - View Mapping	121
Figure 219 - Edit Configuration	122
Figure 220 - Edit Configuration.....	122
Figure 221 - Confirmation Message	123
Figure 222 - Success Message.....	123
Figure 223 - Import Objects	123
Figure 224 - Import Objects.....	124
Figure 225 - Import Objects (Cont.)	124
Figure 226 - Import Objects (Cont.).....	124
Figure 227 - Import CI	125
Figure 228 - Import CI	125
Figure 229 - Import Objects	125
Figure 230 - Public Cloud Annual Billing Analysis	127
Figure 231 - Public Cloud Annual Billing Analysis (Cont.).....	127
Figure 232 - Azure Service Usage Report	128
Figure 233 - Azure Service Usage Report (Cont.)	128
Figure 234 - Amazon Service Report	128
Figure 235 - Amazon Service Report (Cont.)	129
Figure 236 - Amazon Service Report (Contd.)	129
Figure 237 - Public Cloud Billing	129
Figure 238 - Public Cloud Billing (Cont.).....	130
Figure 239 - Public Cloud Billing (Cont.)	130
Figure 240 - Public Cloud Billing (Contd.)	131
Figure 241 - Public Cloud Billing.....	131
Figure 242 - CI Report.....	132

Figure 243 – CI Report.....	132
Figure 244 – CI Report (Cont.)	132
Figure 245 – CI Report (Cont.)	133
Figure 246 – CI Report (Cont.)	133
Figure 247 – CI Report.....	134
Figure 248 – CI Report.....	134
Figure 249 – CI Report	134
Figure 250 – Resource Detail	135
Figure 251 – Resource Detail (Cont.).....	135
Figure 252 – Resource Detail (Cont.)	135
Figure 253 – Resource Detail (Cont.)	136
Figure 254 – Request Task Management.....	136
Figure 255 – Request Task Management (Cont.)	137
Figure 256 – Request Task Management (Cont.)	137
Figure 257 – Request Task Management (Cont.)	137
Figure 258 – Request Task Management (Cont.)	137
Figure 259 – Request Task Management (Cont.)	137
Figure 260 – Request Task Management (XML)	138
Figure 261 – Request Task Management (XML) (Cont.)	138
Figure 262 – Request Task Management.....	139
Figure 263 – ITSM Request Racking	139
Figure 264 – ITSM Status Tracking (Cont.).....	140
Figure 265 – ITSM Request Tracking (Cont.)	140
Figure 266 – Request Tracking.....	140
Figure 267 – Request Tracking (Cont.).....	141
Figure 268 – Request Tracking (Cont.).....	141
Figure 269 – Request Tracking (Cont.).....	141
Figure 270 – Amazon Monthly Billing Analysis.....	142
Figure 271 – Amazon Monthly Billing Analysis (Cont.)	142
Figure 272 – SLA Reports.....	143

Figure 273 – SLA Reports.....	143
Figure 274 – vCenter Performance Dashboard (Cont.)	143
Figure 275 – vCenter Performance Dashboard (Cont.)	144
Figure 276 – vCenter Performance Dashboard (Cont.)	144
Figure 277 – vCenter Performance Dashboard (Cont.)	144
Figure 278 – vCenter Performance Dashboard (Cont.)	145
Figure 279 – vCenter Performance Dashboard (Cont.)	145
Figure 280 – vCenter Performance Dashboard (Cont.)	145
Figure 281 – vCenter Performance Dashboard (Cont.)	146
Figure 282 – vCenter Performance Dashboard (Cont.)	146
Figure 283 – vCenter Performance Dashboard (Cont.)	146
Figure 284 – vCenter Performance Dashboard (Cont.)	146
Figure 285 – vCenter Performance Dashboard (Cont.)	147
Figure 286 – vCenter Performance Report (Cont.)	147
Figure 287 – vCenter Performance Report (Cont.)	147
Figure 288 – vCenter Performance Report (Cont.)	148
Figure 289 – vCenter Performance Report (Cont.)	148
Figure 290 – vCenter Performance Report	149
Figure 291 – Public Cloud Annual Billing Analyzer.....	149
Figure 292 – Public Cloud Annual Billing Analyzer (Cont.)	150
Figure 293 – Public Cloud Annual Billing Analyzer (Cont.)	150
Figure 294 – Public Cloud Annual Billing Analyzer (Cont.)	150
Figure 295 – Public Cloud Annual Billing Analyzer (Cont.)	151
Figure 296 – Forecasting and RI Recommendation.....	151
Figure 297 – Forecasting And RI Recommendation.....	152
Figure 298 – Forecasting And RI Recommendation (Cont.)–AWS.....	153
Figure 299 – Forecasting And RI Recommendation (Cont.)–AWS	153
Figure 300 – Forecasting and RI Recommendation (Cont.)–AWS.....	153
Figure 301 – Cloud Calculator	154
Figure 302 – Cloud Calculator (Cont.)	154

Figure 303 – Cost Per Month.....	155
Figure 304 – Create Reminder (Cont.)	155
Figure 305 – Create Reminder (Cont.)	156
Figure 306 – View Reminder	156
Figure 307 – Edit Reminder	157
Figure 308 – Edit Reminder (Cont.).....	157
Figure 309 – Confirmation Message	157
Figure 310 – Success Message	158
Figure 311 – View RunOnce Command (Cont.).....	158
Figure 312 – Edit RunOnce Command.....	159
Figure 313 – Edit RunOnce Command (Cont.)	159
Figure 314 – Confirmation Message.....	159
Figure 315 – Success Message.....	160
Figure 316 – Add RunOnce Command	160
Figure 317 – Add RunOnce Command	161
Figure 318 – CI Column Configuration	161
Figure 319 – Import Configuration (Cont.).....	161
Figure 320 – Import Configuration (Cont.).....	162
Figure 321 – Success Message.....	162
Figure 322 – My Schedules Home Screen.....	163
Figure 323 – Create Schedule	163
Figure 324 – Create Schedule (Cont.).....	164
Figure 325 – Create Schedule (Cont.)	165
Figure 326 – Create Schedule (Cont.)	165
Figure 327 – Create Schedule (Cont.)	165
Figure 328 – View Schedules	166
Figure 329 – Schedule History	167
Figure 330 – View Logs Home Screen	168
Figure 331 – View Logs (Cont.)	168
Figure 332 – Help	169

Figure 333 – Generic Task Detail	169
Figure 334 – Generic Task Detail (Cont.)	169
Figure 335 – Reference Guide	170
Figure 336 – Key Vault Configuration	170
Figure 337 – Add Configuration	171
Figure 338 – Add Configuration (Cont.)	171
Figure 339 – Success Message	171
Figure 340 – View Configuration	172
Figure 341 – View Configuration (Cont.)	172
Figure 342 – Edit Configuration	173
Figure 343 – Success Message	173
Figure 344 – Confirmation Message	174
Figure 345 – Success Message	174
Figure 346 – Add Keys	174
Figure 347 – CI Naming Convention Home Screen	175
Figure 348 – Add Configuration	175
Figure 349 – Success Message	176
Figure 350 – CI Naming Convention Home Screen	176
Figure 351 – View Configuration	177
Figure 352 – Edit Configuration	177
Figure 353 – Success Message	177
Figure 354 – Confirmation Message	178
Figure 355 – Success Message	178
Figure 356 – Manage Keys	178
Figure 357 – Job Notification Details Home Screen	179
Figure 358 – Job Notification Popup	180
Figure 359 – Manage GIT Configuration Home Screen	180
Figure 360 – Manage GIT Configuration	181
Figure 361 – Manage GIT Configuration (Cont.)	181
Figure 362 – Success Message	182

Figure 363 - Manage GIT Configuration.....	182
Figure 364 - Edit Configuration.....	182
Figure 365 - Success Message	183
Figure 366 - Confirmation Message.....	183
Figure 367 - Success Message	183
Figure 368 - Public Cloud Size Allocation	184
Figure 369 - Allocate Size	184
Figure 370 - Allocate Size	185
Figure 371 - Success Message.....	185
Figure 372 - View Allocated Size	185
Figure 373 - List of Allocated Size.....	186
Figure 374 - Confirmation Message.....	186
Figure 375 - Success Message.....	186
Figure 376 - Manage Private Cloud Sizes	186
Figure 377 - Add Size.....	187
Figure 378 - Success Message.....	187
Figure 379 - View Sizes.....	188
Figure 380 - Home Screen.....	188
Figure 381 - Edit Size.....	188
Figure 382 - Success Message	189
Figure 383 - Confirmation Message.....	189
Figure 384 - Success Message	189
Figure 385 - Confirmation Message.....	190
Figure 386 - Success Message	190
Figure 387 - Manage Blueprint Menu	191
Figure 388 - Manage Blueprint Page	191
Figure 389 - Design Blueprint.....	192
Figure 390 - Cloud Platform Selection	193
Figure 391 - Blueprint Object Search Bar	193
Figure 392 - Left Object Menu.....	194

Figure 393 – Left Object Menu (Cont.)	195
Figure 394 – Middle Diagram Pane	195
Figure 395 – Right Attribute Window	196
Figure 396 – Input Attributes.....	196
Figure 397 – Output Attributes.....	197
Figure 398 – Variable Mapping	198
Figure 399 – Variable Mapping (Cont.).....	198
Figure 400 – Provider Mapping	199
Figure 401 – Zone Mapping.....	199
Figure 402 – Object Mapping	200
Figure 403 – Input object ID as Text	200
Figure 404 – Select the Object from List.....	200
Figure 405 – Object Mapping Using Variables	201
Figure 406 – Expand	202
Figure 407 – Save Blueprint.....	202
Figure 408 – Success Message	203
Figure 409 – Add Variable	203
Figure 410 – Variable Type	204
Figure 411 – Add Variable – Key Value Pair Variable.....	204
Figure 412 –Add Variable – Array Variable	204
Figure 413 – Add Variable – Ansible Variable	205
Figure 414 – Add Variable – Ansible Variable (Cont.).....	205
Figure 415 – Add Variable – Ansible Variable (Cont.)	205
Figure 416 – Add Variable – Region Variable.....	206
Figure 417 – Add Variable – Cisco Intersight Params Variable	206
Figure 418 – Add Variable – Cisco Intersight Params Variable (Cont.)	207
Figure 419 – Add Variable – Cisco Intersight Params Variable (Cont.)	207
Figure 420 – Success Message	207
Figure 421 – Edit Variable.....	208
Figure 422 – Delete Variable	209

Figure 423 – Download TF File	209
Figure 424 – Validation Summary	210
Figure 425 – Validation Success Message	210
Figure 426 – New Blueprint.....	210
Figure 427 – Blueprint Title	211
Figure 428 – Manage Blueprint Page	211
Figure 429 – View Blueprint.....	212
Figure 430 – View Blueprint Filter Option	212
Figure 431 – Options in the Action Column	213
Figure 432 – Edit Blueprint.....	214
Figure 433 – Update Blueprint	214
Figure 434 – Success Message for Update	215
Figure 435 – Success Message for a New Version Update	215
Figure 436 – Change Status Confirmation	215
Figure 437 – Success Message for Status Change.....	216
Figure 438 – Status Changed to 'Active'	216
Figure 439 – Status Changed to 'Inactive'	216
Figure 440 – Exported JSON File	217
Figure 441 – Deploy Blueprint from View Blueprint Page	217
Figure 442 – Deployment History	218
Figure 443 – Deployment History Drill Down.....	219
Figure 444 –Deployment Execution Log.....	220
Figure 445 – Multiple Tasks Listed under Deployment History Drill Down	220
Figure 446 – Confirmation Message	221
Figure 447 – Success Message	221
Figure 448 – Import Blueprint.....	221
Figure 449 – Import Blueprint Choose File	222
Figure 450 – Imported Blueprint listed in View Blueprint.....	222
Figure 451 – Ansible Object.....	223
Figure 452 – Ansible Object on Blueprint Diagram.....	223

Figure 453 – Extra Vars in Ansible Object	224
Figure 454 – Cisco Intersight Object	224
Figure 455 – Cisco Intersight Object on Blueprint Diagram	225
Figure 456 – Workflow Parameter in Cisco Intersight Object	225
Figure 457 – Blueprint Deployment	226
Figure 458 – Provisioning Window for Blueprint	227
Figure 459 – Successful Provisioning of Blueprint Objects	227
Figure 460 – Blueprint Deployment Window from Ansible Object	228
Figure 461 – Extra Vars in Ansible Object	228
Figure 462 – Blueprint Deployment Window from Cisco Intersight Object	229
Figure 463 – Workflow Parameter in Cisco Intersight Object	229
Figure 464 – Blueprint Deployment on Re-Run	231
Figure 465 – Blueprint Created for Process Workflow	232
Figure 466 – Create UI Template Menu	232
Figure 467 – UI Template Creation for Blueprint Deployment	233
Figure 468 – Create Process Template Menu	234
Figure 469 – Process Template Creation for Blueprint Deployment	234
Figure 470 – Add Task for Process Template	235
Figure 471 – Manage Task Action	235
Figure 472 – Manage Task Action Window	235
Figure 473 – Map Key Value of Manage Task Action	236
Figure 474 – Ansible Configuration of Manage Task Action	237
Figure 475 – Ansible Configuration of Manage Task Action (Cont.)	237
Figure 476 – Manage Cloud Template Menu	238
Figure 477 – Manage Cloud Templates	238
Figure 478 – Create Cloud Template	238
Figure 479 – Create Catalog Menu	239
Figure 480 – Manage Catalog	239
Figure 481 – Manage Catalog (Cont.)	239
Figure 482 – Publish Service Catalog Menu	240

Figure 483 – Publish Service Catalog	240
Figure 484 – Publish Service Catalog (Cont.).....	240
Figure 485 – Request Service Catalog Menu	241
Figure 486 – Request Service Catalog.....	241
Figure 487 – Request Service Catalog (Cont.).....	241
Figure 488 – Request Service Catalog (Cont.).....	242
Figure 489 – Request Service Catalog (Cont.).....	242
Figure 490 – Request Service Catalog (Cont.)	242
Figure 491 – Request Under My Request.....	243
Figure 492 – Request under My Request (Cont.).....	243
Figure 493 – Request Task Management Menu	244
Figure 494 – Request Task Management	244
Figure 495 – Request Task Management (Cont.)	245
Figure 496 – Request Task Management (Message XML).....	245
Figure 497 – Request Task Management (View Response)	245
Figure 498 – Detailed Logs	246
Figure 499 – Execute Terraform File from Git Repository	246
Figure 500 – Terraform Variables	247
Figure 501 – TF Backend Config with S3 Backend Type.....	248
Figure 502 – TF Backend Config with Blob Backend Type	248
Figure 503 – TF Backend Config with Local Backend Type	248
Figure 504 – Success Message.....	249

List of Tables

Table 1 – Conventions	23
Table 2 – Built-In Roles	25
Table 3 – Role Management	27
Table 4 – Add Role	30
Table 5 – Add User	32
Table 6 – View Users	34
Table 7 – Add Cost Model	49
Table 8 – Assign Cost to The Cost Model	50
Table 9 – List of Fields	53
Table 10 – Create Service Catalog Fields	62
Table 11 – Add Action	87
Table 12 – Add Mapping (Azure)	91
Table 13 – Release IP	96
Table 14 – Release IP Details	97
Table 15 – Edit Configuration	101
Table 16 – Add Mapping	102
Table 17 – Manage Email	105
Table 18 – View Email	106
Table 19 – View Email Grid	107
Table 20 – View Email History	109
Table 21 – View Email History	113
Table 22 – Manage Scripts Schedule	115
Table 23 – Add Schedule	119
Table 24 – Add Mapping	120
Table 25 – Forecasting and RI Recommendation	151
Table 26 – Forecasting And RI Recommendation	153
Table 27 – Create Reminder	155
Table 28 – Manage RunOnce	160
Table 29 – Create Schedule Fields	163

Table 30 – View Users Field	166
Table 31 – Schedule History Field.....	167
Table 32 – Add Configuration	171
Table 33 – View Configuration	172
Table 34 – Edit Configuration	173
Table 35 – Add Configuration	175
Table 36 – Job Notification Details.....	179
Table 37 – Add Configuration.....	181
Table 38 – View Blueprint Table Columns.....	212
Table 39 – Deployment History Table Columns	218
Table 40 – Deployment History Drill Down Table Field	219
Table 41 – Input Attributes in Git Repository	246

Document Revision History

This guide is updated with each release of the product or when necessary.

This table provides the revision history of this Configuration Guide.

Version Date	Description
May, 2020	DRYiCE MyCloud V9.2 Configuration Guide – Provider Module (Part 2)
August, 2020	DRYiCE MyCloud V10.0 Configuration Guide – Provider Module (Part 2)
November, 2020	DRYiCE MyCloud V10.1 Configuration Guide – Provider Module (Part 2)
February, 2021	DRYiCE MyCloud V10.2 Configuration Guide – Provider Module (Part 2)
April, 2021	DRYiCE MyCloud V10.4 Configuration Guide – Provider Module (Part 2)
October, 2021	DRYiCE MyCloud V10.5 Configuration Guide – Provider Module (Part 2)
September, 2022	DRYiCE MyCloud V10.6 Configuration Guide – Provider Module (Part 2)
August, 2023	HCL_DRYiCE_MyCloud_10.7_Configuration_Provider_Guide_Part2
April, 2024	HCL_DRYiCE_MyCloud_10.8_Configuration_Provider_Guide_Part2
September, 2024	HCL_DRYiCE_MyCloud_10.8.1_Configuration_Provider_Guide_Part2
February, 2025	HCL_DRYiCE_MyCloud_10.8.2_Configuration_Provider_Guide_Part2

1. Preface

This section provides information about the MyCloud configuration guide and includes the following topics.

- [Intended Audience](#)
- [About This Guide](#)
- [Related Documents](#)
- [Conventions](#)

1.1 Intended Audience

This document is intended for its administrator's/business administrators those are responsible for configuring MyCloud (provider module) and enabling end-users to consume MyCloud services.

1.2 About This Guide

This guide provides instructions to configure MyCloud. This includes the post-installation and configuration procedures for the product. This document is in continuation to the **MyCloud Configuration Guide – Provider Module (Part 1)**.

1.3 Related Documents

The following documents can be referenced in addition to this guide for further information on MyCloud.

- MyCloud Introduction Guide
- MyCloud Installation Guide
- MyCloud User Guide
- MyCloud Troubleshooting Guide
- MyCloud API Guide
- MyCloud V3 API Guide
- MyCloud Developer Guide
- MyCloud Configuration Guide – Admin Module
- MyCloud Configuration Guide – Provider Module – Part 1

1.4 Conventions

The following typographic conventions are used in this document:

Table 1 – Conventions

Convention	Element
Boldface	Indicates graphical user interface elements associated with an action, or terms defined in text or the glossary
Underlined Blue Face	Indicates cross-reference and links
Courier New (Font)	Indicates commands within a paragraph, URLs, code in examples, and paths

	including onscreen text and text input from users
Italic	Indicates document titles, occasional emphasis, or glossary terms
Numbered Lists	Indicates steps in a procedure to be followed in a sequence
Bulleted Lists	Indicates a list of items that is not necessarily meant to be followed in a sequence

2. MyCloud Configuration and Management

MyCloud environment is an extensive open distributed system that stores the data and protects the privacy of users. A user's role determines the tasks that the user will be able to perform. Each role is associated with permissions or rules that define the degree to access the features in MyCloud.

The following lists five fundamental built-in roles.

Table 2 – Built-In Roles

Section Name	Description
MyCloud Admin	MyCloud admin has the rights to manage providers, admin level jobs and other component related configurations
Provider Admin	Provider admin is a business manager or an administrator responsible for configuring MyCloud as per the organization requirements. The primary responsibilities are: <ul style="list-style-type: none">• Manages and configures the organization• Manages the users and groups (within the organization)• Manages UI template• Manages services catalog• Creates approval groups and workflows• Manage organization resources• Manage domains/AD users in organizations• Request status tracking• Onboard tenant in system
Organization Admin	Organization admin has the rights to manage the users, roles, and groups assigned to them (organization-specific)
Requester	Requester has the rights to request for infrastructure resources (IaaS & PaaS services) view or manage reports related to the resources.
Approver	Approver has the rights to approve the requests raised by the requesters.

1.5 MyCloud Provider Module

This document continues from the last step (Publish Service Catalog) covered in MyCloud Configuration Guide – Provider Guide (Part 1) Module. The Rest of the configuration steps will be covered in the following sections.

1.5.1 Role Based Access Control (RBAC)

Role Based Access Control (RBAC) is an important component of MyCloud. This module details the steps to manage RBAC model within an environment to implement several important security principles such as least privilege, separation of duties, and data abstraction.

This model includes two kinds of role management: Manage Group and Manage User. Different users of this platform communicate with service providers and get permissions to access resources, and these permissions are given based on mapping of the users to system-based groups.

1. On the main menu bar, click **RBAC**.
2. The drop-down appears with the following options:
 - Manage Group
 - Manage User
 - Role Management
 - Transfer Object Ownership




Figure 1 – RBAC

Provider gets to access both Manage User and Manage Group.

1.5.1.1 Role Management

Through this module, provider users can manage roles in an organization through following actions:

- **Add Role** : To add roles in an organization
- **View Role**: To view the existing roles in an organization





Figure 2 – RBAC Role Management

1.5.1.1.1 View Role

Through this module, provider users can view existing roles in an organization.

1. Select **Organization** from the drop-down.
2. Click **Go**.











Role Name	Status	Power User	Parent Role	MyCloud System Role	Action
Organization Admin	●	NO		YES	
Business	●	NO		YES	
Finance	●	NO		YES	
IT Admin	●	NO		YES	
Requester	●	NO		YES	
Custom1	●	NO	Organization Admin	NO	   
Operator	●	NO	Organization Admin	NO	   





Figure 3 - View Roles

3. Refer to the below table to understand the fields mentioned in the above figure:

Table 3 - Role Management


Fields	Description
Role Name	Name of the MyCloud user's role
Status	Whether role is active or in active
Parent Role	MyCloud system created role that will act as a parent role for the newly added role
MyCloud System Role	Yes: default system roles created by MyCloud No: role created by provider

4. Through this, provider user can perform below actions on the role:

- **Edit** (): To edit the roles
- **Delete** (): To delete the roles
- **Configure Menus** (): To assign menu to this role
- **Configure Widget** (): To assign widgets to this role

1.5.1.1.2 Edit Role

To edit/ modify the information of an existing role management, provider user needs to follow the below steps:

1. On the Role Management screen, click View Role.
2. Select Organization.
3. Click Go.
4. Available roles list down in a tabular view.
5. Click Edit () corresponding the role to be edited.
6. Below the screen appears.

Role Management

View Role | **Add Role**

Organization * JSHCL

Role Name* Test

Parent Role* i Organization Admin

Power User i No

Save

Figure 4 - Edit Role

7. Users can modify the appropriate fields and click on **Save**.
8. A success message appears.



Figure 5 - Success Message Role Management

1.5.1.1.3 Delete Role

To delete an existing role, provider user needs to follow the below steps:

1. On the Role Management screen, click View Role.
2. Select Organization.
3. Click **Go**.
4. Available role lists down in a tabular view.
5. Click **Delete** (🗑️) against the role to be deleted.
6. A confirmation message appears.




Figure 6 - Confirm Message

7. Click **OK** to confirm. A success message appears.





Figure 7 - Success Message

1.5.1.1.4 Configure Menu

To configure the menus in existing role, provider user needs to follow the below steps:

1. On the Role Management screen, click View Role.
2. Select Organization.
3. Click **Go**.
4. Available role lists down in a tabular view.
5. Click **Configure Menu** () corresponding to the role for which the user wants to configure menu.
6. The below screen appears.




Figure 8 - Configure Menu

7. Click on checkbox to select the menu items and click on **Assign Menu** to save the selection.

1.5.1.1.5 Configure Widgets

To configure the widgets for an existing role, provider user needs to follow the below steps:


1. On the Role Management screen, click View Role.
2. Select Organization.
3. Click **Go**.
4. Available role lists down in a tabular view.
5. Click **Configure Widgets** () corresponding to the role for which you want to configure widget.
6. The below screen appears.
7. Click on the **checkbox** to configure the appropriate widgets and click on **Assign Widgets** to assign.

Figure 9 - Configure Widgets

1.5.1.1.6 Add Role

Through this module, provider user can **Add** new roles in an organization.

1. Click on **Add Role**, the **Role Management** screen appears.

Figure 10 - Add Role

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 4 - Add Role

Fields	Description
Organization	The name of the organization (business units/ divisions in organizations)
Role Name	The name of MyCloud role
Parent Role	MyCloud system created role that will act as a parent role for the newly added role.
Power User	Power user will be able to see request and object belongs to another user in same role.

3. Select Organization, Role Name, and Power User.
4. Enter Role Name.
5. Click **Go**. A success message appears.




Figure 11 – Success Message

1.5.1.2 Manage User

Through this module, provider users can manage users in an organization. It has following options:




Figure 12 – Manage User

- **Add Users:** To add users in an organization
- **Import Users:** To add bulk users in an organization
- **View Users:** To view the list of users in an organization

1.5.1.2.1 Add User

To add an end user in an organization, provider user needs to follow the below steps:

1. Click on the **Manage User** screen and then click **Add User**.

Manage User

View Users **Add User** Import Users

User Type*
☐ Service Account ☐ Organizational User

Organization*
 --Select--

User Name*

User Id*

Email*

Active
☒

Password*

Generate Password

Token Expiration Time (In Seconds)

Role *

Select Widget

Figure 13 - Add User

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 5 - Add User

Fields	Description
API User	This type of user used for API integration with MyCloud
Organizational User	User for request and manage resources
Password	MyCloud generated password
Generate Password	The option that helps to generate a password in MyCloud
Token Expiration Time (in seconds)	This section is applicable for service account user it is an integer value to define the access token timeout for this user, to override the default token expiration value configured by admin user.
Role	This section is applicable for organization users .Provider-user needs to provide a role to a user while adding it in MyCloud
Select Widget	This section is applicable for organization users. MyCloud dashboard widgets are listed. System defined widgets appear

3. Select **Organization** to add user.
4. Select **User Type**. MyCloud supports two types of users:
 - **API User**: has access to MyCloud apis and used for integration with MyCloud.
 - **Organizational User**: has access to MyCloud web portal and used to request services.
5. Enter the **Username** and then enter the **User ID**.
6. Enter Email ID.

7. Click **Generate Password** to generate new password.
8. Select **Role**.
9. Once the role is selected, the widgets appear in the widget box.
10. Select **Widget**. Provider selects the dashboard widgets according to the role to be assigned to an end user.
11. Click **Save**.

Figure 14 - Add User (Cont.)

Change the password frequently, at least once a month, to keep hackers out of the system. When the application is not being used then log off for security purposes. All fields marked with asterisk (*) are mandatory.

12. A success message box appears.



Figure 15 - Success Message

1.5.1.2.2 View Users

This section lists all the users that have been created by provider users in an organization.





Figure 16 – View Users

Refer to the below table to understand the fields mentioned in the above figure:

Table 6 – View Users

Fields	Description
Organization	Select the name of the organization (business units/ divisions in organizations)
Username	Username of the user that has been added
Email	Email of the user that has been added
User ID	User ID of the user that has been added
Role/Group	Role of the user that has been provided while adding the user
Is User Locked	Displays whether the user has been locked by MyCloud, post multiple failed login attempts
Is API User	Yes: user is API user No: user is organization user
Action	Provider user to take actions like edit and delete against the listed users

It also comprises of the following actions:

- **Edit** (): To modify the details of existing users.

1.5.1.2.3 Edit User

To edit/ modify user details, provider user needs to follow the following steps:

1. On the **Manage User** screen, click **View Users**.

Figure 17 - Edit User

2. Select an **Organization** and then click **Go**. Available users appear in a tabular view.
3. Click **Edit** (✎).
4. Modify the details as desired and click **Update**.

Figure 18 - Edit User (Cont.)

5. A success message box appears.




Figure 19 - User Updated Successfully

1.5.1.2.4 Import Users

To Import end users in an organization, provider users need to follow the below steps:

1. On the Import Users pane, select the Organization Name.
2. Click **Choose File** to select the csv file that has the user details.
3. Click on Import Button.

The screenshot shows the 'Manage User' interface with the 'Import Users' tab selected. It features a dropdown menu for 'Organization' (currently showing '--Select--'), a text input field for 'Import File', a 'Choose a File' button, a 'Download Template' link with a download icon, and a blue 'Import' button at the bottom.

Figure 20 – Import User

4. A success message box appears.




Figure 21 – Upload User Confirmation

To download the csv template for users, click on **Download Template** hyperlink.

1.5.1.3 Manage Group

To create a system group in an organization and map users to it, provider user needs to follow the below steps:

1. On the main menu bar, click **RBAC**, and then click **Manage Group**.
2. The **Manage Group** screen appears. It lists down the available groups in a tabular view that helps to see available groups and map users/assign group user and assign actions to them.

The screenshot shows the 'Manage Group' interface with a table listing various groups. The table has the following columns: Group ID, Name, Type, Organization Name, Map Group To, System Group, and Action. The data rows include groups like 'Business', 'IT Admin', 'Organization Admin', 'Requester', and several 'HCLOrg' and 'orgMultiGroups' entries.


Group ID	Name	Type	Organization Name	Map Group To	System Group	Action
5	Business			RBAC/AD Group / Add User	YES	
7	IT Admin			RBAC/AD Group / Add User	YES	
4	Organization Admin			RBAC/AD Group / Add User	YES	
8	Requester			RBAC/AD Group / Add User	YES	
18	1		HCLOrg	RBAC/AD Group / Add Role, Add User	NO	
19	2		HCLOrg	RBAC/AD Group / Add Role, Add User	NO	
20	3		HCLOrg	RBAC/AD Group / Add Role, Add User	NO	
13	AMGroupBA		orgMultiGroups	RBAC/AD Group / Add Role, Add User	NO	
14	BORIDENT		orgMultiGroups	RBAC/AD Group / Add Role, Add User	NO	
15	BGMHCLDUDORG		orgMultiGroups	RBAC/AD Group / Add Role, Add User	NO	
9	MyGroup		HCLOrg	RBAC/AD Group / Add Role, Add User	NO	

Figure 22 – Group Management

1.5.1.3.1 View Group

To view a group, provider user needs to follow the below steps:

1. On the **Manage Group** screen, click **View Group** against the selected group.



The screenshot shows the 'Manage Group' interface. At the top, there are two tabs: 'View Group' (selected) and 'Add Group'. Below the tabs is a table with the following columns: Group ID, Name, Tags, Organization Name, Map Group To, System Group, and Action. The table contains several rows of data, including groups like 'Business', 'IT Admin', 'Organization Admin', 'Requester', '001Group', and 'ClonetestGroup'. Each row has a set of action icons in the 'Action' column, including a status icon, an edit icon, a delete icon, and a tag icon.


















Group ID	Name	Tags	Organization Name	Map Group To	System Group	Action
5	Business			RBAC/AD Group Add User	YES	
7	IT Admin			RBAC/AD Group Add User	YES	
4	Organization Admin			RBAC/AD Group Add User	YES	
8	Requester			RBAC/AD Group Add User	YES	
30	001Group		HclOrganization	RBAC/AD Group Add Role Add User	NO	   
31	001Group		CloudOrg	RBAC/AD Group Add Role Add User	NO	   
20	ClonetestGroup	:"[]	HclOrganization	RBAC/AD Group Add Role Add User	NO	   

Figure 23 – View Group

2. Below actions are available on the screen.
 - **Change Status** (): to change status of an existing group
 - **Edit Group** (): to edit an existing group
 - **Delete Group** (): to delete an existing group
 - **Add Tags** (): to add tags in an existing group

1.5.1.3.2 Manage RBAC/AD Group Mapping

To add RBAC /AD group to the group, perform the below steps:

1. Click on **RBAC/AD Group** link under the **Map Group to** column on the grid.
2. A pop-up window prompts to map AD group to the selected RBAC group.
3. Select **Organization** to filter group specific to organization.
4. Enter Group Name.
5. Click **Search** and available AD groups appear in the available groups box.
6. Select **AD Groups** and then click on  to move selected AD groups to selected RBAC groups box or vice-versa, to unselect the ad groups from a RBAC group.




Figure 24 - Manage Group User Mapping (Cont.)

7. Click **Save**.
8. A success message box appears.



Figure 25 - Confirmation Message

1.5.1.3.3 Group User Mapping

To add user to the existing group.

1. Click on **Add User** link on the **Map Group To** column on the grid.
2. A pop-up window prompts to map users to the selected RBAC group.
3. Select **Organization** to filter user specific to organization.
4. Enter Email/ Group Name
5. Click **Search** and available users will appear in the available user box.
6. Select **Users** and then click on **>>** to move selected users to selected user box or vice-versa, to unselect the user from a RBAC group.




Figure 26 – Group User Mapping

1.5.1.3.4 Group Role Mapping

To map role to the existing group:

1. Click on **Add Role** link on the **Map Group To** column on the grid.
2. A pop-up window prompts map role to the selected RBAC group.
3. Select **Available Roles** and then click on >> to move selected roles to selected roles box or vice-versa, to unselect the roles from a RBAC group.




Figure 27 – Group Role Mapping

4. Click **Save**.
5. A success message box appears.




Figure 28 – Success Message

1.5.1.3.5 Delete Group

To delete existing RBAC group,

1. Click **Delete** from the **View Group** screen.
2. A confirmation message appears on the screen.
3. Click **OK** to proceed.



The screenshot shows a 'Manage Group' dialog box with two tabs: 'View Group' and 'Add Group'. The 'View Group' tab is active. It contains a 'Name' text field with the value 'sample' and an 'Organization Name' dropdown menu with 'HCLInfra' selected. Below these fields are 'Update' and 'Cancel' buttons.

Figure 29 – View Group





Figure 30 – Confirmation Message

1.5.1.3.6 Edit Group

To edit existing RBAC group.

1. Click **Edit** from the view group screen.
2. The below screen appears.
3. Enter **Name** to update and click **Update**.



The screenshot shows the 'Manage Group' dialog box with the 'Edit Group' tab active. The 'Name' field contains '001Group' and the 'Organization Name' dropdown is set to 'HclOrganization'. 'Update' and 'Cancel' buttons are at the bottom.

Figure 31 – Edit Group

4. A success message appears on the screen.




Figure 32 - Success Message

1.5.1.3.7 Change Status

To change status of existing RBAC group.

1. Click **Change Status** from the **View Group** screen.
2. A confirmation message appears on the screen.




Figure 33 - Confirmation Message

3. Click **OK** to confirm.




Figure 34 - Success Message

1.5.1.3.8 Add Tag

To add tags to existing RBAC group,

1. Click **Add Tags** from the **View Group** screen.
2. The below screen appears.




Figure 35 – Apply Tag(S)

3. Enter comma separated character string inside the **Tag**.
4. Click **Save**.
5. A success message appears.




Figure 36 – Success Message

1.5.1.3.9 Add Group

1. To create new group on the **Manage Group** screen, click **View Group** tab.
2. The below screen appears.




Figure 37 – Add Group

3. Enter Name and Organization
4. Click Enter Name and Select Organization
5. Click **Add**




Figure 38 - Success Message

6. Click **OK**. User will get the option to map RBAC/AD group from this screen

1.5.1.4 Transfer Object Ownership

This section explains how provider users manage to transfer object ownership in MyCloud.

1. On the main menu bar, click **RBAC** and then click **Transfer Object Ownership**.
2. The below screen appears:

A screenshot of the "Transfer Object Ownership" form in the MyCloud application. The form has a title bar with the text "Transfer Object Ownership". Below the title bar, there are five input fields arranged in two rows. The first row contains three dropdown menus: "Organization*" (with "--Select--" and a downward arrow), "Platform*" (with "--Select--" and a downward arrow), and "Provisioning Endpoint*" (with "--Select--" and a downward arrow). The second row contains two dropdown menus: "Object Type*" (with "--Select--" and a downward arrow) and "ObjectID" (a text input field). To the right of the "ObjectID" field is a text input field labeled "Requester Name". At the bottom center of the form is a blue button with the text "Submit" in white.

Figure 39 - Transfer Object Ownership

3. Select Organization, Platform, and Provisioning Endpoint.
4. Select Object Type.
5. Enter Object ID and Requester Name.
6. Click **Submit**.
7. Below screen will appear.

Transfer Object Ownership					
	ObjectID	Object Type	User Email	Lease Period	Action
<input type="checkbox"/>	002	VM			
<input type="checkbox"/>	000001	VM	krequester@hcl.com		
<input type="checkbox"/>	objectSCPlinux	VM	krequester@hcl.com		
<input type="checkbox"/>	000002	VM	krequester@hcl.com		
<input type="checkbox"/>	SonaIVM3	VM	kapiuser@hcl.com	3WEEK(S)	
<input type="checkbox"/>	SonaIVM2001	VM	krequester@hcl.com		
<input type="checkbox"/>	Machine_004	VM			
<input type="checkbox"/>	SonaIVM6	VM	customuser@hcl.com	3WEEK(S)	
<input type="checkbox"/>	TEST3	VM	customuser@hcl.com		
<input type="checkbox"/>	objectSCP	VM	krequester@hcl.com		

Records 1 - 10 of 36

First < 1 2 3 4 > Last

Figure 40 - List of Objects

8. Provider users can either transfer the multiple objects by clicking on checkbox or by individual object.
9. To change multiple object owner ship user can click on "**Transfer Object Ownership**" and for single object user can click on "**Transfer Object Ownership**" action ()
10. The following pop-up appears.

Select Owner to transfer Object

Object Transferred To*

Save

Cancel

Figure 41 - Select Owner to Transfer Object

11. Enter **Requester Name** to whom object will be transferred (auto-populated list).
12. Click **Save**.
13. The success message appears.




Figure 42 - Success Message

1.5.2 User Cost Model

This section explains how provider user manages user cost models in MyCloud.

1. On the main menu bar, click **User Cost Model**. Below screen appears.




Figure 43 - User Cost Model

1.5.2.1 Manage Service Plan

Using this interface, provider user creates service plans like platinum, gold, silver, and bronze etc. And while creating the plan, it defines services that are free of cost.

While requesting service catalog, end users need to specify the service plan that needs to be continued.

It has the following options:

- View Service Plan
- Create Service Plan
- Manage Services

1.5.2.1.1 Create Service Plan

To create a new service plan, provider user needs to follow the below steps:

1. Click on **Create Service Plan** tab.
2. Enter Service Plan Name and Description.
3. Click **Add**.




Figure 44 - Create Service Plan


4. A success message box appears.



Figure 45 - Confirmation Message

1.5.2.1.2 View Service Plan

This section lists all the service plans that have been created by a provider user.



The screenshot shows the 'Manage Service Plan' interface with three tabs: 'View Service Plan', 'Create Service Plan', and 'Manage Services'. The 'View Service Plan' tab is active, displaying a table of service plans. The table has columns for 'Service Plan Name', 'Description', 'Latest Version', 'Activation Date', and 'Action'. The data rows are as follows:

Service Plan Name	Description	Latest Version	Activation Date	Action
platinum	platinum	1.1	02/18/2022	
silver	silver	1.1	02/18/2022	
PlatinumNew	platinumNew	1.1	05/03/2022	
public cloud service plan	public cloud service plan	1.1	05/03/2022	
public cloud service plan 2	public cloud service plan 2	1.1	05/03/2022	
Gold	Gold	1.2	11/21/2022	

Below the table is a 'Sort Service Plan' button. A note at the top right of the table states: 'All dates are in mm/dd/yyyy format'.

Figure 46 - Service Plan


It also comprises of the following actions:

- **Edit** (): To modify/update the details of existing service plans
- **View** (): To view the details of existing service plans
- **Delete** (): To delete the details of existing service plans

1.5.2.1.3 Edit Service Plan

To create a new version of a service plan, the provider needs to follow the below steps:

1. Click on **Edit** ().
2. Click on **Create New Version** after changes.



The screenshot shows the 'Edit Service Plan' form. It has two tabs: 'View Service Plan' and 'Create Service Plan'. The 'Create Service Plan' tab is active. The form has two input fields: 'Service Plan Name *' and 'Description'. Both fields contain the text 'Gold'. Below the input fields are two buttons: 'Create New Version' and 'Cancel'.

Figure 47 - Edit Service Plan (Cont.)

3. A success message box appears.




Figure 48 - Confirmation Message

1.5.2.1.4 Delete Service Plan

To delete the service plan, provider needs to follow the below steps:

1. Click on **Delete** (🗑️).
2. A confirmation appears:




Figure 49 – Confirmation Query

3. Click **OK** to continue.
4. A success message box appears.




Figure 50 – Confirmation Message

1.5.2.1.5 View Service Plan Details

1. To view the details of an existing service plan, click on **View** (🔍). A screen appears as below.




Figure 51 – View Service Plan

1.5.2.1.6 Manage Services

The **Manage Services** tab lists all the configured services. Provider users can edit the service description or can delete the service from this screen.




Figure 52 - Manage Services

Manage services have edit and delete actions. These actions have similar workflow as described above in-service plan actions.

1.5.2.2 Manage Cost Model

This section explains the steps to manage the cost model of an organization which is mapped to a service plan, data center, location, and organization. Cost model is categorized as follows:

- **Allocation Based Cost:** in this type of model, the instance is reserved for the user, and the whole cost for that infra resource is being charged on the first month's bill.
- **Time Based Cost:** under such model, user is charged for the time that the infra resource is on, but storage cost is charged for the whole period i.e., 24 hours.

Along with the above cost models, provider users can also configure additional cost through in-built options like,

- **One-Time Cost:** it is the amount which is paid on a one-time basis (like amc) post availing of services (associated with either allocation or time-based cost model). This option is not mandatory and depends on organizational policies.
- **Recurring Cost:** the cost, which is occurring periodically over a time like daily, weekly, monthly, half-yearly etc. Till the services are availed (associated with either allocation or time-based cost model). This option is not mandatory and depends on organizational policies.

On the main menu bar, click **User Cost Model**, and then click **Manage Cost Model**. The section has the following options:

- Add Cost Model
- View Cost Model

1.5.2.2.1 Add Cost Model

To add a cost model for an organization, provider user needs to follow the below steps:

1. On the Manage Cost Model screen, click **Add Cost Model**.

The screenshot shows a 'Manage Cost Model' window with two tabs: 'View Cost Model' and 'Add Cost Model'. The 'Add Cost Model' tab is active. It contains a form with the following fields:

- Cost Model Name***: A text input field.
- Description***: A text input field.
- Platform***: A dropdown menu with '--Select--' as the current selection.
- Provisioning Endpoint***: A dropdown menu with '--Select--' as the current selection.
- Location/Region***: A dropdown menu with '--Select--' as the current selection.
- Currency***: A dropdown menu with '--Select--' as the current selection.
- Copy From Existing**: A checkbox.
- Existing Cost Model**: A dropdown menu with '--Select--' as the current selection.

At the bottom of the form are two buttons: 'Add' (in blue) and 'Cancel' (in grey).

Figure 53 - Add Cost Model

- Refer to the below table to understand the fields mentioned in the above figure:

Table 7 - Add Cost Model

Fields	Description
Cost Model Name	Field to add the name of a cost model
Description	Describe the cost model and how it is used
Platform	Select Platform from the drop down
Provisioning Endpoint	The cloud endpoint that has been created in MyCloud
Activation Date	The day that will activate the cost model/ billing will start against an organization
Existing Cost Model	Lists of existing cost model that were added before

- Enter Cost Model Name and then enter the Cost Model Description.
- Select the Environment, Platform, and Location.
- Select **Currency** and then enter the **Plan Activation Date**.
- Select the check box **Copy from Existing** if provider user wants to copy the cost plan from the existing cost plan.
- Select Cost Model Plan from Existing Cost Model drop-down.
- Click **Add**.

All fields marked with asterisk (*) are mandatory.

- A success message box appears.



Figure 54 - Add Cost Model (Cont.)

1.5.2.2.2 Assign Cost

Cost assignment in each category is done as steps below:

1. In the Assign Cost pane, click Define Cost against the Cost Item Category.

Cost Item Category	Allocation Based Cost
Catalog	Define Cost
Compute	Define Cost

Figure 55 - Assign Cost to The Cost Model

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 8 - Assign Cost to The Cost Model

Fields	Description
Cost Item Category	Signifies resource Category. This can be Catalog, Disk, and Network etc.

In case of allocation-based cost assignment,

- Click **Define Cost** and a pop-up appears.
- Fill the required details in **Compute Pane** and click **Save**.

Allocation Based Cost Assignment							
Compute							
General Information		One Time Cost			Recurring Cost		
Name	Unit	Daily	Applicable	Cost	Applicable	Period	Cost
Compute Unit	per unit	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>	--Select--	<input type="text"/>
Memory	GB	<input type="checkbox"/>	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>	--Select--	<input type="text"/>

Save Close

Figure 56 - Assign Cost to The Cost Model (Cont.)

3. A success message box appears.




Figure 57 - Assign Cost to The Cost Model (Cont.)

In case of time-based cost assignment,

- Click **Define Cost** and a pop-up appears.
- Fill the required details in **Compute Pane** and click **Save**.

Time Based Cost Assignment							
Compute							
General Information		One Time Cost			Recurring Cost		
Name	Unit	Per Hour Cost	Applicable	Cost	Applicable	Period	Cost
Compute Unit	per unit	<input type="text"/>	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>	--Select--	<input type="text"/>
Memory	GB	<input type="text"/>	<input type="checkbox"/>	<input type="text"/>	<input type="checkbox"/>	--Select--	<input type="text"/>

Save Close

Figure 58 - Assign Cost to The Cost Model (Cont.)

4. A success message box appears.





Figure 59 - Assign Cost to The Cost Model (Cont.)

1.5.2.2.3 View Cost Model

This section lists out all the cost models that have been created by provider users. It also comprises of the following actions:








































View Cost Model		Add Cost Model				
Cost Model Name	Description	Platform	Location/Region	Currency	Latest Version	Action
11	11	Compute on Demand-vCenter	LocationProvider	United States Dollar (USD)	1.1	   
22	22	Cisco Intersight		United States Dollar (USD)	1.1	   
AWSCostModel	AWSCostModel	Amazon Web Services	US East (N. Virginia)	United States Dollar (USD)	1.1	   
AzureCostModel	AzureCostModel	Microsoft Azure	East US	United States Dollar (USD)	1.1	   
CiscoCostModel	CiscoCostModel	Cisco Intersight		United States Dollar (USD)	1.2	   
CM 13019	s	Amazon Web Services	US East (N. Virginia)	Indian Rupee (INR)	1.1	   
CostModelHyperV	CostModelHyperV	Compute on Demand-Hyper V 2012	HyperVLocation	United States Dollar (USD)	1.1	   
CostModelPlatinum	cost model for dev environment	Cisco Intersight		United States Dollar (USD)	1.1	   

Figure 60 - View Cost Model

- **Copy Costmodel** (): To Copy existing cost models into another platform and Region/Location
- **Edit** (): To modify the details of existing cost models
- **View** (): To view the details of existing cost models
- **Delete** (): To delete existing cost model.

1.5.2.2.4 Copy Cost Model

1. Provider admin user can copy existing cost model for another provisioning endpoint and location within the same organization.
2. On the Manage Cost Model screen, click Copy Cost Model.
3. Click **Copy Cost Model** () against the cost model.






















Manage Cost Model						
View Cost Model		Add Cost Model				
Cost Model Name	Description	Platform	Location/Region	Currency	Latest Version	Action
11	11	Compute on Demand-vCenter	LocationProvider	United States Dollar (USD)	1.1	  
22	22	Cisco Intersight		United States Dollar (USD)	1.1	  
AWSCostModel	AWSCostModel	Amazon Web Services	US East (N. Virginia)	United States Dollar (USD)	1.1	  
AzureCostModel	AzureCostModel	Microsoft Azure	East US	United States Dollar (USD)	1.1	  
CiscoCostModel	CiscoCostModel	Cisco Intersight		United States Dollar (USD)	1.2	  
CM 13019	s	Amazon Web Services	US East (N. Virginia)	Indian Rupee (INR)	1.1	  
CostModelHyperV	CostModelHyperV	Compute on Demand-Hyper V 2012	HyperVLocation	United States Dollar (USD)	1.1	  

Figure 61 - Copy Cost Model

While copy cost model provider admin user can create new cost model with following information

Manage Cost Model		
View Cost Model		Add Cost Model
Cost Model Name*	Description*	Platform*
11	11	Compute on Demand-vCenter
Provisioning Endpoint*	Location/Region*	Currency*
vCenterProvisioningProvider	LocationProvider	United States Dollar (USD)
Save & Assign Cost		Cancel

Figure 62 - Copy Cost Model (Cont.)

Table 9 - List of Fields

Fields	Description
Cost Model Name	Field to add the name of a cost model
Description	Describe the cost model and how it is used
Platform	User can copy cost model to any platform
Provisioning Endpoint	User can select provisioning endpoint of selected platform
Location/Region	User can select Location/region of selected provisioning endpoint
Currency	User Can select currency supports by MyCloud

4. A confirmation message appears as below.




Figure 63 – Confirmation Message

5. To view information of existing cost models, click **View** (👁️)

Cost of applicable catalog, compute, service and storage will be copied for new cost model.

In the case of service, compute and storage exist defined cost will populate to save as new cost model and in case of catalog if catalog name will same for current endpoint then cost will pre populate to save as new cost model.

MyCloud					
Catalog					
Item			Pricing Model		
General Information			One Time Cost	Recurring Cost	
Name	Unit	Daily	Cost	Period	Cost
0. for testing update case	PER UNIT	<input type="text"/>	<input type="text"/>	--Select--	<input type="text"/>
1. for testing update case	PER UNIT	<input type="text"/>	<input type="text"/>	--Select--	<input type="text"/>
11528_Kislay_DeleteCI	PER UNIT	<input type="text"/>	<input type="text"/>	--Select--	<input type="text"/>
11528_UpdateCI_Kislay	PER UNIT	<input type="text"/>	<input type="text"/>	--Select--	<input type="text"/>
123	PER UNIT	<input type="text"/>	<input type="text"/>	--Select--	<input type="text"/>
abhishek	PER UNIT	<input type="text"/>	<input type="text"/>	--Select--	<input type="text"/>
Abhishek_Test	PER UNIT	<input type="text"/>	<input type="text"/>	--Select--	<input type="text"/>
AnsibleTower_FBI_9840_Abhishek	PER UNIT	<input type="text"/>	<input type="text"/>	--Select--	<input type="text"/>

Figure 64 – Catalog

1.5.2.2.5 Edit Cost Model

To edit/ modify cost models, provider user needs to follow the below steps:

1. On the Manage Cost Model screen, click View Cost Model.
2. Click **Edit** (✎) against the cost model which requires modifications.

























Manage Cost Model						
View Cost Model		Add Cost Model				
Cost Model Name	Description	Platform	Location/Region	Currency	Latest Version	Action
123	Desc - 123	Compute on Demand-vCenter	vCenter Location	Indian Rupee (INR)	1.1	  
a10	a10	Cisco Intersight		Indian Rupee (INR)	1.1	  
a11	a12	Cisco Intersight		Indian Rupee (INR)	1.1	  
a15	a15	Cisco Intersight		United States Dollar (USD)	1.1	  
a16	a16	Cisco Intersight		United States Dollar (USD)	1.1	  
a2	a2	Cisco Intersight		United States Dollar (USD)	1.2	  
a20	a20	Cisco Intersight		Indian Rupee (INR)	1.1	  
a3	a3	Cisco Intersight		United States Dollar (USD)	1.1	  

Figure 65 – Edit Cost Model

3. Modify the details as required and then click **the New Version**.

Manage Cost Model			
View Cost Model		Add Cost Model	
Cost Model Name*	Description*	Platform*	
GCP cost Model	GCP cost Model	Google Cloud (GCP)	
Provisioning Endpoint*	Location/Region*	Currency*	
GcpDev	Los Angeles, California, USA	INR	
		New Version	Cancel


Assign Cost	
Cost Item Category	Time Based Cost
Storage	Define Cost
GCP Chargeable Component	Define Cost

Figure 66 – Edit Cost Model (Cont.)


4. A confirmation message appears as below.



Figure 67 – Confirmation Message

To view information of existing cost models, click **View** ()

1.5.2.2.6 Delete Cost Model

1. To delete Existing Cost Model, click on Delete Action ()
2. A confirmation message appears.




Figure 68 – Confirmation Cost Model

1.5.2.3 Cost Model Mapping

To map a cost model with service plan, platform, environment, location, and organization, provider user needs to follow the below steps:

1. On the main menu bar, click **User Cost Model** and then click **Cost Model Mapping**.
2. To map a cost model with an organization, follow the steps below:
3. On the Map Cost Model screen, click Add Cost Mapping.
4. Select the Organization, Platform, Provisioning Endpoint, Location/Region, Cost Model and Service Plan.
5. Click **Save** to map a cost model and click **Cancel** to discard changes.

 A screenshot of the "Cost Model Mapping" form. The form has a blue header bar with the text "Cost Model Mapping". Below the header, there are two tabs: "Manage Cost Mapping" and "Add Cost Mapping". The "Add Cost Mapping" tab is active. The form contains six dropdown menus arranged in two rows. The first row contains "Organization*", "Platform*", "Provisioning Endpoint*", and "Location/Region*". The second row contains "Cost Model*" and "Service Plan*". Each dropdown menu has a "--Select--" option. At the bottom of the form, there are two buttons: "Save" and "Cancel".

Figure 69 – Cost Model Mapping

6. A success message box appears.





Figure 70 – Cost Model Mapping (Cont.)

All the fields marked with asterisk (*) are mandatory.

1.5.2.3.1 View Mapping

This section lists out all the cost models that have been created by provider users.



Organization	Service Plan	Platform	Location/Region	Cost Model	Action
HCLorg	Private Cloud master-data	Compute on Demand-vCenter	vCenter Location	Private Cloud Master-data	
HCLorg	Public cloud Service Plan	Amazon Web Services	US East (N. Virginia)	AWS Cost Model	
HCLorg	Public cloud Service Plan	Google Cloud Platform	Mumbai, India	GCP Cost Model	
HCLorg	Public cloud Service Plan	Microsoft Azure	East US	Azure Cost Model	
HCLorg	Private Cloud master-data	Compute on Demand-Hyper V 2012	HyperV Location	Private Cloud HyperV	
HCLorg	Service Plan1	Compute on Demand-vCenter	vCenter Location	Test_Model_PBI_8628	
HCLorg	Public cloud Service Plan	Cisco Intersight		Cost Model - Cisco Intersight	
HCLorg	Service Plan1	Cisco Intersight		cisco - \$	


Figure 71 - Delete Cost Model Mapping

It also comprises of the following action:

- **Delete** (): To delete the existing cost model

1.5.2.3.2 Delete Cost Model Mapping

To delete the mapped cost model, provider user needs to follow the below steps:

1. On the Manage Cost Mapping tab, click Delete (.
2. When prompted to confirm, click **Ok**.




Figure 72 - Delete Cost Model Mapping (Cont.)

1.5.3 Service Catalog

Service catalog allows the provider to centrally manage commonly deployed MyCloud services and contains a set of cloud services that an end user requests. It helps MyCloud to meet compliance requirements, while helping providers to quickly deploy only the approved services that end users require.

1. On the main menu bar, click **Service Catalog**.
2. The drop-down appears with the following options:
 - **Manage Action**
 - **Manage Blueprint**
 - **Manage Catalog**
 - **Publish Action**
 - **Publish Service Catalog**




Figure 73 – Service Catalog

1.5.3.1 Manage Catalog

This section details out the process of managing a catalog.

It has the following sections:

- Create Catalog
- View Catalog

1.5.3.1.1 Create Catalog

To create a catalog, provider user needs to follow the steps below:

1. On The Manage Catalog screen, click Create Catalog.

 The screenshot shows the 'Manage Catalog' form with the 'Create Catalog' tab selected. The form contains several fields: 'Platform' (dropdown menu with 'Compute on Demand-vCenter'), 'Provisioning Endpoint' (dropdown menu with 'vCenterProvisioning'), 'Template' (dropdown menu with 'PlyushCloudTempAPIPassword'), 'Region' (dropdown menu with 'vCenter Region'), 'Catalog Name' (text input with 'Catalog_1'), and 'Catalog Description' (text area with 'Description for catalog_1'). There are also 'Save' and 'Cancel' buttons at the bottom right.

Figure 74 – Create Catalog

2. Select Platform and Provisioning Endpoint.
3. Select **Template**.
4. Select **Region**.
5. Enter Catalog Name and Catalog Description.
6. To add a catalog, click **Save**.

Click **Cancel** to discard changes and all the fields marked with asterisk (*) are mandatory.

7. A success message box appears:



Figure 75 - Create Catalog Success Message

8. The new catalog is created and appears in the list of catalogs.

All the fields marked with asterisk (*) are mandatory.

1.5.3.1.2 View Catalog

This section lists all the catalogs that have been created by provider user.

Manage Catalog

View Catalogs Create Catalog

Platform * Provisioning Endpoint * Catalog Name

Catalogs

Catalog Name	Description	Associated Template	Created By	Action
16611_Ungroup_Task	16611_Ungroup_Task	mycl-win2k12	HCL Provider	
Approval 2	Approval 2	mycl-win2k16	HCL Provider	
Approval Catalog	Approval Catalog	mycl-win2k12	HCL Provider	
Approval workflow	Approval workflow	Approval workflow	HCL Provider	
Catalog - ControlVisibilityByFunction	Catalog - ControlVisibilityByFunction	mycl-win2k12	HCL Provider	

Figure 76 - View Catalog

It also comprises of the following actions:

- **Change Status** (): To change the status (**Active/Inactive**) of an existing catalog.
- **Edit** (): To modify the details of an existing catalog.
- **Delete** (): To delete a catalog.

1.5.3.1.3 Edit Catalog

To edit/ modify information of an existing catalog, provider user needs to follow the below steps:

1. On the Manage Catalog screen, click View Catalog.
2. Select Platform and Provisioning Endpoint.
3. Select Catalog Name.
4. Click **Go**.

Manage Catalog

View Catalogs Create Catalog

Platform * Compute on Demand-vCenter Provisioning Endpoint * vCenterProvisioning Catalog Name

Go

Catalogs












Catalog Name	Description	Associated Template	Created By	Action
16611_Ungroup_Task	16611_Ungroup_Task	mycl-win2k12	HCL Provider	 
Approval 2	Approval 2	mycl-win2k16	HCL Provider	 
Approval Catalog	Approval Catalog	mycl-win2k12	HCL Provider	 
Approval workflow	Approval workflow	Approval workflow	HCL Provider	 
Catalog - ControlVisibilityByFunction	Catalog - ControlVisibilityByFunction	mycl-win2k12	HCL Provider	 

Figure 77 – Edit Catalog

- Available catalogs list down in a tabular view.
- Click **Edit** ().
- Modify the details as desired and click **Update**.
- Click **Cancel** to discard all changes.

Manage Catalog

View Catalogs Create Catalog

Platform * Compute on Demand-vCenter Provisioning Endpoint * vCenterProvisioning Template * MyCloudTempAPIPassword

Region * vCenter Region Catalog Name * Catalog_1 Operating System N/A

Catalog Description * Description for catalog_1

Update Cancel

Figure 78 – Edit Catalog (Cont.)

- A success message box appears:




Figure 79 – Edit Catalog Success Message

1.5.3.1.4 Delete Catalog

To delete a catalog from the platform, provider users need to follow the below steps:

1. On the **Catalog** pane, click **Delete** ().


Catalogs					
Catalog Name	Description	Platform	Status	Created By	Action
Catalog1_VMware	Description - Catalog for VMware.	Compute on Demand-vCenter	Active	pvd demo	

Figure 80 - Delete Catalog

2. When prompted to confirm, click **OK**.




Figure 81 - Delete Catalog (Cont.)

3. A success message box appears:




Figure 82 - Delete Catalog Success Message

1.5.3.2 Publish Service Catalog

This section emphasizes how to publish service catalogs for end-user of an organization and align dynamic UI fields that are mentioned in **Manage Cloud Templates**. Provider user adds a custom image to service catalogs.

It has following Options:

- Create Service Catalog
- View Service Catalog

1.5.3.2.1 Create Service Catalog

To publish a new service catalog from imported template of an organization, provider user needs to follow the below steps:

1. On the Publish Service Catalog screen, click Create Service Catalog tab.

Figure 83 - Create Service Catalog

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 10 - Create Service Catalog Fields

Fields	Description
Organization	The name of the organization (business units/ divisions in organizations)
Platform	The name of cloud service providers
Environment	The cloud endpoints that have been created in MyCloud
Catalog Type	This lists the different types of catalogs
Catalog	Name of the catalog
Service Type	Lists all service types that are created
Service Name	Name of service
Object Type	Type of object that will be provisioned
Process Template Workflow	This is the template for orchestrating tasks sequence
Max. Number of Instances	This template has max no. of instances.
Draft Applicable	To enable draft button on service request.
Cost Applicable	To enable cost button, user must ensure that UI template must defined JavaScript function showcost ().
Request For Applicable	To enable "request for" option, this will help user to create request on behalf of another user.
Generate API Json Applicable	To enable generate API JSON button on service request. It helps user to generate API JSON.

SLA Applicable	To enable "SLA (in mins)" option.
Allow Document Upload	This will enable the document upload functionality on requester form.
Architecture Diagram	After saving the image from Publish Service Catalog, same image will display on requester side in first tab when dynamic form will open for requester. If requester will place a request, then this diagram will be applicable for that request, and if provider delete or change the image at service catalog it will not impact on placed request.

3. Select Organization.
4. Select **Platform**.
5. Select Provisioning Endpoint.
6. Select **Catalog**.
7. Select Service Type and Service Name.
8. Select Object Type.
9. Enter **Short Description** and **Description** of the catalog.
10. Select Process Template Workflow.
11. Select Maximum number of Instances.
12. Upload image file for **Catalog Logo**.
13. To publish a catalog, click **Create**.

Click cancel to discard changes. All fields marked with asterisk (*) are mandatory.

14. A success message box appears:




Figure 84 - Publish Service Catalog Confirmation Message

15. The new service catalog is published and appears in the list of service catalogs.

1.5.3.2.2 View Service Catalog

This section lists all service catalogs that have been created by provider user.






Figure 85 - View Published Service Catalog

It also comprises of the following actions:

- **Edit** (

1.5.3.2.3 Edit Service Catalog

To edit/ modify the information of an existing service catalog, provider user needs to follow the below steps:

1. On the Publish Service Catalog screen, click View Service Catalog pane.
2. Select Organization.
3. Select Platform and Provisioning Endpoint.
4. Select Service Type.
5. Click **Go**.
6. Available catalogs list down in a tabular view.
7. Click **Edit** () against the Published Service Catalog to be edited.

Service Name	Associated Process Template	Associated UI Template	Service Type	Catalog Name	Tags	Action
Vcenter Service	VMwareTemplate1980 (Version 1)	VMwareUITemplate_Sonal	NA	VcenterCatalog	Tag1,Tag2	[Icons]
Window2019	VMwareTemplate1980 (Version 1)	VMwareUITemplate_Sonal	NA	Window2019		[Icons]
test	Action Process (Version 1)	Action UI	NA	test		[Icons]
test1	test (Version 1)	testui	NA	Windows Server 2008		[Icons]

Figure 86 - Edit Published Service Catalog

8. Modify the details as desired and click **Update**.
9. Click **Cancel** to discard all changes.

Figure 87 - Edit Public Service Catalog (Cont.)

10. A success message appears:




Figure 88 - Edit Catalog Confirmation Message

1.5.3.2.4 Publish Service Catalog Export/Import

Export:

To export a service catalog, provider needs to select **Organization**, **Platform**, and **Endpoint** as per the mandatory check and click on export icon under the **Action** column.

Publish Service Catalog

View Service Catalog | Publish Service Catalog | Import Service Catalog | Service Catalog Library

Organization * Platform * Provisioning Endpoint * Service Type

Service Name Tags

Go

Service Name	Associated Process Template	Associated UI Template	Service Type	Catalog Name	Tags	Action
Vcenter Service	VMwareTemplate1980 (Version 1)	VMWABUITemplate_Sonal	NA	VcenterCatalog	Tag1,Tag2	
Window2019	VMwareTemplate1980 (Version 1)	VMWABUITemplate_Sonal	NA	Window2019		
test:	Action Process (Version 1)	Action UI	NA	test:		
test1	test (Version 1)	testui	NA	Windows Server 2008		

Figure 89 – Publish Service Catalog Export

Import:

To import a service catalog, select the **Import Service Catalog** tab in the **Publish Service Catalog** screen and perform the following steps:

1. Upload File
 - Provide the preliminary information (**Organization**, **Platform**, **Provisioning Endpoint**, and **Upload File**) that is mandatory. If not provided, then it would trigger a validation message.

Publish Service Catalog

View Service Catalog | Publish Service Catalog | Import Service Catalog | Service Catalog Library

Step 1: Upload File → Step 2: Cloud Template → Step 3: Catalog → Step 4: Approval Definition → Step 5: UI Template → Step 6: Process Template → Step 7: Publish Service Catalog → Step 8: Custom Table Import → Step 9: Preview and Submit

Step 1 Upload File


Organization * Platform * Provisioning Endpoint * Upload File * **Choose a file**

Note: Import the Zip file for Publish Service Catalog.

Next

Figure 90 – Publish Service Catalog Import

While Importing JSON template, region must be mapped with the selected end point region. Failing this, results to a validation message as shown in the figure below:



If Object Type does not exist in current environment as per the imported Zip File, then it will show the validation message as Object Type does exist.

When we import the zip for all the steps then it checks inactive Resources for all the steps and if it is inactive they will show the validation message for the same to active or delete the element to proceed with import.

2. Cloud Template

- **Public Cloud** – In the case of public cloud, if user selects the **Map & Overwrite** option as **Import Type**, it will overwrite the existing information from the selected zip file and map with same. But if the user selects the **Map Only** option, it only maps the template with existing information and do not overwrite to existing one.

If no matches occur, then only 'NEW' option appears, and it creates a new template as per the imported information.

- **Private Cloud** – In the case of private cloud, the **NEW** option never appears and **Map & Overwrite** and **Map Only** options work similarly as in the case of Public Cloud.

Publish Service Catalog

View Service Catalog Publish Service Catalog **Import Service Catalog** Service Catalog Library

Step 1: Upload File Step 2: Cloud Template Step 3: Catalog Step 4: Approval Definition Step 5: UI Template Step 6: Process Template Step 7: Publish Service Catalog Step 8: Custom Table Import Step 9: Preview and Submit

Organization: HclOrganization Platform: Google Cloud Platform Provisioning Endpoint: GCPProvisioningEndpoint

Step 2: Cloud Template

Import Type *

☒ Map & Overwrite ☐ Map Only

Template Name *

Manage Cloud Template - GCP

Map & Overwrite- The information as per imported Package will overwrite to existing one.
Map Only- As per imported Package, the information will map only with existing one, not be overwritten.

Note-

- Please select existing Template after import to MyCloud.
- Template password will not be imported. User has to update the password manually.

Back Next

Figure 91 – Publish Service Catalog Import

3. Once the **Import Type** is specified, click **Next**.
4. **Catalog:** In the case of **Public Cloud**, it works as it per previous. In the case of **Private Cloud**, it comes as per the cloud template selected in **step 1**. If the selected template is not mapped with catalog, it shows a validation message.
 - **Catalog Exists in the Current Environment** – It works as **step 1**. If the user selects a cloud template which is mapped with the catalog to be imported, then it comes as auto selected or is available in the dropdown to select the mapped catalog.
 - **Catalog does not exist in the Current Environment** – If catalog does not exist in the current environment, then it will be available for 'New' creation.

Publish Service Catalog

View Service Catalog Publish Service Catalog **Import Service Catalog** Service Catalog Library

Step 1: Upload File Step 2: Cloud Template (Manage Cloud Template - GCP (Map & Overwrite)) **Step 3: Catalog** Step 4: Approval Definition Step 5: UI Template Step 6: Process Template Step 7: Publish Service Catalog Step 8: Custom Table Import Step 9: Preview and Submit

Organization: HclOrganization Platform: Google Cloud Platform Provisioning Endpoint: GCPProvisioningEndpoint

Step 3 Catalog

Import Type *
☒ Map & Overwrite ☐ Map Only

Catalog Name *
 GCP New Account

Map & Overwrite- The information as per imported Package will overwrite to existing one.
Map Only- As per imported Package, the information will map only with existing one, not be overwritten.

Back Next

Figure 92 – Publish Service Catalog Import

5. Click **Next**.
6. Approval Definition
 - **Static Approval** – If static approval is mapped with the Imported info, then it follows the same process as for Public Cloud explained in **step 2** for **NEW**, **Map & Overwrite** and **Map Only** options.
 - **Dynamic Approval** – If user has imported the dynamic rule, the drop down works as static but there will be a list of static templates which are tagged to dynamic rule and appear with same action as **New**, **Map & Overwrite** and **Map only** options.

Publish Service Catalog

View Service Catalog Publish Service Catalog **Import Service Catalog** Service Catalog Library

Step 1: Upload File Step 2: Cloud Template (Manage Cloud Template - GCP (Map & Overwrite)) Step 3: Catalog (GCP New Account (Map & Overwrite)) **Step 4: Approval Definition** Step 5: UI Template Step 6: Process Template Step 7: Publish Service Catalog Step 8: Custom Table Import Step 9: Preview and Submit

Organization: HclOrganization Platform: Google Cloud Platform Provisioning Endpoint: GCPProvisioningEndpoint

Step 4 Approval Definition

Import Type *
☒ Map & Overwrite ☐ Map Only

Approval Template Name *
 BA

Map & Overwrite- The information as per imported Package will overwrite to existing one.
Map Only- As per imported Package, the information will map only with existing one, not be overwritten.

Back Next

Figure 93 – Publish Service Catalog Import

7. Click **Next**.
8. **UI Template**: The UI Template Import works similarly as for Public Cloud explained in **step-2** as per the given action.

Publish Service Catalog

View Service Catalog | Publish Service Catalog | **Import Service Catalog** | Service Catalog Library

Step 1: Upload File | Step 2: Cloud Template | Step 3: Catalog | Step 4: Approval Definition | **Step 5: UI Template** | Step 6: Process Template | Step 7: Publish Service Catalog | Step 8: Custom Table Import | Step 9: Preview and Submit

Organization: HclOrganization Platform: Google Cloud Platform Provisioning Endpoint: GCPProvisioningEndpoint

Step 5 UI Template

Import Type * ☒ Map & Overwrite ☐ Map Only

UI Template * GCP New Account

ITSM Configuration	Action
Configuration_Abhishek	<input checked="" type="radio"/> Map & Overwrite <input type="radio"/> Map Only

Map & Overwrite- The information as per imported Package will overwrite to existing one.
 Map Only- As per imported Package, the information will map only with existing one, not be overwritten.

[Back](#) [Next](#)

Figure 94 – Publish Service Catalog Import

If provider user exports any published service catalog, then all existing custom JS functions using in the UI should also be export with existing UI JSON (manageuitemplate.json). Similarly, if provider user imports any publish service catalog, then all custom JS functions (using in the mapped UI) should also be import.

9. Process Template

- **Process templates** – It works similarly as for Public Cloud explained in **step-2** for the imported information.
- This screen also contains the ITSM information which has been imported in **step-1** ith the same action as **NEW, Map & Overwrite** and **Map Only**.

Publish Service Catalog

View Service Catalog | Publish Service Catalog | **Import Service Catalog** | Service Catalog Library

Step 1: Upload File | Step 2: Cloud Template | Step 3: Catalog | Step 4: Approval Definition | Step 5: UI Template | **Step 6: Process Template** | Step 7: Publish Service Catalog | Step 8: Custom Table Import | Step 9: Preview and Submit

Organization: HclOrganization Platform: Google Cloud Platform Provisioning Endpoint: GCPProvisioningEndpoint

Step 6 Process Template

Import Type * ☒ Map & Overwrite ☐ Map Only

Process Template Name * GCP New Account

ITSM Configuration	Action
Configuration_Abhishek	<input checked="" type="radio"/> Map & Overwrite <input type="radio"/> Map Only

Map & Overwrite- The information as per imported Package will overwrite to existing one.
 Map Only- As per imported Package, the information will map only with existing one, not be overwritten.
 Note- ITSM user password will not be imported. User has to update the password manually.

[Back](#) [Next](#)

Figure 95 – Publish Service Catalog Import

10. Click **Next**.

11. Publish Service Catalog

- It publishes the service catalog information for the imported information and works as for public cloud explained in **Step-2**.

Publish Service Catalog

View Service Catalog | Publish Service Catalog | **Import Service Catalog** | Service Catalog Library

Step 1: Upload File | Step 2: Cloud Template | Step 3: Catalog | Step 4: Approval Definition | Step 5: UI Template | Step 6: Process Template | **Step 7: Publish Service Catalog** | Step 8: Custom Table Import | Step 9: Preview and Submit

Organization: H3Organization Platform: Google Cloud Platform Provisioning Endpoint: GCPProvisioningEndpoint

Step 7 Publish Service Catalog

Import Type * ☒ Map & Overwrite ☐ Map Only

Publish Service Catalog * GCP New Account

Service Type * SaaS

Map & Overwrite: The information as per imported Package will overwrite to existing one.
Map Only: As per imported Package, the information will map only with existing one, not be overwritten.

Back Next

Figure 96 – Publish Service Catalog Import

12. Click **Next**.

13. Preview and Submit

- This screen displays the summary of all the steps which the user have selected. There is a **Submit** button to process all the information related to Imported and Selected information.
- If any error occurs while processing, it shows an error message on the same **Summary** page.

Publish Service Catalog

View Service Catalog | Publish Service Catalog | Import Service Catalog | **Service Catalog Library**

Step 1: Upload File | Step 2: Cloud Template | Step 3: Catalog | Step 4: Approval Definition | Step 5: UI Template | Step 6: Process Template | Step 7: Publish Service Catalog | Step 8: Custom Table Import | **Step 9: Preview and Submit**

Organization: H3Organization Platform: Google Cloud Platform Provisioning Endpoint: GCPProvisioningEndpoint

Step 9 Preview and Submit

Resource Order	Action	Target Value
Cloud Template	Map & Overwrite	Manage Cloud Template - GCP
Catalog Details	Map & Overwrite	GCP New Account
Approval Definition	Map & Overwrite	BA
UI Template	Map & Overwrite	GCP New Account
UI Details	N/A	1. Configuration, Admins (Map & Overwrite)
Import Process Template	Map & Overwrite	GCP New Account
Publish Service Catalog	Map & Overwrite	GCP New Account

Note: It is preview of selected workflow. After submitting the modifications will be done accordingly.

Back Submit

Figure 97 – Preview and Submit

14. Click **Submit**. The system confirms the action. Click **OK** to confirm.





Figure 98 – Confirmation Message

1.5.3.2.5 Delete Published Catalog

To delete a service catalog, the provider needs to follow the below steps:

1. On **View Service Catalog** pane, click Delete ().



















Service Name	Associated Process Template	Associated UI Template	Service Type	Catalog Name	Tags	Action
Vcenter Service	 VMwareTemplate1980 (Version 1)	VMWARUITemplate_Sonal	NA	VcenterCatalog	Tag1,Tag2	  
Window2019	 VMwareTemplate1980 (Version 1)	VMWARUITemplate_Sonal	NA	Window2019		  
test	 Action Process (Version 1)	Action UI	NA	test		  
test1	 test (Version 1)	testui	NA	Windows Server 2008		  

Figure 99 - Delete Published Service Catalog

2. When prompted to confirm, click **OK**.




Figure 100 - Delete Published Service Catalog

3. A success message box appears:




Figure 101 - Confirmation Message

1.5.3.2.6 Copy Service Catalog to Other Region

To Copy a service catalog for Other Region, provider needs to follow the below steps:


1. On **View Service Catalog** pane, click Copy to Other Region ().

Figure 102 – Copy Service Catalog to Other Region

2. When prompted to confirm, click **OK**.




Figure 103 – Success Message

1.5.3.2.7 Copy Service Catalog to Other Endpoint

To copy a service catalog, provider needs to follow the below steps:

1. On **View Service Catalog** pane, click Copy to Other Endpoint (📄).

	Provisioning Endpoint	Publish Service Catalog	Template	Catalog
<input checked="" type="checkbox"/>	JFunctionEndpoint	VMware - Testing	mycl-win2k16	VMware - Testing
<input type="checkbox"/>	SDKmmwaredev01	VMware - Testing	--Select--	VMware - Testing
<input type="checkbox"/>	TestOne	VMware - Testing	--Select--	VMware - Testing
<input type="checkbox"/>	VMwarePerfEndpoint	VMware - Testing	--Select--	VMware - Testing

Figure 104 – Copy Published Service Catalog to Other Endpoint

2. When prompted to confirm, click **OK**.




Figure 105 – Success Message

1.5.3.2.8 Service Catalog Library

This section lists out of box catalog library to import.




Figure 106 – Service Catalog Library

Select a platform and click the GO button. List of existing Service Catalog Library shown below :-




Figure 107 – List of Existing Service Catalog Library

Select a Service Catalog Library and click on Import Button the page redirect to Import Service Catalog Tab.




Figure 108 – Import Service Catalog by Existing Service Catalog Library

Select an Organization, Platform automatic selected as per existing Service Catalog Library and Select a Provisioning Endpoint then click **Next** button.




Figure 109 – Import Service Catalog by Existing Service Catalog Library

After that Refer to 1.5.3.2.4 Section for Import Service Catalog.

1.5.3.3 Publish Action

Through this module, a provider user can map action and respective process workflow templates to an object type like Virtual Machine (VM), load balancer, RDS etc. For an organization. The workflow will be triggered or executed after an action request is placed on an object (once it gets provisioned).

1.5.3.3.1 Create Publish Action

To add a publish action in MyCloud, provider user needs to follow the below steps:

1. Click **Publish Action** under Service Catalog menu and then click Create Publish Action.

Figure 110 - Publish Action

2. Select **Organization**.
3. Select **Platform**.
4. Select **Object Type**.
5. Select **Action**.
6. Select **Process Template Workflow**.
7. Enter **Tags**.
8. Select **Filter Type**, **Filter Operators**, **Filter Value** for rule filters.
9. To map the publishing action to selected object type, click **Create**.
10. A success message box appears.




Figure 111 - Add Publish Action (Cont.)

All the fields marked with asterisk (*) are mandatory. Click reset to discard changes.

11. The **Publish Action** is created and appears.

1.5.3.3.2 View Publish Action

This section lists out all the object actions that have been created by provider user.

Organization *	Platform *	Object Type					Save Sequence
hclorg	Compute on Demand-vCenter	--All--					
Go							
Action Name	Object Type	Associated Process Template	Generate API Json	Schedulable Action	Sequence	Action	
ActionPiyush1	Virtual Machine	TempTestPiyush1 (Version 1)	No	Yes	↑↓	✎ 🗑 ⚙	
ActionPiyush2	Virtual Machine	TempTestPiyush2 (Version 1)	No	Yes	↑↓	✎ 🗑 ⚙	
ActPiyush4	Virtual Machine	TempProcessPiyush4 (Version 1)	Yes	Yes	↑↓	✎ 🗑 ⚙	

Figure 112 - View Action

It also comprises of the following actions:

- **Edit** (✎): To modify the details of existing object actions
- **Delete** (🗑): To delete the actions of existing objects
- **Configure Conflict Action** (⚙): To configure the conflict action settings.
- **Configure Export Action** (📄): To Export the Publish action with all depended resources .

1.5.3.3.3 Edit Published Action

To edit/ modify an assigned publish action in MyCloud, provider user needs to follow the below steps:

1. On the Publish Action screen, click View Publish Action.
2. The Edit Pane appears as shown in **Figure 113 - Edit Action (Cont.)**.
3. Click **Edit** (✎) against the **Publish Action** to be edited. It redirects the user to **Create Publish Action** pane.
4. Modify the details as desired and click **Update**.

Publish Action

View Publish Action
Publish Action

Organization *
hclorg

Platform *
Amazon Web Services

Object Type *
Amazon Kubernetes Cluster

Action *
ActionCreatedByPiyushToTestActionColumnScatterer

Process Template Workflow *
Process_BPCiscolntersight Testing AWS (Version 1)

Tags

☒ Display Action ⓘ
☐ Change Window ⓘ
☐ SLA Applicable ⓘ

☐ Generate API Json ⓘ
☐ Allowed In Grace Period ⓘ

☐ Schedulable Action ⓘ
☐ IT Verification Enabled ⓘ

Filters

Filter Types
Filter Operator
--Select--
Filter Value

Update
Cancel

Figure 113 - Edit Action (Cont.)

5. A success message box appears.




Figure 114 - Confirmation Message

1.5.3.3.4 Delete Action

To delete a publish action from MyCloud, provider user needs to follow the below steps:

1. On the **View Publish Action** pane, click **Delete** (🗑️).

 A screenshot of the "View Publish Action" pane in MyCloud. It features a table with the following columns: Action Name, Object Type, Associated Process Template, Generate API Json, Schedulable Action, Sequence, and Action. There are three rows of data. To the right of the table is a "Save Sequence" button.

Action Name	Object Type	Associated Process Template	Generate API Json	Schedulable Action	Sequence	Action
ActionPiyush1	Virtual Machine	TempTestPiyush1 (Version 1)	No	Yes	↑↓	✎ 🗑️ ⚙️
ActionPiyush2	Virtual Machine	TempTestPiyush2 (Version 1)	No	Yes	↑↓	✎ 🗑️ ⚙️
ActPiyush4	Virtual Machine	TempProcessPiyush4 (Version 1)	Yes	Yes	↑↓	✎ 🗑️ ⚙️

Figure 115 - Delete Object Action

2. When prompted to confirm, click **OK**.




Figure 116 - Delete Object Action

3. A success message box appears.



Figure 117 - Confirmation Message

4. Click **OK**.

1.5.3.3.5 Export Publish Action

To Export a published action from MyCloud, provider user needs to follow the below steps:

1. On the **View Publish Action** pane, select organization and platform click Export Action ().




Figure 118 – Publish Action

2. After clicking the export button open custom table export window.






Figure 119 – Publish Action Export

3. In the Export Window If you need to select the table name available in the custom table section, move to the selected custom tables section, and after that, click the export button to export a JSON zip folder.

1.5.3.3.6 Configure Conflict Action

To configure an object action from MyCloud, provider user needs to follow the below steps:

1. On the View Publish Action pane, click Configure Conflict Action ().



















Action Name	Object Type	Associated Process Template	Generate API Json	Schedulable Action	Sequence	Action
Demo Generic Filter	Virtual Machine	Tagtest (Version 1)	No	Yes	↑↓	  
testNavin	Virtual Machine	Azure 23 May template (Version 1)	No	No	↑↓	  
Navintest1	Virtual Machine	Azure 23 May template (Version 1)	No	No	↑↓	  
navintest2	Virtual Machine	Azure 23 May template (Version 1)	No	No	↑↓	  
Sonal_Action	Virtual Machine	11 (Version 1)	No	No	↑↓	  

Figure 120 - Configure Conflict Action



Configure Conflict Action : Virtual Machine

Kindly check conflicted action for **Virtual Machine**, i.e. If checked actions are under fulfillment then request for **Virtual Machine** could not be placed.

<input type="checkbox"/>	Action Name
<input type="checkbox"/>	Demo 28 Generic Filter
<input type="checkbox"/>	DemoFilterAction
<input type="checkbox"/>	testNavin
<input type="checkbox"/>	Navintest1
<input type="checkbox"/>	navintest2
<input type="checkbox"/>	Sonal_Action
<input type="checkbox"/>	sonal_test

Save Close

Figure 121 - Configure Conflict Action (Cont.)

- Click on the checkbox and **Save** to configure the **Conflict Action**.

1.5.3.3.7 Import Publish Action

- New:** When imported, key information does not exist in the current environment based on required parameters such as platform, provider, object type, etc. It will create a new entry for the ongoing step as per the selected Zip file.
- Map & Overwrite:** When imported information already exists in the current environment, it will appear, and on selection, it will overwrite the existing information from the selected Zip file.
- Map Only:** When imported information already exists in the current environment, it will appear, and on selection, it will map with the existing information and not overwrite the existing one.

To Import a published action from MyCloud, provider user needs to follow the below steps:

Step- 1 - Upload File: User need to select preliminary information that is mandatory if not then it would trigger a validation message. As mentioned below:

- Organization: Select the organization where you need to import the published action.
- Platform: Select the platform where you need to import the published action.
- Upload: Click the upload file button and choose import zip file for import.

Figure 122 – Upload File

If a user does not select an organization or platform, and clicks the next button, then the alert message below will be shown.

- **When organization is not selected**




Figure 123 – Organization Not Selected

- **When Platform is not selected**




Figure 124 – Platform Not Selected

- **When uploaded file is not a Zip folder**




Figure 125 – Invalid Zip File

When an invalid zip file that is imported and is not mapped to the correct platform, the alert message shown below appears.

- **When a zip file without valid content is uploaded.**




Figure 126 – Incorrect Zip File/Content

- **When selected platform and uploading zip file platform are not the same.**




Figure 127 – Platform Name does Not Match

Click on **Next** to validate that the object type exists for which the publish action import is being processed and it will show the validation message for the same.




Figure 128 – Validation Message

Step 2 – Approval Definition

- **Approval Exists in the Current Environment:** If Approval exists in the current environment, Map Only and Map & Overwrite options will available.
- **Approval does not Exist in the Current Environment:** If Approval does not exist in the current environment, then it will be available for "NEW" creation.
- **Approval does not Exist in the Current Environment:** If approval does not exists in the imported file then it will skip the approval definition step and it goes to UI template step.




Figure 129 – Approval Definition

Step 3 – UI Template

- **UI Template Exists in the Current Environment:** If UI Template exists in the current environment, Map Only and Map & Overwrite only options are available.
- **UI Template does not Exist in the Current Environment:** If Approval does not exist in the current environment, then it will be available for "NEW" creation.

Publish Action

View Publish Action Publish Action Import Publish Action

Step 1: Upload File Step 2: Approval Definition
BA+IT (Map & Overwrite) Step 3: UI Template Step 4: Process Template Step 5: Action Step 6: Publish Action Step 7: Custom Table Import Step 8: Preview and Submit

Organization: HCLOrg Platform: Compute on Demand-vCenter Object Type: Virtual Machine

Step 3 UI Template

Import Type * UI Template *

☒ Map & Overwrite ☐ Map Only

Multi Key Value Control test

Map & Overwrite- It will overwrite the existing information from selected Zip file.
Map Only- It will map with the existing information and will not overwrite to existing one.

Figure 130 – UI Template

Step 4 – Process Template

- **Process Template Exists in the Current Environment:** If Process template exists in the current environment, map and Map & Overwrite only are options.
- **Process Template does not Exist in the Current Environment:** If Process template does not exist in the current environment, then it will be available for "NEW" creation.
- Process Template map ITSM information that has been imported with the same actions as NEW, Map & Overwrite, and Map Only option.

Publish Action

View Publish Action Publish Action Import Publish Action

Step 1: Upload File Step 2: Approval Definition
2-level-App (Map & Overwrite) Step 3: UI Template
testui (Map & Overwrite) Step 4: Process Template Step 5: Action Step 6: Publish Action Step 7: Custom Table Import Step 8: Preview and Submit

Organization: hclorg Platform: Compute on Demand-vCenter Object Type: VM

Step 4 Process Template

Import Type * Process Template Name *

☒ Map & Overwrite ☐ Map Only

test

Map & Overwrite- It will overwrite the existing information from selected Zip file.
Map Only- It will map with the existing information and will not overwrite to existing one.
Note- ITSM user password will not be imported. User has to update the password manually.

Back Next

Figure 131 – Process Template

Step 5 – Action

- **Action Exists in the Current Environment:** If Action exists in the current environment, Map Only Option will appear.

- **Action does not Exist in the Current Environment:** If Action does not exist in the current environment, then it will be available for "NEW" creation.

Publish Action

View Publish Action Publish Action Import Publish Action

Step 1: Upload File Step 2: Approval Definition (2-level-App (Map & Overwrite)) Step 3: UI Template (testui (Map & Overwrite)) Step 4: Process Template (test (Map & Overwrite)) **Step 5: Action (testPiyush1 (New))** Step 6: Publish Action Step 7: Custom Table Import Step 8: Preview and Submit

Organization: hclorg Platform: Compute on Demand-vCenter Object Type: VM

Step 5 Action

Import Type * Imported Value

☒ New testPiyush1

New- it will create new Action as per selected Zip file.

Back Next

Figure 132 - Action

Step 6 - Publish Action

- **Publish Action Exists in the Current Environment:** If Publish Action exists in the current environment, Map Only and Map & Overwrite only are options.
- **Publish Action does not Exist in the Current Environment:** If Publish Action does not exist in the current environment, then it will be available for "NEW" creation.

Publish Action

View Publish Action Publish Action Import Publish Action

Step 1: Upload File Step 2: Approval Definition (2-level-App (Map & Overwrite)) Step 3: UI Template (testui (Map & Overwrite)) Step 4: Process Template (test (Map & Overwrite)) Step 5: Action (testPiyush1 (New)) **Step 6: Publish Action** Step 7: Custom Table Import Step 8: Preview and Submit

Organization: hclorg Platform: Compute on Demand-vCenter Object Type: VM

Step 6 Publish Action

Import Type * Publish Action *

☒ Map & Overwrite ☐ Map Only testPiyush1

Map & Overwrite- it will overwrite the existing information from selected Zip file.
Map Only- It will map with the existing information and will not overwrite to existing one.

Back Next

Figure 133 - Publish Action

Step 7 - Upload Custom Table

Upload custom table is being populated with the table name which has been imported, and it checks the existence in current environment.

- **New** – It does not exist in the current environment

- Existing – Already exists in the current environment

Once the user will click upload table and next it will upload the selected row only one by one and update the status.

- Not Initiated – Initial state once no action has performed
- Success – It will process successfully
- Fail – when error occurred

Every time it will drop the existing table from the current environment and recreate the table.

If Imported Zip does not have table or it has been exported without custom table, then in this case it will automatically skip the upload custom table step and goes to summary page of the import screen.

Publish Action

View Publish Action Publish Action **Import Publish Action**

Step 1: Upload File Step 2: Approval Definition
BA+IT (Map & Overwrite)

Step 3: UI Template
Multi Key Value Control test (Map & Overwrite)

Step 4: Process Template
Multi Key Value Control test (Map & Overwrite)

Step 5: Action
multi key value control test (Map Only)

Step 6: Publish Action
multi key value control test (Map & Overwrite)

Step 7: Custom Table Import

Step 8: Preview and Submit

Organization: HCLOrg Platform: Compute on Demand-vCenter Object Type: Virtual Machine

Step 7 Upload Custom Table

✓	Table Name	Description	Category	Status
✓	1	1	Existing	Not Initiated
✓	AbhishekNewTable	Desc TableA	Existing	Not Initiated
✓	CustomTable_PSTesting_2	Custom Table for PS Testing.	Existing	Not Initiated
✓	Final_Testing1234	Desc Final Testing1234 on this Build.	Existing	Not Initiated
✓	PBI15212	Kislay API 15212	Existing	Not Initiated

Figure 134 – Upload Custom Table

Step 8 – Preview and Summary

- This will be a summary of all the steps that you have selected. There will be a submit button to process all the information related to Imported and Selected information.
- If any error occurs while processing, it will show an error message and be on the same summary page.




Figure 135 – Preview and Summary




Figure 136 – Success Message

1.5.3.4 Manage Action

This section explains how actions that are assigned to an object type in an organization, are managed through this module. This section has the following options:

- Create Action
- View Action

1.5.3.4.1 Create Action

To create object actions in an organization, the provider needs to follow the steps below:

1. On the Manage Action screen, click Create Action.

Figure 137 – Add Action

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 11 – Add Action

Fields	Description
Action Code	It is a code to initiate an action against the infrastructure resources
Action Name	Name the action as per the user
Action Description	Highlight the purpose of the action

3. Enter Action Code and Action Name.
4. Enter Action Description.
5. To add object action, click **Save**.
6. A success message box appears.




Figure 138 – Confirmation Message

All the fields given with asterisk (*) mark are mandatory.

1.5.3.4.2 View Action

This section lists all the provider users that have been created by MyCloud Admin.












Manage Action			
View Action		Create Action	
Action Code	Action Name	Action Description	Action
567890Ghjfhj8_____hfhjth__JHGyhfgyjhl_jhgdnjshs	567890Ghjfhj8_____hfhjth__JHGyhfgyjhl_jhgdnjshs	567890Ghjfhj8_____hfhjth__JHGyhfgyjhl_jhgdnjshs	  
Action1	Action1	When provider is creating custom js function from popup, same function will be save in database and after getting confirmation from database, same function will be the part of MCLD.Function.CustomFunc	  
Action10	Action10		  


Figure 139 – Edit Action

It also comprises of the following actions:

- **Edit** (): To edit/ modify the details of existing actions
- **Add** (): To add the actions
- **Change Status** (): To change the status of the action as active / inactive.

1.5.3.4.3 Edit Action

To edit/ modify existing actions in an organization, provider user needs to follow the below steps:

1. On the Action Master screen, click **View Action**.
2. Click **Edit** (.
3. Modify the details as desired and click **Update**.

Object Action Mapping	
View Action	
Action Code * <input type="text" value="start"/>	Action Name * <input type="text" value="Start"/>
Action Description <input type="text" value="Start VM"/>	Is Active <input checked="" type="checkbox"/>
<input type="button" value="Update"/>	

Figure 140 – Edit Action (Cont.)

All the fields marked with asterisk (*) are mandatory.

4. A success message box appears.




Figure 141 – Edit Action (Cont.)

1.5.3.4.4 Action Mapping

To map the actions to an object type in MyCloud, provider user needs to follow the below steps:

1. On the Object Action Mapping screen, click View Action.
2. Click **Add** (+) against the action code to be mapped to an object type.
3. It prompts the following window:




Figure 142 – Action Object Mapping (Cont.)

4. Select **Platform**.
5. The object type configured in a selected platform appears in the **Object Type** text box.
6. Select the **Object Type**.
7. Click **Create**.




Figure 143 – Action Mapping (Cont.)

All the fields marked with asterisk (*) are mandatory.

8. A success message box appears.




Figure 144 - Action Mapping (Cont.)

9. The action is mapped to an object type and appears in a list of mapped action.

1.5.3.4.5 Change Status

To change the status of an action, provider user needs to follow the below steps:

1. On the Object Action Mapping screen, click View Action.
2. Click **Change Status** (🔄) against the action code to change the status from active to inactive and vice versa.




Figure 145 - Change Action Status

3. Click **OK** to change the status. A success message box appears.




Figure 146 - Confirmation Message

1.5.4 Manage Billing Configuration

This section details the steps to manage cloud billings.

1. On the main menu bar, click **Master** and then click **Manage Billing Configuration**.
2. The section has the following options:

- Add Mapping
- View Mapping

1.5.4.1 Add Mapping

To add configuration of billing, provider user needs to follow the below steps:

1. On the Manage Billing Configuration screen, click Add Mapping.




Figure 147 - Add Mapping

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 12 - Add Mapping (Azure)

Fields	Description
Platform	The field lists down the cloud service providers
Enrolment ID	Signifies unique enrolment ID provided by Microsoft
Secret Key	To access account secret key is required associated with account
Currency	The field list down the available currencies i.e., INR, USD, EUR etc.

3. Select **Platform**. Enter details based on the platform selected.
4. Select **Subscriptions** (Endpoints).
5. Click **Save**.
6. A success message box appears as below:




Figure 148 - Add Mapping (Cont.)

All the fields given with asterisk (*) mark are mandatory.

The mapping for the subscriptions is created and appears in the **View Mapping**.

1.5.4.2 View Mapping

This section lists all the configurations that have been created by provider user.




Figure 149 – View Mapping

It also comprises of following actions:

- **Edit** (✎): To Modify the details of Existing Mapping
- **View** (🔍): To View the Details of Existing Mapping
- **Delete** (🗑): To delete the Mappings
- **Map Tags** (🏷): To do tags & column mapping (applicable only for amazon)

1.5.4.3 Edit Mapping

To edit/ modify the assigned mapping of subscription or configuration of billing access key, provider user needs to follow the below steps:

1. On Mange Billing Configuration screen, select View Mapping.
2. Select the Platform Type.
3. Click **Edit** (✎). Modify the desired details.
4. Click **Update** to save the changes.

Figure 150 – Edit Mapping

5. A success message box appears.




Figure 151 - Edit Mapping (Cont.)

All the fields marked with asterisk (*) are mandatory.

1.5.4.4 Delete Configuration

To delete a configuration from MyCloud environment, provider user needs to follow the below steps:

1. On View Mapping pane, select the Platform Type.
2. Click **Delete** (🗑️) against desired configuration.




Figure 152 - Delete Mapping

3. When prompted to confirm, click **OK**.




Figure 153 - Delete Mapping (Cont.)

4. A success message box appears.




Figure 154 - Delete Mapping (Cont.)

1.5.4.5 View Configuration

To view the configuration of amazon cloud, follow the steps below:

1. On View Mapping pane, under Action, click on View Configuration.

Cloud Billing Mapping Detail		
PlatformID	SubscriptionID	SubscriptionName
24	718534781473	AWSBillingTest2 (718534781473)

Figure 155 - View Mapping

2. A pop-up window with **Configuration** details like **PlatformID**, **SubscriptionID** & **SubscriptionName** appears as above.

1.5.4.6 View Tag Mapping

To edit/modify the mapping of Amazon cloud, follow the steps below:

1. On **View Mapping** pane, under **Action**, click on **Tag Mapping**.

Manage Billing Configuration

View Mapping

Add Mapping

Platform *

Amazon Web Services

Go





Platform	Bucket Name	Account ID	Access Key	Subscription	Action
Amazon Web Services	MonthlyReports_HCL			AWSBillingEndPoint	   

Figure 156 - Tag Mapping

2. A pop-up window with **Tag** and **Column** mapping appears as below:

Tag Value	Mapping Column
Custom1	Custom1
Custom2	Custom2
Custom3	Custom3
Custom4	Custom4
Custom5	Custom5
Custom6	Custom6

Save Close

Figure 157 - Tag Mapping (Cont.)

3. Modify the desired details.
4. Click **Save**.
5. A success message box appears.





Figure 158 - Tag Mapping (Cont.)

Tag Mapping is only available for AWS. To View any of the Listed Mappings, click View

1.5.5 Release /Reserve IP


This section details out the steps to release IPs which remained unutilized in private cloud environment. To release IP, provider user needs to follow the below steps:

1. On the **Release/Reserve IP** screen fill the below information:
2. Select Organization, Platform and Provisioning Endpoint.
3. Lastly, select **Cluster** and **Network**.



The screenshot shows the 'Release IP' home screen. It features a form with five dropdown menus: 'Organization *' (with a blacked-out selection), 'Platform *' (with '--Select--'), 'Provisioning Endpoint *' (with '--Select--'), 'Cluster *' (with '--Select--'), and 'Network *' (with '--Select--'). A blue 'Go' button is located to the right of the 'Network' dropdown.

Figure 159 – Release IP Home Screen



The screenshot shows the 'Release IP' home screen for Cisco Intersight. The form includes dropdowns for 'Organization *' (blacked out), 'Platform *' (set to 'Cisco Intersight'), 'Provisioning Endpoint *' (blacked out), 'Network Type *' (set to 'Virtualization - Distributed Switch'), and 'Distributed Switch Name*' (with '--Select--'). A blue 'Go' button is centered below the 'Distributed Switch Name' dropdown.

Figure 160 – Release IP Home Screen for Cisco Intersight


4. Refer the below table to understand the fields mentioned in the above figure:

Table 13 – Release IP

Table Field	Description
Organization	Name Of the Organization (Business Units/Divisions in Organizations)
Platform	Name of the cloud service providers
Provisioning Endpoint	The cloud endpoints that have been created in MyCloud
Cluster	It lists the clusters associate with cloud platform.
Network	It lists the network associate with cloud platform
Network Type	It is the network type applicable for Cisco Intersight, possible values could be distributed switch or distributed network
Distributed Switch Name	It lists the distributed switch name for Cisco Intersight
Distributed Network Name	It lists the distributed network name for Cisco Intersight

All fields marked with (*) are required.

5. Click **Go**.



Select	IP Address	Object ID	NIC Prefix	Action
<input type="checkbox"/>	XX.X.X.X			
<input type="checkbox"/>	XX.X.X.X			
<input type="checkbox"/>	XX.X.X.X			
<input type="checkbox"/>	XX.X.X.X			
<input type="checkbox"/>	XX.X.X.X			


■ Reserved
 ■ Not Reserved

Figure 161 - Release IP Details

6. Refer the below table to understand the fields mentioned in the above figure:

Table 14 - Release IP Details

Field	Description
IP	List of IP
Is Used	Whether IP is in use or not
Active	Whether IP is in active state
Action	To release the allocated IP, release IP action is available. And to reserve the released IP, reserve IP action is available.
Select	To select multiple IP address for bulk IP release

7. Click **Release** ().
8. A confirmation message appears as below.




Figure 162 - Confirmation of Release IP

9. Click **Ok** to **Release** or **Cancel** to **Discard** the action.
10. Click **OK**.
11. A success message box appears as below.




Figure 163 - Success Message

12. Click **Reserve** (📄).
13. A popup box appears as below.

A "Reserve IP" popup window with a blue header and a close button (X) in the top right. The form has three input fields: "Object ID*" (a single-line text box), "NIC Prefix*" (a single-line text box), and "Comments" (a multi-line text box). At the bottom right, there are two blue buttons: "Reserve" and "Close".

Figure 164 - Popup Box For Reserve IP

14. Enter Object ID, NIC Prefix, and Comments.
15. Click **Reserve** to Reserve the IP or **Close** to close the popup.
16. On clicking **Reserve**, a confirmation message appears as below:




Figure 165 - Confirmation for Reserve IP

17. Click **Ok** to reserve or **Cancel** to discard the action.
18. Click **OK**.
19. A success message box appears as below.




Figure 166 - Success Message For Reserve IP

20. Select multiple IP addresses for bulk IP release.

Release Reserve				
Select	IP Address	Object ID	NIC Prefix	Action
<input type="checkbox"/>	██████████	SSSS	SSS	

Figure 167 - Success Message for Bulk IP Release

21. Click on **Release** button.
22. A success message box appears as below:




Figure 168 - Success Message for Bulk IP Release

1.5.6 Manage Public Cloud Advisory

This section details the steps to manage public cloud advisory module.

1. On the main menu bar, click **Master** and then click **Manage Public Cloud Advisory**. It has following options:
 - Add New Configuration
 - View Configuration

Figure 169 – Manage Public Cloud Advisory

1.5.6.1 Add New Configuration

To add a public cloud advisory configuration, provider user needs to follow the below steps:

1. On Manage Public Cloud Advisory screen, click Add New Configuration.

Figure 170 – Add New Configuration

2. Select **Platform**.
3. Select Subscription.
4. Select Use Subscription Access Details.
5. Click **Save**.
6. A success message box appears.




Figure 171 – Confirmation Message

All the fields marked with asterisk (*) are mandatory.

1.5.6.2 View Configuration

This section lists out all the subscriptions that have been created by provider user. It has following actions:

- **Edit** (🔗): To modify the details of existing configurations

1.5.6.3 Edit Configuration

To edit/modify the assigned mapping of subscription or configuration of public cloud advisory, provider user needs to follow the below steps:

The screenshot below is in reference to AWS:

1. Select **View Configuration** and then click **Edit** ()




Figure 172 - Edit Configuration

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 15 - Edit Configuration

Fields	Description
Subscription Name	Highlights the endpoint subscription of a cloud service provider
AWS Account ID	Signifies unique identity of AWS account generated by AWS
AWS Access Key	Access key is key to access subscription programmatically
Is Same as Platform	Signifies whether MyCloud uses same configuration of endpoint or different
Action	Provider user to take actions like edit against listed configurations

3. Modify the desired details.




Figure 173 - Edit Configuration Cont.

4. Click **Update** to save the settings.
5. A success message box appears.




Figure 174 - Confirmation Message

All the fields marked with asterisk (*) are mandatory.

1.5.7 Performance Configuration

This section details the steps to configure performance parameters like CPU utilization, memory utilization, and many more from an endpoint/ cloud platform.

1. On the main menu bar, click **Master** and then click **Performance Configuration**.
2. It has the following options:
 - Add Mapping
 - View Mapping

1.5.7.1 Add Configuration

To add configuration, provider user needs to follow the below steps:

1. On the Performance Configuration screen, click Add Mapping.
2. Screenshot below is with reference to azure.

 A screenshot of the 'Performance Configuration' screen, specifically the 'Add Mapping' tab. The form contains the following fields:

- Platform***: A dropdown menu with 'Microsoft Azure' selected.
- Subscription***: A dropdown menu with '--Select--' selected.
- Storage Account Name***: A text input field.
- Storage Access Key***: A text input field with a search icon (magnifying glass) to its right.
- Resource Group**: A text input field with the placeholder 'Resource Group Name'.

 At the bottom right of the form is a blue button labeled 'Enable Performance'. Below the form, there is a note: 'Notes: Data on Performance reports will be available only after resources are allocated to Organization.'

Figure 175 - Add Mapping

3. Refer to the below table to understand the fields mentioned in the above figure:

Table 16 - Add Mapping

Field	Description
Platform	The field lists down the cloud service providers
Subscription	List the endpoints created

Storage Account Name	Name of storage account where performance data needs to be picked
Storage Access Key	Required to access storage account programmatically
Resource Group	Name of the resource group where storage account exists. This is a logical boundary created to manage resources as per their usage

4. Select **Platform**.
5. Select Subscription.
6. Provide Storage Account Name and Storage Access Key.
7. Click Enable Performance.
8. A success message box appears as below:




Figure 176 - Add Mapping (Cont.)

All the fields marked with asterisk (*) are mandatory.

The mapping is added and gets listed.

1.5.7.2 View Mapping

This section lists out all the configurations that have been created by the provider user.




Figure 177 - View Mapping

It also comprises of following actions:

- **Edit** (): To modify the details of existing configurations
- **Reinitiate** (): To reinitiate the configurations
- **Schedule** (): To schedule data frequency and max retry count of an existing configuration.

1.5.7.3 Edit Mapping

To edit/modify the assigned mapping of subscription or configuration of performance access key, provider user needs to follow the below steps:

1. On the Performance Configuration screen, select View Mapping.
2. Click **Edit** (✎) against the configuration that needs to be edited.




Figure 178 – Edit Mapping

3. Select Status as Enable/Disable.
4. Click **Update** to save the changes.

1.5.7.4 Reinitiate Mapping

To reinitiate the performance job. Provider user needs to follow below steps:

1. On The Performance Configuration Screen, Select View Mapping.
2. Click **Reinitiate** (↺) against the configuration that needs to be reinitiated.
3. A success message appears.




Figure 179 – Reinitiate Mapping

4. Selected configuration reinitiated successfully.

1.5.7.5 Schedule Mapping

To schedule the performance job, provider user needs to follow below steps:

1. On the Performance Configuration screen, select View Mapping.
2. Click **Schedule** (📅) against the configuration that needs to be scheduled.

Figure 180 – Schedule Mapping

3. Enter Data Frequency (Mins) and Max Retry Count.
4. Click **Update**.
5. A success message appears.




Figure 181 – Success Message

1.5.8 Manage Email

This module helps provider user to manage emails that get triggered as notification for various events like VM Provisioning, VM Customization (Change Size, Disk, Start, Stop), Decommission, Custom Task Execution.

1. On the main menu bar, click **Master** and then click **Manage Email**.

Figure 182 – Manage Email

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 17 – Manage Email

Field	Description
-------	-------------

Email Type	Type Of Email – Either Approval, Final Intimation or Other
Email Status	Current Status of The Email.
Event Type	Activity Done Under MyCloud Areas Like Approval, Cancel Etc.
From Date	Start Date Range
To Date	End Date Range
Request No.	MyCloud Request No., To View Email Status.

3. This has following sections:

- View Email
- History

1.5.8.1 View Email

Through this tab, provider user can view mails which have been triggered by MyCloud for various events.

To view, provider user needs to follow the below steps,

1. Click View Email.

Figure 183 – View Email

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 18 – View Email

Field	Description
Email Type	Type Of Email – Either Approval, Final Intimation or Other
Email Status	Current Status of The Email
Event Type	Activity Done Under MyCloud Areas Like Approval, Cancel Etc.
From Date	Start Date Range
To Date	End Date Range
Request No	MyCloud Request No., To View Email Status

3. Select Email Type, Email Status, and Email Type.
4. Choose From Date and To Date.
5. Or Search By (Request No).
6. Click **Go**.

Request No	Event Type	To	Cc	Email Type	Email Status	Created On	Last Update Date	Mail Sent Date	Action
SRREQ001402	Approved	[redacted]	[redacted]	Request and Approvals	Sent Successfully	10/06/2022 14:28:57	10/06/2022 14:31:00	10/06/2022 14:31:00	
SRREQ001402	Submit	[redacted]	[redacted]	Request and Approvals	Sent Successfully	10/06/2022 14:22:33	10/06/2022 14:24:34	10/06/2022 14:24:34	


Figure 184 - View Email (Cont.)

7. Refer to the below table to understand the fields mentioned in the above figure:

Table 19 - View Email Grid

Field	Description
Request No	Type of Email Either Approval, Final Intimation or Other
Email State	Current Status of The Email.
Event Type	Activity Done Under MyCloud Areas Like Approval, Cancel Etc.
Last Updated Date	Last Updated Status of Email
Mail Sent Date	The Date on which Email Sent.
To/CC	Email Recipients
Action	Action On the Email Sent.

8. It also comprises of following actions:

- **Mail Resend** (

1.5.8.2 Mail Resend

To resend an already sent email, in case of failure or to get another copy of an already sent email, provider user needs to follow the below steps:

1. Click **Mail Resend** (.

2. A confirmation message screen appears.




Figure 185 - Confirmation Message (Resend Mail)

3. Click **OK** to resend and **Cancel** to close the screen.
4. A success message appears.



Figure 186 - Success Message (Resend Mail)

1.5.8.3 History

To view the history of an email, provider user needs to follow the below steps:

1. Click **History** (🔄).




Figure 187 - History Manage Email

2. Click **Expand icon** (+) to view the detailed logs.

Request Id	Email Type	Creation Date
64b8f93f-2382-4a8e-9e13-ea39892e608a	Approval	7/23/2020 7:38:23 AM

Job Type	Step Operation Performed	Step Description	Step Executed Date	Error	View
ET	EmailSend	Email send successfully	07/23/2020 01:10:07 PM		Detailed Logs
ET	EmailSent	Email sent successfully	07/23/2020 01:10:07 PM		
ET	PickedFromQueue	Picked from queue label: ID^2^Type^AP^EmailRequestId^64b8f93f-2382-4a8e-9e13-ea39892e608a	07/23/2020 01:10:03 PM		
ET	PrepareEmail	Start SendEmail	07/23/2020 01:10:03 PM		
EP	BodyCreated	Body created success for Auto Id 2	07/23/2020 01:08:24 PM		Detailed Logs

Figure 188 - History Manage Email (Cont.)

- Refer to the below table to understand the fields mentioned in the above figure:

Table 20 - View Email History

Field	Description
Job Type	Type of the Job
Step Operation Performed	Steps /operations performed to send an email
Step Executed Date	Date at the time of steps executed
Error	Error details
View	To view detailed log

- Click on **Detailed Log Link** ([Detailed Logs](#)) to check the log in detail.

Log Details:	
2020-07-23 13:10:03,426 [14]	INFO EmailTask - {"Data":{"Message going to Sent. \n Label ID^2^Type^AP^EmailRequestId^64b8f93f-2382-4a8e-9e13-ea39892e608a"}}
2020-07-23 13:10:03,426 [14]	INFO EmailTask - {"Data":{"EmailState":6,"EmailId":2,"EmailRequestId":"64b8f93f-2382-4a8e-9e13-ea39892e608a","MailBody":null,"EmailType":"AP","E"}}
2020-07-23 13:10:03,426 [14]	INFO EmailTask - Update Job Completed with JobState: PickedFromQueue
2020-07-23 13:10:03,426 [14]	INFO EmailTask - Start SendingMail
2020-07-23 13:10:03,426 [14]	INFO EmailTask - {"Data":{"EmailState":6,"EmailId":2,"EmailRequestId":"64b8f93f-2382-4a8e-9e13-ea39892e608a","MailBody":null,"EmailType":"AP","E"}}

Figure 189 - Detailed Log History (Cont.)

1.5.9 Manage Custom Script

This module helps provider users to manage user defined (custom) scripts in MyCloud.

- In Master menu, click on Manage Custom Script.
- Below screen appears.

Manage Custom Script

View Script Create Script

Script Language *
--Select--

Tags ⓘ

Go

Figure 190 - Manage Custom Script

3. This has the following actions:

- View Script
- Create Script

1.5.9.1 View Script

To view the existing Custom Scripts, provider users need to follow the below steps:

1. Click **View Script** Tab.
2. Below screen appears:

Manage Custom Script

View Script Create Script

Script Language *
--Select--

Tags ⓘ

Go

Figure 191 - Manage Custom Script

3. Select Organization and Language.
4. Click **Go**.

Manage Custom Script

View Script Create Script

Script Language *
Power Shell Script

Tags ⓘ

Note: Supported Powershell versions are 5.1 and above.

Go

ScriptID	Name	Description	System Script	Status	Action
39	Again		No	●	
40	Again_Wrong		No	●	
41	Anshul		No	●	
42	Anshul_1		No	●	
17	API-Test-Script	Desc: API-Test-Script	No	●	

Figure 192 - Manage Custom Script (Cont.)

5. View Script Has Following Actions:

- **Edit** (): This Helps To Modify The Existing Custom Scripts
- **Export JSON** (): This Helps To Export The Existing Custom Scripts

- **Change Status** (🔄): This Helps To Toggle The Existing Custom Script Status
- **Add To Repository** (+📁): This Helps To Add The Script In The Master Data

1.5.9.2 Edit Script

To modify /update existing custom scripts, provider user needs to follow the steps below:

1. Click **Edit** (✎).
2. It will route the provider user to **Create Script** tab, where user can update **Description** and **Script**.

The screenshot shows the 'Manage Custom Script' interface with the 'Create Script' tab selected. The form contains the following elements:

- Script Language**: A dropdown menu showing 'Power Shell Script'.
- Script Name**: A text input field containing 'custom script clone'.
- Description**: A text input field containing 'custom script clone'.
- Tags**: A section with a search icon and a text input field.
- Write Script Here**: A large text area with a light blue border containing the text '1. dffsfadff'.
- Update**: A blue button at the bottom right of the form.

Figure 193 – Edit Manage Custom Script

3. Click **Update**



Figure 194 – Success Message Manage Custom Script

1.5.9.3 Change Status

To modify /update existing custom scripts status, provider user needs to follow the below steps:

1. Click **Change Status** (🔄).
2. A confirmation message appears on the screen.




Figure 195 - Confirmation Message

3. Click **OK** to confirm.
4. A success message appears on the screen.

1.5.9.4 Add Repository

To add existing custom scripts in repository, perform the below steps. This action is applicable only for system scripts.

1. Click on the **Add Repository** (🔗).
2. A confirmation message appears.




Figure 196 - Confirmation Message




Figure 197 - Success Message

1.5.9.5 Export Script JSON

To export existing JSON Custom Scripts, the provider user needs to follow the below steps. This action is applicable only for system scripts.

1. Click on the **Export JSON** icon (🔗).

```

1  [
2    {
3      "ScriptLanguage": "POWERSHELL",
4      "ScriptName": "sasas",
5      "ScriptDescription": "sass",
6      "Tags": "",
7      "Script": "H9+g8vqhsJgRw9cUNUIwBQ==",
8      "IsSystemScript": "N"
9    }
10 ]

```

Figure 198 - Export JSON

1.5.9.6 Create Script

To create a new custom script, provider user needs to follow the below steps:

1. Click on the **Create Script** tab.
2. The below screen appears:

The screenshot shows the 'Manage Custom Script' interface. At the top, there are two tabs: 'View Script' and 'Create Script'. The 'Create Script' tab is selected. Below the tabs, there are several input fields: 'Input Mode' with radio buttons for 'Manual' (selected) and 'JSON'; 'Script Language' with a dropdown menu showing '--Select--'; 'Script Name' with a text input field; 'Description' with a text input field; 'Tags' with a text input field; and a large text area labeled 'Write Script Here' with a line number '1' at the top. A blue 'Save' button is located at the bottom right of the form.

Figure 199 - Create Custom Script

3. Refer the below table to understand the fields mentioned in the above figure:

Table 21 - View Email History

Field	Description
Input Mode	Manual: Create script using MyCloud. JSON: Import existing JSON.
Tags	A Tag is simply a character string added to a Tags field in a resource, such as RBAC subscription. Tags will be used to define scope of permission. Objects with same tag will be able to access same tagged resources.

Script Language	Supported Languages MyCloud (Powershell and Python)
Script Name	Unique Name of The Script
Description	Description of the Script
Write Script Here	Write User Defined Script

4. Select Input Mode and Language.
5. Enter Name, Description, Tags, and Script.
6. Click **Save**.




Figure 200 - Success Message Create Script

1.5.10 Manage Script Schedule

This module helps provider users to schedule the custom scripts. The module will have scripts which were already created in MyCloud under manage custom script section.

1. On the main menu Master, click Manage Script Schedule.
2. The below screen appears.




Figure 201 - Manage Script Schedule

3. It has following tabs:
 - View Schedule
 - Add Schedule
 - Schedule History (Not Direct Clickable)

1.5.10.1 View Schedule

To view the schedule of existing scripts, provider user needs to follow the below steps:

1. Click View Schedule tab.

2. Below screen appears.





Figure 202 - Manage Script Schedule

3. Select Organization & Script.

4. Click **Go**.












Schedule Name	Script	Frequency	Start Time	Time Zone	Start Time (UTC)	Execution Status	Next Scheduled Date (UTC)	Action
TESTFailMail	Test	OneTime	11/21/2022 15:30	India Standard Time-IST (+5:30)	11/21/2022 10:00	Fail		  
...testScript test ScripttestDushedule	TestNavinScript_TestNavinScript	OneTime	11/08/2022 15:45	India Standard Time-IST (+5:30)	11/08/2022 10:15	Success		  
...testScript test ScripttestDushedule	Test Navin ScriptTestNavinScript TestNavinScript	OneTime	11/08/2022 15:45	India Standard Time-IST (+5:30)	11/08/2022 10:15	InProgress	11/08/2022 10:15	  



Figure 203 - Manage Script Schedule (Cont.)

5. Refer the below table to understand the fields mentioned in the above figure:

Table 22 - Manage Scripts Schedule

Field	Description
Script	Name of the Script
Name	Unique name of the Scheduled Script
Description	Description of the Script
Frequency	Intervals at which the script can be scheduled
Start Time and Time Zone	From when the script to start and on which time zone
Action	User can take actions like Edit, Delete, and View History
Execution Status	Current Status of the Scheduled Script
Next Scheduled Date	The Date and Time when the schedule will execute in future

6. View Script has following actions:

- **Edit** (): To update /modify the schedule of existing scripts.
- **Delete** (): To delete any schedule of existing scripts.

- **History** (🕒): To view the execution history of a script.
- **Execute Now** (🚀): To execute the schedule immediately.

1.5.10.2 Edit Schedule

To update/ modify any schedule of an existing script, provider user needs to follow the below steps:

1. Click **Edit** (🔍).
2. It will route the provider user to **Add Schedule** tab.

Figure 204 – Manage Script Schedule (Edit.)

3. Modify the fields as per requirements.
4. Click **Update** or **Cancel** to discard the changes. Confirmation messages appear (in case of daily jobs)
5. Click **OK**. A success message appears.




Figure 205 – Success Message Script Schedule (Edit.)

1.5.10.3 Delete Schedule

To delete a schedule, provider user needs to follow the below steps:

1. Click **Delete** (🗑️).
2. A confirmation message appears.




Figure 206 - Confirmation Message Script Schedule (Delete.)

3. Click **OK** to confirm.




Figure 207 - Success Message Script Schedule (Delete.)

1.5.10.4 Schedule History

To view the execution history of a script, provider user needs to follow the below steps:

1. Click **History** (🕒).
2. The below screen appears.




Figure 208 - History

3. Choose the Start Date (UTC).
4. Choose the End Date (UTC).
5. Choose the **Status**.
6. Click **Filter**.
7. The below screen will appear with detailed execution history of a script.

Schedule Request ID		Step State	Date Executed (UTC)	Action
8C58CE07-AAD8-4C0E-8B52-E70CDB5AEF4B		Success	7/23/2020 1:00:25 PM	Step Query
Date	Component Code	Step Description	Step Query	View
2020-07-23 06:30:00 PM	ORCSERVICE	Schedule Updated Success	[{"JobId":129,"PlatformID":2,"Step":"Orchestrator","DateExecuted":"2020-07-23T13:00:27.273","Description":"Schedule Updated Success","Status":0,"StepTableUpdated":"ScheduleExecutionTaskHistory","ScheduleRequestId":"8C58CE07-AAD8-4C0E-8B52-E70CDB5AEF4B","ComponentCode":"ORCSERVICE"}]	Detailed Logs
2020-07-23 06:30:00 PM	WORKFLOW	Start Orchestrator URL : http://localhost:9093/OrchestratorService	[{"ScheduleOutput":{"ScheduleId":50,"ScheduleState":0,"StepExecuted":"CallService","StepRemarks":"Start Orchestrator URL : http://localhost:9093/OrchestratorService","ScheduleRequestId":"8C58CE07-AAD8-4C0E-8B52-E70CDB5AEF4B"}}]	Detailed Logs
2020-07-23 06:30:00 PM	WORKFLOW	Start ProcessScheduleScript	[{"ScheduleOutput":{"ScheduleId":50,"ScheduleState":0,"StepExecuted":"ProcessScheduleScript","StepRemarks":"Start ProcessScheduleScript","ScheduleRequestId":"8C58CE07-AAD8-4C0E-8B52-E70CDB5AEF4B"}}]	
2020-07-23 06:30:00 PM	WORKFLOW	Schedule Start for Schedule Id :50 and ScheduleRequestId: 8C58CE07-AAD8-4C0E-8B52-E70CDB5AEF4B	[{"ScheduleOutput":{"ScheduleId":50,"ScheduleState":0,"StepExecuted":"updateSchedule","StepRemarks":"Schedule Start for Schedule Id :50 and ScheduleRequestId: 8C58CE07-AAD8-4C0E-8B52-E70CDB5AEF4B","ScheduleRequestId":"8C58CE07-AAD8-4C0E-8B52-E70CDB5AEF4B"}}]	

Figure 209 - History

1.5.10.5 Execute Now

To execute schedule now for a script, provider user needs to follow the below steps.

1. Click on the **Execute Now** action.
2. The below message appears.




Figure 210 - Manage Script Schedule

1.5.10.6 Add Schedule

To add a new schedule for a script, provider user needs to follow the below steps.

1. Click the **Add Schedule** tab.
2. The below screen appears.

Figure 211 - Create Schedule

3. Refer to the below table to understand the fields mentioned in the above figure:

Table 23 -Add Schedule

Field	Description
Organization	Name of the MyCloud organization
Name	Unique name of the scheduled script
Description	Description of the script
Script	Custom script name.
Frequency	Interval at which the script needs to be scheduled
Start Time and Time Zone	Time from when the script needs to be executed and in which time zone.
Parameter Name	To add dynamic parameter in the script, user can add the name of the parameter through this option.
Data Type	Type of value to that parameter. It can be SQL function, secret key, or static.
Parameter Value	Value of the respected parameter name.
Failure Email To	This field will be used to send "To" Email notification, in case of Task Failure. Please use comma (,) to add multiple emails in this fields.
Failure Email CC	This field will be used to send "CC" Email notification, in case of Task Failure. Please use comma (,) to add multiple emails in this fields.
Failure Email BCC	This field will be used to send "BCC" Email notification, in case of Task Failure. Please use comma (,) to add multiple emails in this fields.

- Choose Organization, Script & Time Zone.
- Enter Name & Description.
- Choose Active, Frequency.

7. Enter **Parameter Name**, **Data Type**, and **Value**. Click **Add** to add in the script.
8. Click **Save**.
9. A success message appears.




Figure 212 - Success Schedule

1.5.11 AWS Cost Explorer Configuration

This section details the steps to configure the AWS cost explorer.

1. On the main menu bar, click **Master** and then click **AWS Cost Explorer Configuration**.
2. It has the following options:
 - Add Configuration
 - View Configuration

1.5.11.1 Add Configuration

To add configuration, provider user needs to follow the below steps:

1. On the AWS Cost Explorer Configuration screen, click Add Configuration tab.

Figure 213 - Add Configuration

2. Refer to the below table to understand the fields mentioned in the above figure:

Table 24 - Add Mapping

Field	Description
Platform	The field lists down the cloud service provider
Subscription	Lists down the endpoints that were created
Use Subscription Access Details	Select this dropdown as:

- **Yes**, if you want to use the same access details as of the subscription, instead of adding new.
- **No**, if you want to enter new account access details like account ID, access key & secret key.

Report Type	Type of the report, which the user wants for this configuration
--------------------	---

3. Select **Platform**.
4. Select Subscription.
5. Select **Use Subscription Access Details** (By default, it is Yes).
6. Select Report Type.
7. Click **Save**.
8. A success message box appears as below:




Figure 214 - Add Configuration (Cont.)

All the fields marked with asterisk (*) are mandatory.

9. The configuration is added successfully.

1.5.11.2 View Configuration

This section lists out all the configurations that have been created by the provider user.




Figure 215 - View Mapping

It also comprises of following actions:

- **Edit** (edit icon): To modify the details of existing configurations.

1.5.11.3 Edit Configuration

To edit/ modify the existing configuration, provider user needs to follow the below steps:

1. Click **Edit** (✎) against the configuration that needs to be edited.

The screenshot shows the 'AWS Cost Explorer Configuration' dialog box. It has two tabs: 'View Configuration' and 'Add Configuration'. The 'Add Configuration' tab is selected. The form contains the following fields and values:

- Platform***: Amazon Web Services
- Subscription***: AWSBilling (686338381863)
- Use Subscription Access Details**: NO
- Account Id***: [Redacted]
- Access Key***: [Redacted]
- Secret Key***: AwsProvisioning(cyberark)
- Report Type***: ☒ Reserved Instance, ☐ Usage Forecast

At the bottom, there are 'Update' and 'Cancel' buttons.

Figure 216 - Edit Configuration

2. Select **Platform**.
3. Select Subscription.
4. Select Use Subscription Access Details as Yes/No.
 - **Yes** – The access details of subscription will be used.
 - **No** – The user can edit Account ID, Access Key & Secret Key
5. Select Report Type.
6. Click **Update** to save the changes.
7. A success message box shown as below:




Figure 217 - Edit Configuration

1.5.11.4 Delete Configuration

To delete the existing configuration, provider user needs to follow the below steps:

1. Click **Delete** (🗑) against the configuration that needs to be deleted.
2. A confirmation message appears.




Figure 218 - Confirmation Message

3. A success message appears.




Figure 219 - Success Message

1.5.12 Import Objects

Objects are native resources that are managed through MyCloud and synced from underlying infrastructure which get assigned to end users by provider user.

Figure 220 - Import Objects

1.5.12.1 View CI

To import objects for specific customers, provider needs to follow the steps below:

1. On the main menu bar, click **Master** and then click **Import Objects**.
2. Select Organization and Platform.
3. Select Provisioning Endpoint and Object Type.

4. Enter **Object ID** for specific object search (optional)
5. Enter **Search Keys** and **Value** (optional)
6. Click **Go**.

Figure 221 - Import Objects

7. The below screen appears.

ObjectID	Object Type	Platform	Object Status	Computer Name	Power Status	Region Name	No of CPU	Action
MAC-WEB-467-1	Virtual Machine	Cisco Intersight	NEW	MAC-WEB-467-1	STOPPED	Region1	1	
MAC-WEB-471-1	Virtual Machine	Cisco Intersight	NEW	MAC-WEB-471-1	RUNNING	Region1	1	
MAC-WEB-472-1	Virtual Machine	Cisco Intersight	NEW	MAC-WEB-472-1	RUNNING	Region1	1	
MAC-WEB-473-1	Virtual Machine	Cisco Intersight	NEW	MAC-WEB-473-1	RUNNING	Region1	1	
mctestkubedownload-control-p-2c8b684975	Virtual Machine	Cisco Intersight	NEW	mctestkubedownload-control-p-2c8b684975	STOPPED	Region1	1	
mctestkubedownload-worker-pr-2c4174f668	Virtual Machine	Cisco Intersight	NEW	mctestkubedownload-worker-pr-2c4174f668	STOPPED	Region1	1	
nvmdacwebalqp01	Virtual Machine	Cisco Intersight	NEW	nvmdacwebalqp01	RUNNING	Region1	4	

Figure 222 - Import Objects (Cont.)

MCLD-24-1	Virtual Machine	Compute on Demand-vCenter	NEW	MCLD-24-1	STOPPED	US	1	
Indrmclapsr01	Virtual Machine	Compute on Demand-vCenter	NEW	Indrmclapsr01	RUNNING	US	2	

1 2 3 4 5 6 7 8 9 10 > Last

Figure 223 - Import Objects (Cont.)

All the fields marked with asterisk (*) are mandatory.

1.5.12.2 Import CI

To import any CI, provider user needs to follow the below steps:

1. Click **Import** ().
2. The below pop-up will appear on the screen.

Figure 224 - Import CI

3. Click **Expand icon** () to expand to enter all the mandatory fields to import CI.
4. Master configuration of CI columns has been done from **CI Columns Configuration** screen.

Figure 225 - Import CI

5. Click **Save**.

1.5.12.3 Upload CI

1. To upload the CI from MyCloud screen, click on **Upload CI** tab.

Figure 226 - Import Objects

2. Select Organization, Platform, Provisioning Endpoint, and Object Type.

3. Enter **Search Keys** (Optional)
4. Choose Upload File.

1.5.13 My Reports

1. On the main menu bar, click **My Reports**.
2. The drop-down appears with the following options:
 - **Public Cloud Billing:** Displays the resource usage and consumption report associated with cost. User can further drill down the reports, extending from subscription level to resource level.
 - **Resource Detail:** Shows the data of underlying infrastructure resources synced with MyCloud.
 - **Request Task Management:** Provide the detailed task wise execution status of requests placed by an end-user.
 - **ITSM Request Tracking:** Displays the ITSM task execution status associated with each request.
 - **Request Tracking:** To track request and its tasks status associate with each request.
 - **Amazon Monthly Billing Analysis:** Displays AWS resource usage and consumption report based on months.
 - **Public Cloud Annual Billing Analysis:** Displays annual consumption of public cloud resources.
 - **Azure Service Usage Report:** This report displays the usage of various Azure services.
 - **Amazon Service Billing:** This report displays the usage of various Amazon services.
 - **CI Report:** Provider User can track CI object using this report.
 - **SLA Report:** This report displays the SLA status associated with each task and the time frame in which it is completed.
 - **vCenter Dashboard Report:** This report displays vCenter related Cluster, Host, Data Store, VM and Resource Pool Information in graphical, textual and numerical format.
 - **vCenter Performance Report:** This report of vCenter which shows hierarchal data in textual and graphical format.
 - **Public Cloud Billing Analyzer:** This report displays billing information for specific cloud platform and subscription based on months.
 - **Forecasting And RI Recommendation:** Enables cost optimization and resource utilization by analyzing the past usage patterns & recommending the most optimal resource types on AWS and Azure.

1.5.13.1 Public Cloud Annual Billing Analysis

This report gives comparison of expenses of cloud subscription of last 12 months. Tag filters can be used to narrow down search.

To view the public cloud billing analysis report, provider user needs to follow the below steps:

1. Click Public Cloud Billing Analysis from the My Reports drop-down menu.
2. Select Provider, Platform, Subscription, Tag Name, and Tag Value from drop-down.
3. Click Show Report.

Public Cloud Annual Billing Analysis

Cloud Filters

Provider *
 hcl provider

Platform *
 Microsoft Azure (ARM)

Subscription *
 AzureBilling

Tag Name
 --All--

Tag Value
 --All--

Export

Show Report

Figure 227 – Public Cloud Annual Billing Analysis

4. The following screen appears:




Figure 228 – Public Cloud Annual Billing Analysis (Cont.)

1.5.13.2 Azure Service Usage Report

This report gives service wise billing for all Azure accounts or specific Azure account for specific months' range. Filters can be used to narrow down search.

To view the Azure service usage report, provider user needs to follow the below steps:

1. Click Azure Service Usage Report from the My Reports dropdown menu.
2. Select Provider, Platform & Subscription.
3. Select From Months and To Months.
4. Click Show Report.

Figure 229 - Azure Service Usage Report

5. The following screen appears:

JobId	Service Name	Unit Of Measure	January 2022	February 2022	March 2022	April 2022	May 2022	June 2022	July 2022	August 2022
1	Azure App Service Basic Plan - B1	100 Hours	0.0000	0.0000	0.0000	3,072.6600	2,801.6800	0.0000	3,417.1300	3,417.1300
2	Azure App Service Basic Plan - B3	100 Hours	0.0000	0.0000	0.0000	12,290.6400	11,206.7100	0.0000	13,668.5200	13,668.5200
3	Azure App Service Free Plan - F1	1 Hour	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000
4	Bandwidth - Data Transfer Out - Zone 1	10 GB	0.0000	0.0000	0.0000	22.2500	17.1300	0.0000	0.0000	0.0000
5	Bandwidth Inter-Region - Data Transfer Out - NAM or EU To Any - Intercontinental	1 TB	0.0000	0.0000	0.0000	0.2000	0.0800	0.0000	0.0000	0.0000
6	Bandwidth Inter-Region - Inter Continent Data Transfer Out - NAM or EU To Any - Intercontinental	1 TB	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.1200	0.0600
7	Bandwidth Inter-Region - Intra Continent - Data Transfer Out - North America	1 TB	0.0000	0.0000	0.0000	0.0900	0.0600	0.0000	0.0000	0.0000
8	Bandwidth Inter-Region - Intra Continent Data Transfer Out - North America	1 TB	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0200	0.0100
9	Event Hubs - Standard - Throughput Unit	100 Hours	0.0000	0.0000	0.0000	1,232.6900	1,124.3000	0.0000	1,366.7900	1,366.7900
10	Event Hubs - Standard Throughput Unit	100 Hours	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0000

Figure 230 - Azure Service Usage Report (Cont.)

1.5.13.3 Amazon Service Report

This report gives service wise billing for all AWS accounts or specific AWS account. Filters can be used to narrow down search.

To view the amazon service report, provider user needs to follow the below steps:

1. Click on **Amazon Service Report** from the **My Reports** dropdown menu.
2. Select Provider, Platform & Subscription.
3. Select **Months** and **Year**.
4. Select **Tags**.
5. Click Show Report.

Figure 231 - Amazon Service Report

6. The following screen will appear:

AWS Services		Total Cost
Amazon Athena		\$0.0092
Subscription Name		Total Cost
AWSBillingEndPoint (716523076871)		\$0.0092
Amazon CloudSearch		\$41.2056
Amazon Comprehend		\$0.1022
Amazon DynamoDB		\$122.0119
Amazon EC2 Container Registry (ECR)		\$1.6580
Amazon Elastic Compute Cloud		\$8,874.7210
Amazon Elastic Container Service for Kubernetes		\$334.0445

Figure 232 – Amazon Service Report (Cont.)

- Click **Expand icon** (+) to expand the selection.
- The data will appear in tabular format.

AWS Services		Total Cost
Amazon Elastic Compute Cloud		\$267.16
Subscription Name		Total Cost
AmazonDevBilling (686338381863)		\$267.16

Figure 233 – Amazon Service Report (Contd.)

1.5.13.4 Public Cloud Billing

This report gives a list of the billed usage details. User can drill down the data up to resource level. Filter's options are also available to narrow down the data.

To view the **Public Cloud Billing** report, provider user needs to follow the below steps:

- Click **Public Cloud Billing** from the **My Reports** dropdown menu.
- Select Provider, Platform & Subscription.
- Select **Months** and **Year**.
- Select **Tags**.
- Click Show Report.
- The following screen appears.

Public Cloud Billing

Cloud Filters

Provider*
PVDemo

Platform*
--Select--

Subscription*
--Select--

Month
March

Year
2021

Tag Name
--Select--

Tag Value
--Select--

Export

Show Report
Reset

Figure 234 – Public Cloud Billing





Figure 235 - Public Cloud Billing (Cont.)

7. On clicking of **Expand** () button, it displays account information.
8. The following screen appears.





Figure 236 - Public Cloud Billing (Cont.)

9. On clicking of **Expand** () button, it displays product information.
10. The following screen appears.





Figure 237 - Public Cloud Billing (Contd.)

11. On clicking of **Expand** () button, it displays usage information.
12. The following screen appears.




Figure 238 - Public Cloud Billing

1.5.13.5 CI Report

To view the CI report, provider user needs to follow below steps:

1. On main menu, click **My Reports** and then click **CI Report**.
2. The below screen appears.

CI Report

All dates are in mm/dd/yyyy HH:mm:ss format

Filters

Organization * --Select--

Platform * --Select--

Provisioning Endpoint --All--

Object Type * --Select--

CI Status --All--

Date Range Type Any

Request From Date From Date

Request To Date To Date

Object ID OR Please enter minimum 3 characters to search ObjectID

Report By * --Select--

Additional Filter

Export

Show Report Reset

Figure 239 - CI Report

Fields marked with (*) are mandatory to fill. Reset will enable the cloud filters.

3. Select Organization, Platform & Environment\Endpoint.
4. Select Object Type, CI Status, Date Range Type.
5. Select Request from Date and Request To Date.
6. Or search by **Object ID**.
7. Click Show Report.

CI Report

All dates are in mm/dd/yyyy HH:mm:ss format

Filters

Additional Filter

Export

Show Report Reset

	ObjectID	Cloud Name	Actual Disk	Availability Set	Backup Default	Backup IPAddress	Backup Subnet	Cluster Name	Computer Name	CreatedDate	Custom Field 1	Custom Field 2
+	AWS - kslay_InsertCI_01									10/03/2022 19:41:39		
+	i-0f16a48f48d22c42		[[{"AvailabilityZone": "us-east-1a", "VolumeId": "vol-...", "Read more"}]]							09/30/2022 10:16:27		
+	i-0b1adcf87f139099		[[{"AvailabilityZone": "us-east-1a", "VolumeId": "vol-...", "Read more"}]]							09/11/2022 16:02:38		

Figure 240 - CI Report

8. Click to **Expand** (+) to see the request wise details of an object.

	ObjectID	ComputerName	Machine Name	IsBackup	IsEnableMonitoring	IsImported	LocationName	IsAvailabilitySet	PlatformName
+	MCLD-39-1	MCLD-39-1	MCLD-39-1			N	NY		VMWAR
-	MYCLD-VM-LIN-1	MYCLD-VM-LIN-1	MYCLD-VM-LIN-1			N	NY		VMWAR

Request No	Request Date	Service Catalog	Request Action	Status
SRREQ000040-1	05/11/2020 03:20:16 PM	Red Hat Enterprise Linux 7.2 (Billing)	Request Provisioning	Fulfilment Completed

Figure 241 - CI Report (Cont.)

9. Click on Request No. to view the Request Details.

Request Details

Request No	SRREQ000040	Location Name	NY
Request Date (mm/dd/yyyy)	05/11/2020	Catalog Name	Red Hat Enterprise Linux 7.2 (Billing)
Region Name	US	Requester Name	requester
Platform	Compute on Demand-vCenter	Provisioning Endpoint	VcenterDev
Request Type	VM-Virtual Machine Provisioning	Request for	

Item : 1

General Information	Compute	Additional Information	Tags	Network	Disk
Period	1	Cost Type	Allocation based model		
Service Plan	Platinum	Provision Date	05/11/2020		
Period Value	Month(s)	Decommission Date	06/10/2020		
Region	US	Location	NY		
VM Display Name	MYCLD-VM-LIN-1	Remarks	Billing testing dummy machine Linux 7.2		
Size	Small (vCPU : 1, Memory : 2 GB)		Cluster		
Os Disk Storage					

Figure 242 - CI Report (Cont.)

10. Click on **Configure CI Columns** (). This column setting configuration is user specific.
- **Default Case:** In case no columns settings are done, by default all CI columns will appear. A screen appears as below.

Configure CI Columns

Available Columns

- ObjectID
- ObjectStatus
- ObjectType
- OrgEntityID
- OS
- OSDiskSize
- PlatformEntityID
- polycname
- Power Status
- Primary IP
- PrimaryDefault
- PrimarySubnet
- PrivateDNS
- ProviderEntityID
- ProvisionDate
- PublicDNS
- Recoveryvalut

Selected Columns

- ComputerName
- MachineName
- IsBackup
- IsEnableMonitoring
- IsImported
- LocationName
- IsAvailabilitySet
- PlatformName

Save


Figure 243 - CI Report (Cont.)

- **Available Columns:** Displays list of all the available CIs.
 - **Selected Columns:** Displays list of all the CIs that have been selected to configure in the report.
- This screen also compromises of some actions,
- **Swap All Right** (): Move/swap all the available CIs under selected columns.
 - **Swap Right** (): Move selected CIs under selected column.
 - **Swap Left** (): Move/shift selected CIs to the left side (selected to available).
 - **Swap All Left** (): Move/swap all the selected CIs under available columns.

Above actions are applicable for available columns and selected columns

11. To change the order of display of the selected columns, provider user can use the following options.

- Click **Save**.
- A success message appears.



- Figure 245 - CI Report

- Figure 246 - CI Report

1. Click on **Resource Detail** from the **My Reports** dropdown menu.
2. The following screen appears.

Resource Detail

Filters

Platform*
Microsoft Azure

Provisioning Endpoint*
AzureDev

Resource Type*
Virtual Networks

Additional Filter

Go

Figure 247 - Resource Detail

Resource Detail

Filters

Platform*
--Select--

Provisioning Endpoint*
--Select--

Resource Type*
--Select--

Additional Filter

Filter Type*
--Select--

Filter Operators*
--Select--

Filter Value*
--Select--

Go

Figure 248 - Resource Detail (Cont.)

3. Select **Platform**.
4. Select Provisioning Endpoint.
5. Select Resource Type.
6. **Additional Filter** is optional. On clicking **Additional Filter**, following parameters need to be filled.
 - Select Filter Type.
 - Select Filter Operators.
 - Enter Filter Value.
7. Click **Add Button** (+)
8. Click **Go**.

Resource Detail

Filters

Platform*
Microsoft Azure

Provisioning Endpoint*
AzureDev

Resource Type*
Virtual Networks

Additional Filter

Filter Type*
Resource Group Name

Filter Operators*
CONTAINS

Filter Value*
aro_dryice

Logical Operator
--Select--

Filter Type*
--Select--

Filter Operators*
--Select--

Filter Value*
--Select--

Go

Figure 249 - Resource Detail (Cont.)

9. Reports are displayed in a tabular form.

Resource Detail

Filters

Platform* Microsoft Azure Provisioning Endpoint* AzureDev Resource Type* Virtual Networks

Additional Filter

Go

Export **Map Service Plan**

All dates are in mm/dd/yyyy HH:mm:ss format

	ActualDonEnvironment	Name	IsActive	Resource Group Name	Region Name	PlatformEntityID	EntityID	ServicePlan
<input type="checkbox"/>	c800fb56-7415-41ba-80f3-e7ee9c979030	aro-vnet	Y	aro_dryice	eastus	ARM-58B227EC-707F-4549-9EB3-8EB1D06F55D2	NTW-A89C7759-903D-4563-9B21-1AB1F7367F80	silver

Records 1 - 1 of 1

Remove All Service Plan **Map Service Plan**

Figure 250 - Resource Detail (Cont.)

1.5.13.7 Request Task Management

This report lists the task level details against a request item. Users can also take actions on task. Task status with different color codes will appear on screen. Users can filter records based on available filters.

To view the **Request Task Management** report, provider user needs to follow the below steps:

1. Click on **Request Task Management** from the **My Reports** dropdown menu.
2. The following screen appears.

Request Task Management

Filters

Organization* --Select-- Platform --All-- Provisioning Endpoint --All--

Status --All-- Search Keys Key Value

OR Search By

Request Number Request Number

Show Report

Figure 251 - Request Task Management

3. Select Organization.
4. Select Platform & Provisioning Endpoint.
5. Enter Status and Search Keys.
- Or
6. Enter Request Number.
7. Click Show Report.

All dates are in MM/dd/yyyy hh:mm:ss format

	Request No	Catalog Name	Platform	Provisioning Endpoint	Request Status	Request Date	Requester Name
+	SRREQ000031-1	testservice	Compute on Demand-vCenter	VMWARTest	Fulfilment Completed	04/25/2020 08:41:33 PM	requester
+	SRREQ000005-1	Windows 2012	Compute on Demand-vCenter	VMWARTest	Fulfilment In-Progress	04/02/2020 04:41:26 PM	requester

■ Task Maximum Timeout Reached
■ Task Failed
■ Task in progress
■ Task Success
■ Task not Started

Figure 252 - Request Task Management (Cont.)

8. Reports are displayed in a tabular form.
9. Click **Expand** (+) against a request if a user wishes to take an action.

+	SRREQ000031-1	testservice	Compute on Demand-vCenter	VMWARTest	Fulfilment Completed	04/25/2020 08:41:33 PM	requester
---	---------------	-------------	---------------------------	-----------	----------------------	------------------------	-----------

Figure 253 - Request Task Management (Cont.)

10. Details are displayed in a tabular form.

	Request No	Catalog Name	Platform	Provisioning Endpoint	Request Status	Request Date	Requester Name
	SRREQ000031-1	testservice	Compute on Demand-vCenter	VMWARTest	Fulfilment Completed	04/25/2020 08:41:33 PM	requester

Task Name	Task Status	Task Start Date	Task End Date	Exec Plan Id	Execution Type	Sequence	Retry Count	Action
testTask	Task Success	04/25/2020 08:44:00 PM	04/25/2020 08:44:52 PM	62	AUTO	1	0	

Figure 254 - Request Task Management (Cont.)

11. To mark a task as **Completed**, click **Complete**.

1.5.13.7.1 Restart Task

1. To restart a task, click on **Restart icon** (↺).

Task Name	Task Status	Plan Execution Date	Task Start Date	Task End Date	Exec Plan Id	Execution Type	Sequence	Group Sequence	Retry Count	Action
GetVmname	Task Success	09/16/2022 13:44:19	09/16/2022 13:44:20	09/16/2022 13:46:53	2513	AUTO	1	1	0	

Figure 255 - Request Task Management (Cont.)

2. Click **OK**.




Figure 256 - Request Task Management (Cont.)

3. The task is restarted successfully.

1.5.13.7.2 View XML

1. To validate requested XML, click **View XML** (📄).
2. A pop-up appears.




Figure 257 - Request Task Management (XML)

1.5.13.7.3 View Response

1. To validate response XML, click on **View Response** (💬).
2. A pop-up appears.




Figure 258 - Request Task Management (XML) (Cont.)

To check the status of the task, click on **Sequence**. To check the error detail of the task, click on **Detailed Logs**.

In request Task management there is new column External Tool which is configured by key "EnableExternalToolId" by provider admin.

To set value "Y" of this key admin user can enable to show external tool id in request task management screen for provider.

Request No	Service Catalog	Requested Action	Platform	Provisioning Endpoint	Request Status	Request Date	Requester Name
SRREQ001311-1	Trigger Sync	Request Provisioning	Amazon Web Services	AWSDev	Fulfillment In Progress	01/17/2024 19:22:38	requester

Task Name	Task Status	Plan Execution Date	Task Start Date	Task End Date	Exec Plan Id	Execution Type	Sequence	Group Sequence	Rel. Cost	External Toolid	Action
t1	Task Failed	01/17/2024 19:23:16	01/17/2024 19:25:01	01/17/2024 19:25:48	22022	AUTO	1	1	0	CH001	[Icons]
t2	Task not Started	01/17/2024 19:23:16			22022	AUTO	2	2	0	CH002	[Icons]
t3	Task not Started	01/17/2024 19:23:16			22022	AUTO	3	3	0	CH003	[Icons]

Figure 259 – Request Task Management

1.5.13.8 ITSM Status Tracking

To view the ITSM Status Tracking Report, provider user needs to follow the below steps:

1. Click ITSM Status Tracking under My Reports dropdown menu.
2. The following screen appears.

ITSM Status Tracking

Cloud Filters

Organization *

Platform *

Provisioning Endpoint *

ITSM Execution Status

OR Search By

Request Number

Show Report

Figure 260 – ITSM Request Racking

3. Select Organization & Platform.
4. Select Provisioning Endpoint.
5. Select ITSM Execution Status.
- Or
6. Search by Request Number.
7. Click Show Report.

ITSM Status Tracking

Cloud Filters

Show Report

All dates are in mm/dd/yyyy HH:mm:ss format

Request No	Orchestrator Task Name	Orchestrator Task Status	Sequence	Retry Count	Action	Logs
SRREQ001257-1	StartVM	Task Failed	1	3	↻	Logs
SRREQ001256-1	StopVM	Task Failed	1	3	↻	Logs
SRREQ001254-1	StopVM	Task Failed	1	3	↻	Logs
SRREQ001251-1	StopVM	Task Failed	1	3	↻	Logs
SRREQ001240-1	StopVM	Task Failed	1	3	↻	Logs
SRREQ001239-1	StopVM	Task Failed	1	3	↻	Logs
SRREQ001168-1	StopVM	Task Failed	1	3	↻	Logs
SRREQ001167-1	StopVM	Task Failed	1	3	↻	Logs

Figure 261 - ITSM Status Tracking (Cont.)

1.5.13.8.1 Reset Task

- To **Restart** a task, click ([↻](#)).




Figure 262 - ITSM Request Tracking (Cont.)

- The task gets restarted.

To check the error details of the task, click on **Retry Count Hyperlink**.

1.5.13.9 Request Tracking

To view the request tracking report, provider user needs to follow the below steps:

- Click **Request Tracking** under **My Reports** dropdown menu.
- The following screen appears.

Request Tracking

Filters

Organization*

Platform

Provisioning Endpoint

Status

Search Keys

Key Value

OR Search By

Request Number

Show Report

Figure 263 - Request Tracking

- Select Organization, Platform, and Provisioning Endpoint.

4. Select **Status**.
5. Enter **Search Keys** or **Search By Request Number**.
6. Click Show Report.

All dates are in mm/dd/yyyy HH:mm:ss format

	Request No	Service Catalog	Requested Action	Platform	Provisioning Endpoint	Request Status	Request Date	Requester Name
+	SRREQ001363	Service_Plyush_Final	Request Provisioning	Compute on Demand-vCenter	vCenterProvisioning	Fulfillment Completed	09/16/2022 14:23:54	HCL Requester
	SRREQ001362	Service_Plyush_Final	Request Provisioning	Compute on Demand-vCenter	vCenterProvisioning	Pending By IT Approval	09/16/2022 14:19:36	HCL Requester
+	SRREQ001361	Service_Plyush_Final	Request Provisioning	Compute on Demand-vCenter	vCenterProvisioning	Fulfillment Completed	09/16/2022 13:42:54	HCL Requester

Figure 264 - Request Tracking (Cont.)

7. On clicking **Expand** (+) button, it displays task information.
8. The following screen appears:


	Request No	Service Catalog	Requested Action	Platform	Provisioning Endpoint	Request Status	Request Date	Requester Name
	SRREQ001363	Service_Plyush_Final	Request Provisioning	Compute on Demand-vCenter	vCenterProvisioning	Fulfillment Completed	09/16/2022 14:23:54	HCL Requester
Item No	Task Sequence	Group Sequence	Task Name	Task Status	Item Status	Execution Start Date	Execution End Date	
1	7	8	UpdateCL_New	Task Success	Fulfillment Completed	09/16/2022 14:54:24	09/16/2022 14:57:01	

Figure 265 - Request Tracking (Cont.)

9. On clicking **Request No**. It displays item details.
10. The following screen appears.

Request No : 162 Item No : 1

All dates are in MM/dd/yyyy hh:mm:ss format

Sequence	Task Status	Retry Count	Task Name	Task Short Name	Task Start Date	Task End Date
1	Task Success	0	CheckIs64Bit	CheckIs64Bit	07/01/2020 12:31:09 PM	07/01/2020 12:31:12 PM
2	Task Success	0	bringDataDiskTag	bringDataDiskTag	07/01/2020 12:32:00 PM	07/01/2020 12:33:00 PM

Figure 266 - Request Tracking (Cont.)

1.5.13.10 Amazon Monthly Billing Analysis

This report gives details of the monthly bill for AWS. Data is the line item of AWS Usage Bill. Tags filters can be used for search specific tagged resources.

To view the Amazon Billing Analysis Report, provider user needs to follow the below steps:

1. Click on Amazon Monthly Billing Analysis under My Reports dropdown menu.
2. The following screen appears.

Figure 267 – Amazon Monthly Billing Analysis

3. Select Platform, Subscription, Tag Name, Tag Value, and Month from drop-down.
4. Click Show Report.
5. The following screen appears. Provider user can see the **Monthly Billing Report** as shown in the below figure:

Subscription Name	Billing Start Date	Billing End Date	Product Name	Usage Type	Usage Start Date	Usage End Date	Usage Quantity	Cost Before Tax
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	Amazon Elastic Compute Cloud	APS1-ElasticIPIdleAddress	01 Mar 2020	01 Apr 2020	732.00	\$3.56
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	AWS Data Transfer	DataTransfer-Out-Bytes	01 Mar 2020	01 Apr 2020	0.06	\$0.01
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	Amazon Elastic Compute Cloud	APS1-EBS:VolumeUsage	01 Mar 2020	01 Apr 2020	560.62	\$44.85
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	Amazon Elastic Compute Cloud	EBS:VolumeUsage	01 Mar 2020	01 Apr 2020	50.22	\$2.51
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	Amazon Simple Storage Service	APS3-TimedStorage-ByteHrs	01 Mar 2020	01 Apr 2020	0.46	\$0.01
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	AWS Key Management Service	ap-south-1-KMS-Keys	01 Mar 2020	01 Apr 2020	0.96	\$0.96
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	Amazon Elastic Compute Cloud	ElasticIPIdleAddress	01 Mar 2020	01 Apr 2020	4990.00	\$24.95
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	AWS Data Transfer	USE1-EUC1-AWS-Out-Bytes	01 Mar 2020	01 Apr 2020	0.00	\$0.00
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	Amazon Elastic Compute Cloud	EBS:SnapshotUsage	01 Mar 2020	01 Apr 2020	128.90	\$6.44
AmazonDevBilling (686338381863)	01 Mar 2020	01 Apr 2020	AWS Data Transfer	USE1-APN1-AWS-Out-Bytes	01 Mar 2020	01 Apr 2020	0.00	\$0.00

Figure 268 – Amazon Monthly Billing Analysis (Cont.)

1.5.13.11 SLA Report

To view **SLA Report**, Provider user needs to follow the below steps:

1. Click **SLA Reports** Under **My Reports** Dropdown Menu.
2. The following screen appears.

Figure 269 – SLA Reports

3. Select Organization, Platform, and Provisioning Endpoint.
4. Select Applicable Dates, From Date, To Date, and Status.
5. Select Object Type.
- Or
6. Provide **Request Number** from Input Box.
7. Click Show Report.
8. The following screen appears:

Request No	CI Type	Request Type	CI Name	Request Date	Approval Date	Completion Date	Configured SLA(In Minutes)	Total Time(In Minutes)	Status	Requested Name	Computer Name
1358	Virtual Machine	VM	NA	09/15/2022			60		Pending For Approval	HCL Requester	
1316	Virtual Machine	VM	NA	09/09/2022	NA	09/09/2022 17:13:06	0	3	SLA Not Applicable	HCL Requester	

Figure 270 – SLA Reports

1.5.13.12 vCenter Performance Dashboard

This report shows complete health of vCenter. This report has multiple widgets for different vCenter resources for their respective performances. All resources can be drilled down with the lowest level of performance information.

To view the **vCenter Performance Dashboard** report, provider users need to follow the below steps:

1. Click vCenter **Performance Dashboard** under **My Reports** dropdown menu.
2. The following screen appears.

Figure 271 – vCenter Performance Dashboard (Cont.)

3. Select **Platform** and **Environment** from dropdown.
4. Click Show Report.
5. The dashboard appears containing multiple widgets. The description of each widget is as follows:
 - **vCenter Summary:** Highlights the overall summary of vCenter environment.



Figure 272 - vCenter Performance Dashboard (Cont.)

- **OS Wise Distribution Detail:** This section displays number of VMs based on OS.



Figure 273 - vCenter Performance Dashboard (Cont.)

- **Cluster Utilization:** This section displays the details of cluster and their utilization.




Figure 274 - vCenter Performance Dashboard (Cont.)

6. Click the bar chart for further details (of Hosts).

Host Name	Free CPU (%)	Used CPU (%)	Used Memory (%)	Free Memory (%)	Total Memory Capacity In GB	Total CPU Count	Server Model	Current CPU Usage In GHz	Current Memory Usage In GB
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455
indresxi04.dryicelabs.com	34	66	84	16	510.4971	36	Cisco Systems IncUCSB-B200-M5	77.6580	412.6455

Figure 275 - vCenter Performance Dashboard (Cont.)

- **Top 30 Host With CPU Utilization Detail:** This section displays the details of host and their utilization based on CPU utilization.




Figure 276 - vCenter Performance Dashboard (Cont.)

7. Click the **bar chart** for further details.

Host Name	Cluster Name	Data Store Name	Total Disk Space (GB)	Current Usage (%)	No of VM	Consolidation (%)	Free CPU (%)	Used CPU (%)	Used Memory (%)	Free Memory (%)	Total CPU Count	Server Model
indresxi04.dryicelabs.com	SB-Compute-Cluster	datastore1 [3]	335	1	0	1	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	rubrik_Seed547ce5c400b9ad95a8bc066aa6	27993	24	0	24	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	rubrik_e02a4ff3b5d54ec594aaa2f8c361363	27993	24	0	24	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	rubrik_fa132d870b44314b03494d6e255646	27993	22	1	21	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	SharedDatastore01	5632	79	54	99	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	SharedDatastore02	5632	81	35	122	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	SharedDatastore03	5632	78	33	123	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	SharedDatastore04	12800	86	82	116	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	SharedDatastore05	11764	93	50	113	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	SharedDatastore06	13872	97	60	125	34	66	84	16	36	Cisco Systems IncUCSB-B200
indresxi04.dryicelabs.com	SB-Compute-Cluster	SharedDatastore07	5120	86	4	94	34	66	84	16	36	Cisco Systems IncUCSB-B200

Figure 277 - vCenter Performance Dashboard (Cont.)

- **Top 30 Host With Memory Utilization Detail:** This section displays the details of host and their utilization based on memory utilization.




Figure 278 - vCenter Performance Dashboard (Cont.)

- clicking of bar chart, popup window will open which displays host details.




Figure 279 - vCenter Performance Dashboard (Cont.)

- Top 30 Data Storage Detail:** This section displays the details of datastorage and its utilization.




Figure 280 - vCenter Performance Dashboard (Cont.)

- Resource Pool:** This section displays the details (utilization) of resource pool and its clusters.




Figure 281 - vCenter Performance Dashboard (Cont.)

- Cluster, Host And Data Store Detail:** This section displays the details of cluster, host and data store and their utilization for last 30 days.



Figure 282 - vCenter Performance Dashboard (Cont.)

1.5.13.13 vCenter Performance Report

This report shows the nested visualization of vCenter. Starting from topmost datacenter level, users can view the data to lower-level resources like datastore.

To view the **vCenter Performance Report**, provider user needs to follow the below steps:

1. Click vCenter Performance Report under My Reports dropdown menu.
2. The following screen appears.

Figure 283 - vCenter Performance Report (Cont.)

3. Select Provider, Platform, and Provisioning Endpoint from dropdown.
4. Click Show Report.
5. The following screen appears:

Data Center Name
+ secondary-site-datacenter

Figure 284 - vCenter Performance Report (Cont.)

6. On clicking **Expand** (+) button, data store's information will be displayed in textual and graphical representation.
7. The following screen appears:





Figure 285 - vCenter Performance Report (Cont.)

8. On clicking **Expand** () button, cluster related information will be displayed.
9. The following screen appears:





Figure 286 - vCenter Performance Report (Cont.)

10. On clicking of **Expand** () button, host related information will be displayed.
11. The following screen appears:




Figure 287 - vCenter Performance Report

1.5.13.14 Public Cloud Billing Analyzer

To view the **Public Cloud Billing Analyzer Report**, provider user needs to follow the below steps:

1. Click Public Cloud Billing Analyzer under My Reports drop-down menu.
2. Select Provider, Platform, Month, Subscription, Tag Name, and Tag Value.
3. Click Show Report.

Public Cloud Billing Analyzer

Cloud Filters

Provider

pvdDemo

Platform

Microsoft Azure (ARM)

Month

May 2020

Subscription

--All--

Tag Name

--Select--

Tag Value

--Select--

Show Report

Reset

Figure 288 - Public Cloud Annual Billing Analyzer

4. The following screen appears:




Figure 289 - Public Cloud Annual Billing Analyzer (Cont.)



Figure 290 - Public Cloud Annual Billing Analyzer (Cont.)




Figure 291 - Public Cloud Annual Billing Analyzer (Cont.)




Figure 292 - Public Cloud Annual Billing Analyzer (Cont.)

1.5.13.15 Forecasting and RI Recommendation

This enables cost optimization and resource utilization by analyzing the past usage patterns & recommending the most optimal resource types on AWS and Azure.

For Example, Amazon EC2 Reserved Instances (RI) provides a significant discount (up to 72%) compared to on-demand pricing and provide a capacity reservation when used in a specific availability zone. Based on this provider user can reserve its resources for future and avail benefits in terms of cost.

1. On main menu, My Reports section, click Forecasting and RI Recommendation.
2. The below screen appears.

Figure 293 shows a form titled 'Forecasting And RI Recommendation'. It has a 'Cloud Filters' section with four dropdown menus: 'Organization*', 'Platform*', 'Subscription*', and 'Report Type*'. Each dropdown has a '--Select--' option. Below the filters are two buttons: 'Show Report' and 'Reset'.

Figure 293 - Forecasting and RI Recommendation

3. Refer the below table to understand the fields mentioned in Figure 295 - Forecasting And RI Recommendation (Cont.)-AWS:

Table 25 - Forecasting and RI Recommendation

Field	Description
Organization	MyCloud unique name for organization
Platform	The field lists down the cloud service providers

Subscription	Name of the endpoint (subscription of cloud service provider)
Report Type (AWS)	Forecasting or RI recommendation
Report Type (Azure)	RI recommendation
Term In Year (Azure) – RI Recommendation	For example, 1 year or 3 years
Region (Azure) – RI Recommendation	List of available regions
Granularity (AWS)-Forecasting	Frequency daily or monthly
Term In Year (AWS) – RI Recommendation	For example, 1 year or 3 year
Payment Option (AWS) – RI Recommendation	All upfront, partial upfront, no option
Service Type -(AWS) – RI Recommendation	Type of services offered

4. Select Organization, Platform, and Subscription.
5. Based on platform (AWS/AZURE) report type will vary. For ARM choose **RI Recommendation**.
6. Select Time In Years and Region.
7. Click Show Report.

Figure 294 – Forecasting And RI Recommendation

(*) Are mandatory fields. Reset will enable the cloud filters.

8. A screen appears as below and displays the total forecast amount/cost and daily forecasting prediction in the form of bar chart.




Figure 295 – Forecasting And RI Recommendation (Cont.)-AWS

9. Hover the mouse on the bar chart and detailed forecast prediction will be shown as below:




Figure 296 – Forecasting And RI Recommendation (Cont.)-AWS

10. In case the report type is RI Recommendation (AWS), below screen appears:




Figure 297 – Forecasting and RI Recommendation (Cont.)-AWS

11. Refer the below table to understand the fields mentioned in the above figure:

Table 26 – Forecasting And RI Recommendation

Field	Description
Recommended Instances	No. of recommended instances
Recommended Size	Size of AWS instance

Monthly Savings	Name of the endpoint (subscription of cloud service provider)
Upfront Cost	Cost associated to it
Recurring Monthly Cost	Recurring Monthly Cost
Recommendation Details	Recommendation details

1.5.14 Cloud Calculator

Cloud Calculator Report is used to get comparative cost between platform and available services such as for ARM virtual machine and disk and for VMVAR virtual machine and disk etc.

To view the Cloud Calculator Report, provider user needs to follow the below steps:

1. Click **Cloud Calculator** under **My Reports** drop-down menu.

The screenshot shows the 'Cloud Calculator' interface. At the top, there's a 'Filters' section with three dropdown menus: 'Report Type' (set to '--Select--'), 'Platform' (set to '--Select--'), and 'Services' (set to '--Select--'). Below these is a 'Period' section with a 'Months' dropdown and an empty input field. At the bottom right, there are two buttons: 'Show Report' and 'Reset'.

Figure 298 - Cloud Calculator

2. Select Report Type, Platform, Month, Services, and Period.
3. Click Show Report.

This screenshot shows the 'Cloud Calculator' interface after selections. The 'Report Type' dropdown is set to 'Cost Calculator', 'Platform' is set to 'Amazon Web Services', and 'Services' is set to 'Disk'. The 'Period' dropdown is set to 'Months' with an empty input field. Below the filters, there's a 'Disk' section with a 'Region' dropdown set to 'Asia Pacific (Mumbai)'. Underneath, there's a 'Disk' section with a 'Disk Type' dropdown set to 'General Purpose SSD (gp2) volumes' and a 'Disk in GB' input field with a '+' icon. At the bottom right, there are two buttons: 'Show Report' and 'Reset'.

Figure 299 - Cloud Calculator (Cont.)

4. In the above report we have taken an example of platform AWS and virtual machine as services. Likewise, MyCloud provides multiple different services, platform-wise and based on requirement provider user can calculator the price.

Total Cost per month: 0.786			
Storage Cost(Per Month)			
Region	Description	Usage Type	Total Cost in USD
Asia Pacific (Mumbai)	\$0.131 per GB-month of Provisioned IOPS SSD (io1) provisioned storage - Asia Pacific (Mumbai)	APS3-EBSVolumeUsage.plops	0.786

Figure 300 - Cost Per Month

1.5.15 Decommission Reminder

Through this section, provider user can configure reminder mails when decommissioning date is approaching.

1. On the main menu bar, click **Workflow Management** and then click **Decommission Reminder**.
2. The section has following options:
 - Create Reminder
 - View Reminder

1.5.15.1 Create Reminder

To add reminder, provider user needs to follow the below steps:

1. On the Decommission Reminder screen, click Create Reminder.

Figure 301 - Create Reminder (Cont.)

2. Refer below table for reference:

Table 27 - Create Reminder

Field	Description
Organization	Name of the organization (business units/ divisions in organizations)
Days	Date filed which shows that machine will be decommissioned after days.
Frequency	In which frequency, the machine will be decommissioned

3. Select Organization.
4. Enter **Days**.
5. Select Frequency.
6. Click **Add** or **Cancel** to discard changes.
7. A success message box appears as below:




Figure 302 - Create Reminder (Cont.)

All the fields marked with asterisk (*) are mandatory.

1.5.15.2 View Reminder

Through This Section, Provider User Can View All the Existing Reminder Mails For A Specific Organization.

1. On Decommission Reminder module, select View Reminder tab.
2. Select the **Organization**.
3. Click **Go**.
4. A screen appears as below:






Figure 303 - View Reminder

5. It also comprises of following actions:
 - **Edit** (): To modify the details of existing reminder.
 - **Change Status** (): Toggle the status of existing reminder.

1.5.15.3 Edit Reminder

To edit/ modify the assigned reminder, provider user needs to follow the below steps:


1. Click **Edit** () to modify the desired details.
2. Click **Update** to save the changes.

Figure 304 – Edit Reminder

3. A Success Message Box Appears.




Figure 305 – Edit Reminder (Cont.)

All the fields marked with asterisk (*) are mandatory.

4. Click **OK**.

1.5.15.4 Change Status

To toggle the status of the assigned reminder, provider user needs to follow the below steps:

1. Click **Change Status** (🔄) toggle the status of desired reminder.




Figure 306 – Confirmation Message

2. A Success Message Appears.




Figure 307 - Success Message

1.5.16 Manage Run Once

This screen configures RunOnce, which can be used to specify commands that the system will execute on provisioned VM. This is a day one activity (provisioning) specific to private cloud (VMWAR and SCVM) environment.

1. On the main menu bar, click **Master** and then click **Manage RunOnce**.
2. The section has following options:
 - View RunOnce Command
 - Add RunOnce Command

1.5.16.1 View RunOnce Command

To view command, provider user needs to follow the below steps:

1. On view **RunOnce Command** screen, select **Platform**.
2. Click **Go**.






Figure 308 - View RunOnce Command (Cont.)

3. It also comprises of following actions:
 - **Edit** (

1.5.16.2 Edit RunOnce Command

To edit/modify a command, provider user needs to follow the below steps:

1. Click **Edit** (

Configuration Guide

Figure 309 – Edit RunOnce Command

3. A success message box appears.





Figure 310 – Edit RunOnce Command (Cont.)

All the fields marked with asterisk (*) are mandatory.

1.5.16.3 Delete RunOnce Command

To delete a command, provider user needs to follow the below steps:

1. Click **Delete** ().
2. A popup message appears.




Figure 311 – Confirmation Message

3. Click **OK**
4. A success message appears.




Figure 312 - Success Message

1.5.16.4 Add RunOnce Command

To add commands, provider user needs to follow the below steps:

1. On Manage RunOnce command screen, click Add RunOnce Command.

Figure 313 - Add RunOnce Command

2. Refer the below table to understand the fields mentioned in the above figure:

Table 28 - Manage RunOnce

Field	Description
OS Type	Displays the operating system type
Platform	Private cloud platform i.e., VMWARE or SCVMM.
Provisioning Endpoint	Displays the name of the environment (cloud endpoint)
Name	Command name
Description	Command description
Is Published	Command will be published if this checkbox is checked.
RunOnce Command	Command which will be executed when machine creates first time

3. Select **Platform**.
4. Select Provisioning Endpoint.
5. Enter **Name**.

6. Enter Description.
7. Check or uncheck **Is Published** checkbox.
8. Enter **Command**.
9. Click **Add**.
10. A success message box appears as below:




Figure 314 - Add RunOnce Command

1.5.17 CI Column Configuration

Through this section, provider users can configure CI Columns to import objects.

1. On the Main Menu bar, click Master and then click CI Column Configuration.
2. The below screen will appear.

CI Column Configuration

Platform * Object Type *

Column Name	Is Applicable	Is Editable	Is Mandatory	Custom Validation	Alias	Display Order
PowerStatus	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	IN(running,stopped)	Power Status	↑↓
NoOfVCPU	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Numeric	No Of vCPU	↑↓
MemoryInMB	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Numeric	Memory In MB	↑↓
OSDiskSize	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	AlphaNumeric	OS Disk Size	↑↓
DataDisk1Size	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	AlphaNumeric	Data Disk Size 1	↑↓
DataDisk2Size	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	AlphaNumeric	Data Disk Size 2	↑↓

Figure 315 - CI Column Configuration

3. Select Platform and Object Type.
4. Click **Go**.

CI Column Configuration

Platform * Object Type *

Column Name	Is Applicable	Is Editable	Is Mandatory	Custom Validation	Alias	Display Order
PowerStatus	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	IN(running,stopped)	Power Status	↑↓
NoOfVCPU	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Numeric	No Of vCPU	↑↓
MemoryInMB	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Numeric	Memory In MB	↑↓
OSDiskSize	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	AlphaNumeric	OS Disk Size	↑↓
DataDisk1Size	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	AlphaNumeric	Data Disk Size 1	↑↓
DataDisk2Size	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	AlphaNumeric	Data Disk Size 2	↑↓

Figure 316 - Import Configuration (Cont.)

5. All the CI Columns will be displayed on the screen.

UserEntityID	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--Select--	UserEntityID
UserEmail	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Email	User Email
LeasePeriod	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	--Select--	Lease Period
Itemno	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	Numeric	Itemno
PlatformName	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	--Select--	Platform Name
MachineStatus	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	--Select--	Machine Status
ProviderEntityID	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>	--Select--	ProviderEntityID
OrgEntityID	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--Select--	OrgEntityID
IsImported	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	--Select--	IsImported
CreatedDate	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	Date	CreatedDate

Records 1 - 88 of 88

Save

Figure 317 - Import Configuration (Cont.)

6. Click **Save**.



Figure 318 - Success Message

1.5.18 My Schedules

Through this module, the user can **Schedule Action(s)** on **Object(s)** in an organization. Pre-requisites of using my schedules:

1. Organization should have enabled "**Action Scheduling Enabled**" in the organization module.
2. At least one action should be active for respective object.
3. UI associated with action should not have approval associated with it.
4. Controls used in UI should be textbox and hidden controls only.
5. It has the following options:
 - View Schedules
 - Create Schedules
 - Schedule History

Figure 319 – My Schedules Home Screen

1.5.18.1 Create Schedule

To create a schedule of an action in an organization, login user needs to follow the steps below:

1. Click on the **My Schedules** menu option and then click **Create Schedule**.

Figure 320 – Create Schedule

2. Refer the below table to understand the fields mentioned in the above figure.

Table 29 – Create Schedule Fields

Fields	Description
Organization	Select the name of the organization (business units/ divisions in organizations)
Platform	The field lists down the cloud service provider.
Provisioning Endpoint	Displays the name of the environment (cloud endpoint)
Object Type	Name of the infrastructure resource.
Action	Displays the list of action(s) associated to object.
Name	This unique name of schedule action.
Description	Description of schedule action.
Time Zone	This field represents the time zone of start time.

Start Time	The field represents when to start/schedule the action.
Frequency	Interval at which the action can be schedules
Action Parameter(S)	List of parameters depends on selected action

3. Select Organization.
4. Select Platform and Provisioning Endpoint.
5. Select Object Type.
6. Select **Action**.
7. Enter the **Name** and **Description** of schedule.
8. Select Time Zone and Start Time.
9. Select **Frequency**.
10. Now map the **Parameters of Action**. Parameter Data Type supports two types:
 - **Static** – User can provide the static value of a control.
 - **SQL Function** – SQL function can be used to find the dynamic value of a control.
11. Click **Save**.

Figure 321 – Create Schedule (Cont.)

All The Fields Marked with an Asterisk (*) Are Mandatory.

12. A Success Message Box Appears.




Figure 322 - Create Schedule (Cont.)

13. Now click **OK**. A popup will open containing relevant object(s).
14. You can select the appropriate object(s), on which **Action** need to be scheduled.




Figure 323 - Create Schedule (Cont.)

15. Now click on **Map Button**.
16. A success message box appears.




Figure 324 - Create Schedule (Cont.)

17. Action is scheduled successfully.

1.5.18.2 View Schedule

This section lists all the schedules that have been created by an organization admin.

The screenshot shows the 'My Schedules' interface. At the top, there are tabs for 'View Schedules', 'Create Schedule', and 'Schedule History'. Below the tabs, there is a form with the following fields:

- Organization ***: A dropdown menu with 'HclOrg' selected.
- Platform ***: A dropdown menu with 'Google Cloud (GCP)' selected.
- Provisioning Endpoint ***: A dropdown menu with 'GcpDev' selected.
- Object Type ***: A dropdown menu with 'VM-Virtual Machine' selected.
- Action**: A dropdown menu with '--Select--' selected.
- Go**: A blue button.

Below the form, there is a table with the following columns: Name, Description, Action Name, Frequency, Start Date, Time Zone, Start Date (UTC), Next Run Date, Status, and Action. The table contains one record: 'Start/VM - Daily'.

Records 1 - 1 of 1



Figure 325 - View Schedules


Refer the below table to understand the fields mentioned in the above figure.

Table 30 - View Users Field

Fields	Description
Organization	Select the name of the organization (business units/ divisions in organizations)
Platform	The field lists down the cloud service provider.
Provisioning Endpoint	Displays the name of the environment (cloud endpoint)
Object Type	Name of the infrastructure resource.
Action	Displays the list of action(s) associated to object.
Name	This unique name of schedule action.
Description	Description of schedule action.
Action Name	Name of action for which schedule has been created
Frequency	Interval at which the action can be schedules
Start Date	The field represents when to start/schedule the action.
Time Zone	This field represents the time zone of start time.
Start Date (UTC)	The field represents when to start/schedule the action in UTC time zone
Next Run Date	The field represents next schedule time of the action
Status	The status of the schedule
Action	User to take actions like edit, change status, map objects, history, delete against the listed schedules

It also comprises the following actions:


- **Edit** (): To modify the details of schedule.
- **Change Status** (): To change the status of schedule.


- **Map Objects** (

1.5.18.3 Schedule History

This section lists all the history of schedules actions.

To view the Schedule History, follow the below steps:

1. Click on () icon in the grid records on **View Schedule** tab.
2. The **Schedule History** tab will open.



My Schedules

View Schedules Create Schedule **Schedule History**

Schedule Name: Start VM OneTime Action Name: StartVM Frequency: OneTime

Start Date: 02/12/2021 07:47 End Date: 02/12/2021 15:57 Status: --Select--

Go Back

All dates are in MM/dd/yyyy HH:mm format

Schedule Request ID	Status	Schedule Run Date
9742F68E-4841-4B2B-95F8-A4724511D779	Completed	02/12/2021 15:47

Request No	Object ID	Schedule Run Date	Execution Status
SRREQ000006	6319415243861367066	02/12/2021 15:47	Request Created Successfully

Figure 326 – Schedule History

3. Refer the below table to understand the fields mentioned in the above figure.

Table 31 – Schedule History Field

Fields	Description
Schedule Name	Refers to the unique name to be given for schedule action.
Action Name	Name of action for which schedule has been created
Frequency	Interval at which the action can be schedules
Start Date	Start time, to filter the history of schedules from this time
End Date	End time, to filter the history of schedules till this time
Status	InProgress, completed, failed filter status
Schedule Request ID	Unique GUID for the schedule instance.
Status	Status of the scheduled instance
Schedule Run Date	Run date of the scheduled instance

Request No.	Request tracking request number created by schedule request ID.
Object ID	Object ID, unique ID of the object on which action is performed.
Schedule Run Date	Run date of the scheduled instance
Execution Status	Status of the request execution

1.5.19 Logs

Through this module, user can view log(s) for components such as website and WebAPI.

1. User can click on **Logs** from **MyCloud** screen and below screen will appear.

Figure 327 - View Logs Home Screen

2. Select Component Code, Level Code, From Date, and To Date.
3. Enter Absolute URL.
4. Click **Go**.

All dates are in MM/dd/yyyy HH:mm:ss format

Level Code	User Host Id	User Email	Absolute URL	Log Date
INFO	::1	[REDACTED]	http://localhost:47046/Reports/MonthlyReport.aspx	03/05/2021 16:12:25
Log Date	Description	Message	Exception	
03/05/2021 16:12:25	inside BindDynamicMenu start	["ClassName":"MasterPage","MethodName":"BindDynam...		
+	INFO	::1	[REDACTED]	http://localhost:47046/Reports/MonthlyReport.aspx
+	INFO	::1	[REDACTED]	http://localhost:47046/Reports/MonthlyReport.aspx
+	INFO	::1	[REDACTED]	http://localhost:47046/Dashboard/MyCloudDashboard.aspx?language=US

Figure 328 - View Logs (Cont.)

1.5.20 Help

To understand more about MyCloud, provider users can navigate to help icon from menu bar.

It has following actions:

- Download Reference Guide
- Generic Task Details
- License Report




Figure 329 - Help

1.5.20.1 Generic Task Details

This section guides the provider user while configuring manage generic tasks (under manage process workflow) by mapping parameters.

Figure 330 - Generic Task Detail

1. Select Platform, Generic Task and Type.
2. Click **Go**.

Parameter	DataType	Description	Sample	Type
ClientSecretKey	String	ClientSecretKey	ClientSecretKey	INPUT
DataDisks		DataDisks	DataDisks	OUTPUT
Disks	String	Disks	Disks	INPUT
IPAddress		IPAddress	IPAddress	OUTPUT
ManagedStorageAccountType	String	ManagedStorageAccountType	ManagedStorageAccountType	INPUT
NativClientid	String	NativClientid	NativClientid	INPUT
ResourceGroupName	String	ResourceGroupName	ResourceGroupName	INPUT
RoleName	String	RoleName	RoleName	INPUT
Size		Size	Size	OUTPUT
SubscriptionID	String	SubscriptionID	SubscriptionID	INPUT
tag		tag	tag	OUTPUT
TenantId	String	TenantId	TenantId	INPUT
VMName		VMName	VMName	OUTPUT

Figure 331 - Generic Task Detail (Cont.)

1.5.20.2 Download Reference Guide

To help Provider User, MyCloud Has **Provided Reference Guides**.

1. Click **Download** to get the guides.

Document	Description	Action
API Guide	This document explains about Rest APIs which are being used in My Cloud to support cloud infrastructure. With the help of these APIs, we can connect multiple enterprise applications with MyCloud over HTTP and HTTPS.	Download View
Developer Guide	This guide provides instructions to developers for developing UI forms and defining process workflows. This includes the post-installation and configuration procedures for the product.	Download View
Configuration Guide	This document is intended for IT administrators/ Business Administrators those are responsible for configuring MyCloud and enabling end-users to consume MyCloud services.This includes the post-installation and configuration procedures for the product.	Download View
Introduction Guide	This document is intended for IT administrators/ Business Administrators those are responsible for configuring MyCloud and enabling end-users to consume MyCloud services.This includes the post-installation and configuration procedures for the product.	Download View
Troubleshoot Guide	This guide provides instructions to troubleshoot some of the commonly occurring issues along with steps to resolve the issues.	Download View

Figure 332 - Reference Guide

Click on the download link and guides will be downloaded in pdf.

1.5.21 Key Vault Configuration

Through this section, the provider user configures the key vault. Key Vault Configuration can be done by two ways.

- **Cyberark:** External tool to manage the confidential information.
 - **MyCloud Secret Manager:** MyCloud Out Of The Box tool to manage the confidential information.
 - **Azure Key Vault:** Azure vault to manage secret information
1. On the main menu bar, click **Master** and then click **Key Vault Configuration**.
 2. The following screen appears:

Figure 333 - Key Vault Configuration

3. It has following options:
 - Add Configuration
 - View Configuration

1.5.21.1 Add Configuration

To add configuration, the provider user needs to follow the below steps:

1. On the Key Vault Configuration screen, click Add Configuration tab.

Figure 334 - Add Configuration

2. Refer the below table to understand the fields mentioned in the above figure:

Table 32 - Add Configuration

Field	Description
Configuration Tool	Select the configuration tool (Cyberark/ MyCloud Secret Manager/ Azure Key Vault)
Configuration Name	The name of the configuration. Only hyphens and underscores are allowed in the middle of the text. Other special characters are not allowed.
Description	Description of the configuration

Configuration key fields may vary depending on the configuration tool.

Figure 335 - Add Configuration (Cont.)

3. Click **Add**.
4. A success message box appears as below:




Figure 336 - Success Message

1.5.21.2 View Configuration

This section lists out all the Key Vault Configurations that have been created by the provider user.




Figure 337 - View Configuration

1. Select Configuration Tool.
2. Click **Go**.





Figure 338 - View Configuration (Cont.)

3. Refer the below table to understand the fields mentioned in the above figure:


Table 33 - View Configuration

Field	Description
Configuration Name	Name of the configuration which is saved using the add configuration functionality.
Description	Description of the configuration

4. It also comprises of following actions:
 - **Edit** (Add Key.

1.5.21.2.1 Edit Configuration

To edit/ modify the existing configuration, provider user needs to follow the below steps:

1. Click **Edit** () against the configuration that needs to be edited.

Key Vault Configuration

View Configuration | **Add Configuration**

Configuration Tool *
CyberArk

Configuration Name *
GCPCyberArkConfiguration

Description
GCP CyberArk Description

AppID *
1

Safe *
Safe

Folder *
C

Object *
Object

Update **Cancel**

Figure 339 - Edit Configuration

Table 34 - Edit Configuration

Field	Description
Configuration Tool	Configuration tool is non-editable field.
Configuration Name	Configuration name is non-editable field.
Description	Description of the configuration

2. Update the required fields.
3. Click **Update** to save the changes.
4. A success message box shown as below.




Figure 340 - Success Message

1.5.21.2.2 Delete Configuration

To delete the existing configuration, provider user needs to follow the below steps:

1. Click **Delete** (🗑️) against the configuration that needs to be deleted.
2. A confirmation message appears.




Figure 341 - Confirmation Message

3. Click **OK** to continue. A success message appears. Click **Cancel** to cancel the action.




Figure 342 - Success Message

1.5.21.2.3 Add Key

To add any keys to the existing MyCloud secret manager configuration, provider user needs to follow the below steps:

1. Click **Add Key** (+) against the configuration that needs to be edited.
2. The following screen appears:

Key	Action
AWSKey	

Figure 343 - Add Keys

3. Enter **Key** and **Value**.
4. Click **Add**.
5. User can edit and delete the keys based on the configuration.

1.5.22 Object Naming Convention

Through this section, provider user can configure object names.

1. On the Main Menu bar, click Master and then click Object Naming Convention.
2. The below screen will appear.

Figure 344 - CI Naming Convention Home Screen

3. It has following options:
 - Add Configuration
 - View Configuration

1.5.22.1 Add Configuration

To add configuration, provider user needs to follow the below steps:

1. On the Object Naming Convention screen, click Add Configuration tab.

Figure 345 - Add Configuration

2. Refer the below table to understand the fields mentioned in the above figure:

Table 35 - Add Configuration

Field	Description
Organization	Select the name of the organization (business units/divisions in organizations)
Configuration Name	Name of the configuration. Provided that only hyphen and underscore are allowed in middle of text. Other special characters are not allowed.
Global Sequence	This value will be default for all type of keys combination and user can also override its value from manage key action.
Enable Dynamic Key Combination	This key is used to set the output of API based on configuration. If

	value is – <ul style="list-style-type: none">• Yes –If key doesn't exist in the system against a configuration. New key will be created with initial sequence as global sequence.• No – If no key exist then error will be prompted stating that key not exist against configuration.
Description	Description of the configuration

3. Select Organization.
4. Enter Configuration Name, Global Sequence and Description.
5. Enter Enable Dynamic Key Combination.
6. Click **Add**.
7. A success message box appears as below:




Figure 346 - Success Message

1.5.22.2 View Configuration

This section lists out all the CI naming convention configurations that have been created by the provider user.




Figure 347 - CI Naming Convention Home Screen

1. Select Organization.
2. Enter Configuration Name.
3. Click **Go**

Object Naming Convention

View Configuration Add Configuration

Organization * Configuration Name

Configuration Name	Description	Global Sequence	Enable Dynamic Key Combination	Action
Test_Config	Configuration Description	5	Yes	
testConfig	configuration Description	1000	No	

Records 1 - 2 of 2

Figure 348 - View Configuration

4. It also comprises of following actions:

- **Edit** (): To modify the details of existing configuration.
- **Delete** (): To delete the existing configuration.
- **Manage Keys** (): To manage keys of existing configuration.

1.5.22.2.1 Edit Configuration

To edit/modify the existing configuration, provider user needs to follow the below steps:

1. Click **Edit** () against the configuration that needs to be edited.

Object Naming Convention

View Configuration Add Configuration

Organization * Configuration Name * Global Sequence *

Enable Dynamic Key Combination * Description

Figure 349 - Edit Configuration

2. Edit Global Sequence, Enable Dynamic Key Combination, and Description.
3. Click **Update** to save the changes.




Figure 350 - Success Message

1.5.22.2.2 Delete Configuration

To delete the existing configuration, provider user needs to follow the below steps:

1. Click **Delete** (🗑️) against the configuration that needs to be deleted.
2. A confirmation message appears.




Figure 351 – Confirmation Message

3. Click **OK** to continue and **Cancel** to cancel the action.




Figure 352 – Success Message

1.5.22.2.3 Manage Keys

To manage keys in the existing configuration, provider users need to follow the below steps:

1. Click **Manage Keys** (🔑) against the configuration that needs to be added or edited.
2. The below pop up will appear:




Figure 353 – Manage Keys


3. Enter Key and Initial Sequence.
4. Click **Add**.
5. Users can **Edit** and **Delete** the keys based on the configuration.
6. Keys can be a distinct combination for naming logic. Sample values are:
 - PROD_W_AP

- TEST_L_AP
- QAIWIAP

1.5.23 Job Notification Details

Through this section, provider users can view job notifications.

1. On the Main Menu bar, click Master and then click Job Notification Details.
2. The below screen will appear.





Job ID	Job Name	Component	Platform	Provisioning Endpoint	Job Status
230	GCP VPC Sync	Platform Data Sync (SYNC)	Google Cloud Platform	gcpdev	Maximum Retry Reached
1337	IntersightCom Cisco Intersight Target Sync	Cisco Intersight Sync (CICOSYNC)	Cisco Intersight	IntersightCom	Maximum Retry Reached
1338	IntersightCom Virtualization Distributed Network Sync	Cisco Intersight Sync (CICOSYNC)	Cisco Intersight	IntersightCom	Maximum Retry Reached
1340	IntersightCom Virtualization Disk Sync	Cisco Intersight Sync (CICOSYNC)	Cisco Intersight	IntersightCom	Maximum Retry Reached
1342	IntersightCom Virtualization Host Sync	Cisco Intersight Sync (CICOSYNC)	Cisco Intersight	IntersightCom	Maximum Retry Reached
1343	IntersightCom Virtualization Data Store Sync	Cisco Intersight Sync (CICOSYNC)	Cisco Intersight	IntersightCom	Maximum Retry Reached
1344	IntersightCom Virtualization Template Sync	Cisco Intersight Sync (CICOSYNC)	Cisco Intersight	IntersightCom	Maximum Retry Reached
1347	IntersightCom Virtualization DataCenter Sync	Cisco Intersight Sync (CICOSYNC)	Cisco Intersight	IntersightCom	Maximum Retry Reached
1348	IntersightCom Virtualization Cluster Sync	Cisco Intersight Sync (CICOSYNC)	Cisco Intersight	IntersightCom	Maximum Retry Reached

Figure 354 – Job Notification Details Home Screen

3. Refer to the below table to understand the fields mentioned in the above figure:

Table 36 – Job Notification Details

Field	Description
Organization	Select the name of the organization (business units/ divisions in organizations)
Job ID	Unique ID of a job.
Job Name	Unique job name
Component Code	Job belongs to which component, like sync, comp etc.
Providing Endpoint	Unique endpoint name of the provider.
Job Status	Status of the job.

4. User can also check the job notification from the top of the screen by clicking bell icon. ()
5. This will help users to notify the number of jobs which are either on the state of **Maximum Retry Reached**, **Maximum Timeout Reached** or **Failed**.
6. Hover on the **Bell**() Icon.
7. User will get the quick idea of job status.

FinOps Reporting			32	pvd demo ▾
Job ID	Job Name	Status	more ▾	
230	GCP VPC Sync	Maximum Retry Reached	<div> <div>Retry</div> <div>Retry</div> <div>Retry</div> <div>Retry</div> <div>Retry</div> <div>...More</div> </div>	
1337	IntersightCom Cisco Intersight Target Sync	Maximum Retry Reached		
1338	IntersightCom Virtualization Distributed Network Sync	Maximum Retry Reached		
1340	IntersightCom Virtualization Disk Sync	Maximum Retry Reached		
1342	IntersightCom Virtualization Host Sync	Maximum Retry Reached		

Figure 355 – Job Notification Popup

8. Click **More**
9. The user will be redirected to [Job Notification Details](#) screen.

1.5.24 Manage GIT Configuration

Through this section, provider users can manage GIT configuration.

1. On The Main Menu bar, click Master and then click Manage GIT Configuration.
2. The below screen will appear.

Manage GIT Configuration					
View Configuration		Add Configuration			
Configuration Name	Repository URL	Repository Type	User Name	Status	Action
GITConfig1		Private		●	✎ 🔗
GITConfig2		Private		●	✎ 🔗
GITConfig3		Public		●	✎ 🔗
GITConfig_PS_Public_Abhi		Public		●	✎ 🔗
GITConfigPowershell_CyberARC_Abhi		Public		●	✎ 🔗
GITConfigPowershell_SM_Abhi		Public		●	✎ 🔗
GITConfigPS_Input_Private_Abhi		Private	Powershell_Input	●	✎ 🔗
GITConfigPS_CyberARC_Private_Abhi		Private	Powershell_CyberARC	●	✎ 🔗
GITConfigPS_SecretManag_Private_Abhi		Private	Powershell_SecretMang	●	✎ 🔗
GITConfig_PY_Public_Abhi		Public		●	✎ 🔗
GITConfigPY_Input_Private_Abhi		Private	Python_Input	●	✎ 🔗

Figure 356 – Manage GIT Configuration Home Screen

3. It has following options:
 - Add Configuration
 - View Configuration

1.5.24.1 Add Configuration

To add configuration, provider user needs to follow the below steps:

1. On the Manage GIT Configuration screen, click Add Configuration tab.

Figure 357 - Manage GIT Configuration

2. Refer the below table to understand the fields mentioned in the above figure:

Table 37 - Add Configuration

Field	Description
GIT Configuration Name	Unique name of the configuration.
Repository URL	Address of the GIT repository.
Repository Type	Type of the repository, public, or private
Username, Token	For repository type: private, user needs to add creds such as username and token.

3. Select GIT Configuration Name, Repository URL, Repository Type.
4. In the case of '**Private**' repository type, some additional fields appear.

Figure 358 - Manage GIT Configuration (Cont.)

5. Enter Username and Token.
6. Click **Add**.
7. A success message box appears as below:




Figure 359 – Success Message

1.5.24.2 View Configuration

This section lists out all the GIT configurations that have been created by the provider user.

View Configuration		Add Configuration			
Configuration Name	Repository URL	Repository Type	User Name	Status	Action
GITConfig1		Private		●	Edit Delete
GITConfig2		Private		●	Edit Delete
GITConfig3		Public		●	Edit Delete
GITConfig_PS_Public_Abhi		Public		●	Edit Delete
GITConfigPowershell_CyberARC_Abhi		Public		●	Edit Delete
GITConfigPowershell_SM_Abhi		Public		●	Edit Delete
GITConfigPS_Input_Private_Abhi		Private	Powershell_Input	●	Edit Delete
GITConfigPS_CyberARC_Private_Abhi		Private	Powershell_CyberARC	●	Edit Delete
GITConfigPS_SecretMang_Private_Abhi		Private	Powershell_SecretMang	●	Edit Delete
GITConfig_PY_Public_Abhi		Public		●	Edit Delete
GITConfigPY_Input_Private_Abhi		Private	Python_Input	●	Edit Delete

Figure 360 – Manage GIT Configuration

1.5.24.2.1 Edit Configuration

To edit/ modify the existing configuration, provider user needs to follow the below steps:

1. Click **Edit** ([Edit](#)) against the configuration that needs to be edited.

View Configuration		Add Configuration			
Configuration Name*	Repository URL*	Repository Type			
<input type="text" value="GITConfig1"/>	<input type="text"/>	<input type="text" value="Private"/>			
User Name*	Change Token				
<input type="text"/>	<input type="checkbox"/>				
<input type="button" value="Update"/>					

Figure 361 – Edit Configuration

2. Edit GIT Configuration Name, Repository URL, And Repository Type.
3. Click **Update**.
4. A success message appears.




Figure 362 - Success Message

1.5.24.2.2 Change Status

To update/ modify the existing status of configuration, provider user needs to follow the below steps:

1. Click **Change Status** (🔑) against the configuration that status needs to be changed.
2. A confirmation message appears.




Figure 363 - Confirmation Message

3. Click **OK**.




Figure 364 - Success Message

1.5.25 Public Cloud Size Allocation

This module helps provider users to allocate public cloud size allocation.

1. On the main menu Master, click Public Cloud Size Allocation.
2. The below screen appears.

Figure 365 - Public Cloud Size Allocation

3. It has following options:

- View Allocated Size
- Allocate Size

1.5.25.1 Allocate Size

To allocate public cloud size in an organization, user needs to follow the steps below:

1. Click on the **Public Cloud Size Allocation** menu option and then click **Allocate Size**.

Figure 366 - Allocate Size

2. Select Organization, Platform, Region, and Location.
3. Provider user can search by **Name**, **vCPU**, and **Memory**.
4. Click **Submit**.
5. The screen below appears.

Allocate Size				
<input type="checkbox"/>	Name	CPU	Memory (GB)	Description
<input type="checkbox"/>	a1.2xlarge	8	16	a1.2xlarge (vCPU:8, Memory: 16.00)
<input type="checkbox"/>	a1.4xlarge	16	32	a1.4xlarge (vCPU:16, Memory: 32.00)
<input type="checkbox"/>	a1.large	2	4	a1.large (vCPU:2, Memory: 4.00)
<input type="checkbox"/>	a1.medium	1	2	a1.medium (vCPU:1, Memory: 2.00)
<input type="checkbox"/>	a1.metal	16	32	a1.metal (vCPU:16, Memory: 32.00)
<input type="checkbox"/>	a1.xlarge	4	8	a1.xlarge (vCPU:4, Memory: 8.00)

Records 1 - 8 of 294

Figure 367 - Allocate Size

6. Select checkbox for the list of sizes.
7. Click Allocate Size.
8. The below message appears.




Figure 368 - Success Message

1.5.25.2 View Allocated Size

To view allocated public cloud size in an organization, user needs to follow the steps below:

1. Click on the Public Cloud Size Allocation menu option and then click View Allocated Size.

Public Cloud Sizes Allocation

View Allocated Size Allocate Size

Organization* Platform* Region*

Search By

Name vCPU (#) Memory (GB)

Figure 369 - View Allocated Size

2. Select Organization, Platform, Region, and Location.
3. User can search by **Name**, **vCPU**, or **Memory**.
4. Enter **Submit**.

Name	CPU	Memory (GB)	Description	Action
a1.2xlarge	8	16	a1.2xlarge (vCPU:8, Memory: 16.00)	DeAllocate
a1.4xlarge	16	32	a1.4xlarge (vCPU:16, Memory: 32.00)	DeAllocate

Records 1 - 2 of 2

Figure 370 – List of Allocated Size

5. User can **Deallocate** the size.
6. Click on **Deallocate** to the size.
7. A confirmation message appears.




Figure 371 – Confirmation Message

8. Click **OK** to confirm.




Figure 372 – Success Message

1.5.26 Manage Private Cloud Sizes

Through this section, provider users can configure private cloud size.

1. On the main menu bar, click **Master** and then click **Manage Private Cloud Sizes**.
2. The below screen will appear.

The 'Manage Private Cloud Sizes' form has a blue header with the title. Below the header are two tabs: 'View Sizes' and 'Add Size'. Under the 'Add Size' tab, there are two input fields: 'Organization *' with a dropdown menu showing '--Select--' and 'Name' with a text input field. Below these fields is a blue 'Go' button.

Figure 373 – Manage Private Cloud Sizes


3. It has following options:

- View Size
- Add Size

1.5.26.1 Add Size

To add private cloud size in an organization, user needs to follow the steps below:

1. Click on the **Manage Private Cloud Sizes** menu option and then click **Add Size**.



The screenshot shows the 'Manage Private Cloud Sizes' interface with the 'Add Size' tab selected. The form contains the following fields:

- Organization ***: A dropdown menu with '--Select--' as the current selection.
- Name ***: A text input field.
- vCPU (#) ***: A text input field with the value '1'.
- Memory (GB) ***: A text input field with the value '1'.
- Disk (GB)**: A text input field with the value '1'.
- Display Text**: A text input field.
- Display Order**: A text input field.

At the bottom right of the form are two buttons: 'Save' (in blue) and 'Cancel' (in grey).

Figure 374 - Add Size

2. Select Organization.
3. Enter Name, vCPU (#), Memory (GB), Disk (GB), and Display Text.
4. Enter Display Order.
5. Click **Save**.



Figure 375 - Success Message

1.5.26.2 View Sizes

To view private cloud size in an organization, user needs to follow the steps below:

1. Click on the **Manage Private Cloud Sizes** menu option and then click **View Size**.

4. Enter Display Order.
5. Click **Update**.
6. A success message appears.





Figure 379 - Success Message

1.5.26.2.2 Change Status

To toggle the existing status of configuration, provider user needs to follow the below steps:

1. Click **Change Status** () against the check that status needs to be changed.
2. A confirmation message appears.




Figure 380 - Confirmation Message

3. Click **OK** to confirm.





Figure 381 - Success Message

1.5.26.2.3 Delete Size

To delete the existing configuration, provider user needs to follow the below steps:

1. Click **Delete** () against the check that needs to be deleted.
2. A confirmation message appears.




Figure 382 - Confirmation Message




Figure 383 - Success Message

1.6 Blueprint Module

A blueprint is a package of deployable, reusable configuration and policies that implements and documents a specific solution. Blueprints enable users to design infrastructure, platforms, and application services by composing and connecting cloud resources with declarative configuration. Blueprints are designed to capture best practices for specific use cases, including appropriate resource groupings and policies. Once best practices are packaged into a blueprint, they can be shared internally within your organization or distributed among certain groups to evangelize them more broadly. Because blueprints package multiple resources together to target specific use cases, they can provide sensible, contextual default configurations, which reduces the need to tune every option on each resource. This makes onboarding faster and reduces costs. This module describes how to create, edit, and deploy blueprints in DRYiCE MyCloud. It is a drag and drop blueprint designer to support provisioning and post provisioning and has the following features covered.

- Support for GCP, Azure, AWS
- Support Ansible and Cisco Intersight for post provisioning task
- Ability to create infrastructure blueprint using Blueprint Designer
- Blueprint deployment and status tracking
- Out Of Box (OOB) method to deploy blueprints in MyCloud orchestrator
- View execution history and rerun functionality
- Downloads terraform files for blueprint
- History and drift view among multiple versions of blueprint
- Import/export functionality of blueprints

1.6.1 Manage Blueprint

1.6.1.1 Accessing Blueprint

The **Blueprint Module** is managed by the provider user. To access the blueprint, the user needs to login as a provider user and follow the below steps.

1. Login into MyCloud with **provider user** credentials.
2. On the main menu bar, click **Service Catalog** tab.
3. Select **Manage Blueprint** from the available options.




Figure 384 – Manage Blueprint Menu

4. The **Manage Blueprint** page appears:




Figure 385 – Manage Blueprint Page

5. The **Manage Blueprint** page is the landing page for the blueprint module. This page has the options to create and list the blueprint. Under the list section, users have the options to import the blueprint and to view the deployment history, along with other actions. The manage blueprint page covers the following two areas of the blueprint module.
 - Create New Blueprint
 - Manage Existing Blueprints

1.6.1.2 Create New Blueprint

1. To create a new blueprint, click on the **+ Blueprint** icon on **Manage Blueprint** page. The user is directed to the **Design Blueprint** page.




Figure 386 - Design Blueprint

The Design Blueprint page has the following functionalities:

- Cloud platform selection
- Blueprint object search bar
- Left object menu
- Middle diagram pane
- Right attribute window
- Deploy Blueprint (Icon)
- Action Buttons

1.6.1.2.1 Cloud Platform Selection

The Design Blueprint page has a platform selection dropdown where users can select the different configured cloud platforms supported by the Blueprint module.




Figure 387 – Cloud Platform Selection

1.6.1.2.2 Blueprint Object Search Bar

The Design Blueprint page has the option to search for blueprint objects in the left menu. The left menu is filtered based on the input text in the search box.

1. To search, enter any filter value in the search box and click the **Search icon** (🔍).




Figure 388 – Blueprint Object Search Bar

1.6.1.2.3 Left Object Menu

All the configured cloud resources (or objects) of the selected platform appear in the left menu on the **Design Blueprint** page. Cloud objects are arranged category-wise.




Figure 389 - Left Object Menu

To use the configured cloud objects, the user needs to take the following steps:

1. Click on desired **category**.
2. Click on desired **subcategory**.
3. Drag the **object** to the Middle Diagram Pane.




Figure 390 - Left Object Menu (Cont.)

1.6.1.2.4 Middle Diagram Pane

The middle diagram pane in the Design Blueprint page is the area where all the objects are dragged and the blueprints are designed. It is a designer pane where a user can drag objects and map them to other objects.




Figure 391 - Middle Diagram Pane

1.6.1.2.5 Right Attribute Pane

The right attribute pane appears on clicking any object in the diagram pane. It has an attribute list of the selected object. The cloud object attribute can be configured here for the selected object.




Figure 392 - Right Attribute Window

The right attribute window has two types of attributes. The user can configure both types of attributes by selecting the desired tab.

- **Input attributes:** This tab displays the input attributes for the selected object.




Figure 393 - Input Attributes

- **Output attributes:** This tab displays the output attributes for the selected object. There is a checkbox for the attribute name. If this is unchecked, the output property will not be used to capture the output of blueprint execution.




Figure 394 – Output Attributes

By default, the output property is `output_subnet_id1` which is changeable. Ensure that the value is unique throughout the blueprint.


The attribute window has the following options for user input.

- Variable Mapping
- Provider Mapping
- Zone mapping
- Object Mapping/Multiple Object Mapping

1.6.1.2.5.1 Variable Mapping

The user has the option to map the variable to the object attribute which is configured to map variables. Variables can be created using Variables window from top menu. The list of variables shown for that attribute can be filtered by configuring mapping restrictions.


1. Click on the **attribute textbox** and type "var."



A screenshot of a web form with a label 'Key Name *' in bold black text. Below the label is a text input field containing 'var.'. A dropdown menu is open below the input field, showing two suggestions: 'var.subnet' and 'var.keyname'.

Figure 395 – Variable Mapping

2. Select the variables from the list.



A screenshot of a web form with a label 'Key Name *' in bold black text. Below the label is a text input field containing 'var.keyname'. A dropdown menu is open below the input field, showing the selected item 'var.keyname'.

Figure 396 – Variable Mapping (Cont.)

1.6.1.2.5.2 Provider Mapping

The user has the option to map the provider to the object attribute which is configured to map providers. List of providers will be available based on the Cloud platform selected.

1. Click on the attribute textbox and type "**AWS.**" For **Amazon**, and "**google.**" For the **GCP platform**.
2. Select the **provider** from the list.




Figure 397 – Provider Mapping

1.6.1.2.5.3 Zone Mapping

The user has the option to map the zone (in case of AWS and GCP). The zone attribute is used to map the object. A list of zones is available based on the cloud platform selected.

1. Click on the **attribute textbox** and start typing the name of any zone. A list appears.
2. Select the desired zone from the list.




Figure 398 – Zone Mapping

The Object Mapping option allows users to map either single object or collection of objects to the object attribute which is configured to map objects.

Single Object Mapping:

1. Click on the **attribute textbox** and type "obj."
2. Select the object from the list.




Figure 399 – Object Mapping

Multiple Object Mapping:

The Multiple Object Mapping option is used to map multiple objects to the object attribute which is configured to map multiple objects to it. There are three options available in multiple object mapping.

1. **Input object ID as text:** the user can input an existing object ID into the attribute field.




Figure 400 – Input object ID as Text

2. Select the object from list.




Figure 401 – Select the Object from List

3. Map variables to the attributes for providing the objects' name at a later stage:

4. For mapping variables, the user needs to click on the bind variables checkbox next to the attributes.





Figure 402 – Object Mapping Using Variables

1.6.1.2.6 Action Buttons

The icons on the top of the Design Blueprint page are the action buttons and are the short cuts for taking the following actions:

- Expand/Collapse
- Save Blueprint
- Variables
- Download TF (Terraform) File
- Validate Blueprint
- New Blueprint
- Back to Manage Blueprint
- Blueprint Name textbox (Title)

1.6.1.2.6.1 Expand/Collapse

Clicking on the Expand/collapse icon () expands the Diagram Pane to cover the entire page. Clicking the icon again resizes the pane to its original position.





Figure 403 – Expand

1.6.1.2.6.2 Save Blueprint

Clicking the **Save Blueprint** icon () saves the newly created blueprint.

1. Click the **Save Blueprint** icon (), the **Save Blueprint** dialog box appears.

Figure 404 – Save Blueprint

2. The dialog box has the following fields that need to be populated:
 - Blueprint Name
 - Description
 - Tags
3. Click **Save**. A success message appears:




Figure 405 - Success Message

The '**Tags**' field in the Save Blueprint dialog box is to attach tags while saving the blueprint. These tags help users to search for an existing blueprint.

1.6.1.2.6.3 Variables

Create Variable:

To create a variable, take the following steps:

1. Click on **Variables** (+) icon.
2. Click on **Add Variable** tab.

A dialog box titled "Add Variable" with a blue header and a close button (X) in the top right corner. The dialog has two tabs: "Variable List" and "Add Variable", with "Add Variable" being the active tab. Inside the "Add Variable" tab, there are three input fields: "Variable Type" (a dropdown menu currently showing "String"), "Variable Name*" (a text input field with an information icon), and "Value" (a text input field). At the bottom right of the dialog, there are two buttons: "Save" and "Close".

Figure 406 - Add Variable

3. Select the **Variable Type** from the dropdown.




Figure 407 – Variable Type

4. Seven types of variables are available:

- **String:** This variable is used to map plain text values like IDs or any other input value to attributes.
- **Key Value Pair:** This variable is used to map the Tags type of input to any attributes. The value of this variable type is passed in "key=Value" format.

 The "Add Variable" dialog box is shown with the "Add Variable" tab selected. The "Variable Type" dropdown is set to "Key Value Pair". The "Variable Name" field is empty. The "Value" field contains the text "key=value". At the bottom right, there are "Save" and "Close" buttons.

Figure 408 – Add Variable – Key Value Pair Variable

- **Array:** This variable is used to map array type of values to attributes.

 The "Add Variable" dialog box is shown with the "Add Variable" tab selected. The "Variable Type" dropdown is set to "Array". The "Variable Name" field is empty. The "Value" field contains the text "subnet-01,subnet-02". At the bottom right, there are "Save" and "Close" buttons.

Figure 409 –Add Variable – Array Variable

- **Ansible:** This variable is used to map Ansible Extra Vars types of values to attributes.

Variable List

Add Variable

Variable Type

Ansible

Variable Name*

Value

Serial No.	Name	Value	Lookup	Action
1	Name	Mycloud	<input type="checkbox"/>	+

Save

Close

Figure 410 - Add Variable - Ansible Variable

Variable List

Add Variable

Variable Type

Ansible

Variable Name*

Value

Serial No.	Name	Value	Lookup	Action
1	Name	instance1.id	<input checked="" type="checkbox"/>	+

Save

Close

Figure 411 - Add Variable - Ansible Variable (Cont.)

Variable List

Add Variable

Variable Name	Value	Variable Type	Action
myextravar3	[{"sn": 1, "Name": "Hostname", "Value": "... Show more	Ansible	
rbid		String	
subnetname	Subnet1	String	

Close

Figure 412 - Add Variable - Ansible Variable (Cont.)

- Cloud Resource Name:** This variable is used to map the Cloud Resource (Object) Name attribute of an object. In other words, this type of variable is specially used for the name attribute of an object.

- **Region:** This variable is used to map default provider in case of AWS and GCP.

The 'Add Variable' dialog box shows the 'Add Variable' tab selected. The 'Variable Type' is set to 'Region'. The 'Variable Name' is 'awsregion'. The 'Value' field is empty. There are 'Save' and 'Close' buttons at the bottom right.

Figure 413 – Add Variable – Region Variable

- **Cisco Intersight Params:** This variable is used to map Cisco Intersight Params types of values to attributes.

The 'Add Variable' dialog box shows the 'Add Variable' tab selected. The 'Variable Type' is set to 'Cisco Intersight Params'. The 'Variable Name' is 'CI Params'. The 'Value' section contains a table with one row:

Serial No.	Name	Value	KeyType	Lookup	Action
1	Name	host	String	<input type="checkbox"/>	<input type="button" value="+"/>

There are 'Save' and 'Close' buttons at the bottom right.

Figure 414 – Add Variable – Cisco Intersight Params Variable

Add Variable

Variable List
Add Variable

Variable Type

Variable Name*

Cisco Intersight Params

Value

Serial No.	Name	Value	KeyType	Lookup	Action
1	Name	instance1.id	Object	<input checked="" type="checkbox"/>	+

Save
Close

Figure 415 – Add Variable – Cisco Intersight Params Variable (Cont.)

Add Variable

Variable List
Add Variable

Variable Name	Value	Variable Type	Action
civar	<pre>[{ "sn": 1, "Name": "Name", "Value": "outp...</pre> Show more	CiscoIntersight	Edit Delete

Close

Figure 416 – Add Variable – Cisco Intersight Params Variable (Cont.)

- Once the Variable type is selected, enter the **Variable Name** and **Value**.
- Click on **Save** button. A success message appears:

MyCloud



Variable saved successfully.

OK

Figure 417 – Success Message

Edit Variable:

The Edit Variables option is available only for the unmapped variables. If the variables are mapped to the attributes the edit option does not appear. To edit a variable, perform the following steps:

1. Click on the **Variables** () icon.
2. Select the **Variable List** tab.
3. Click on the **Edit** () icon corresponding to the variable to be edited.






Figure 418 – Edit Variable

4. Change the **Value** and Click on **Update** button.

The **Variable Type** and **Name** are not editable.

Delete Variables:

The Delete Variables option is available only for the unmapped variables. If the variables are mapped to the attributes the delete option does not appear. To delete a variable, perform the following steps:

1. Click on the **Variables** () icon.
2. Select the **Variable List** tab.
3. Click on the **Delete** () icon corresponding to the variable to be deleted.




Figure 419 – Delete Variable

1.6.1.2.6.4 Download TF File

1. Click on **Download TF File** () icon.
2. A zip file with the blueprint name is downloaded. The file contains the main.tf, variable.tf, and provider.tf files inside it.

<input type="checkbox"/> Name	Date modified	Type	Size
main.tf	4/12/2022 4:33 PM	TF File	2 KB
providers.tf	4/12/2022 4:33 PM	TF File	3 KB
variables.tf	4/12/2022 4:33 PM	TF File	1 KB

Figure 420 – Download TF File

1.6.1.2.6.5 Validate Blueprint

This option is used to validate the attribute data entered for each object on the blueprint diagram against the configured validation data for each attribute.

1. Click on **Validate attributes** () icon.
2. A Validation Summary dialog box appears.




Figure 421 – Validation Summary

- On successful validation, the following success message appears:




Figure 422 – Validation Success Message

1.6.1.2.6.6 New Blueprint

Clicking the **New Blueprint icon** (📄) opens a new blank blueprint window to create a new blueprint.




Figure 423 – New Blueprint

For a new blueprint, the default name is “**New**”. Once the blueprint is saved with a name, that name appears as the blueprint title.




Figure 424 – Blueprint Title

1.6.1.2.6.7 Back to Manage Blueprint

Clicking on the **Back to Manage Blueprint** (←) icon redirects users to the **Manage Blueprint** page.

1.6.1.2.7 Deploy Blueprint

The **Deploy Blueprint icon** (🚀) on the bottom right allows users to deploy the blueprints through the Design Blueprint page.

For detailed information about the deployment process of blueprints, refer to Deployment from the Design Blueprint Page.

1.6.1.3 Manage Existing Blueprints

All the existing blueprints are listed on the Manage Blueprint page and are managed using the following options available on the page itself:

- View Blueprint
- Import Blueprint
- Deployment History




Figure 425 – Manage Blueprint Page

1.6.1.3.1 View Blueprint

The View Blueprint tab lists all the existing blueprints and displays various options associated with each blueprint. The user can search for specific blueprints by using the filter option.




Figure 426 - View Blueprint

Refer the below table to understand the columns in the above figure:

Table 38 - View Blueprint Table Columns

Fields	Description
Blueprint ID	Displays the ID of the listed blueprint. This is used in process template for the execution of the Blueprint.
Blueprint Name	Displays the Name of the listed blueprint.
Blueprint Description	Displays the Description of the listed blueprint.
Platform	Displays the Platform of the listed blueprint.
Tags	Displays the tags associated with the listed blueprint.
Status	Displays the Active/Inactive status of the listed blueprint.
Action	Displays the actions that can be performed on the listed blueprints.

The search can be filtered by selecting the Platform and by providing Tags associated with the blueprints. By default, the page displays data for all the platforms.




Figure 427 - View Blueprint Filter Option

The gear icon (⚙️) under the **Action** column displays the actions that can be performed on each blueprint.




Figure 428 - Options in the Action Column

Below actions can be performed to manage an existing blueprint:

- Edit
- Change Status
- Download Blueprint Terraform
- Export JSON
- Deploy
- Deployment History
- Compare Blueprint Files

1.6.1.3.1.1 Edit

To edit a blueprint, follow the below steps:

1. From the list of the existing blueprints under the **View Blueprint** tab, click on the gear icon corresponding to the blueprint to be edited and then click the **Edit** icon (✎).
2. It opens the **Design Blueprint** page in edit mode loaded with the selected blueprint in the diagram pane along with all the attributes and variables.




Figure 429 - Edit Blueprint

3. Make the required changes and click on the **Save** (💾) action button.
4. The **Update Blueprint** dialog box appears.

Figure 430 - Update Blueprint

5. On the **Update Blueprint** screen, users can add or remove tags while updating the blueprint. This can be used to search for the created blueprint with the help of tags attached to it under the **View Blueprint** tab.

Only **Blueprint Description** and **Tags** fields are editable here.

6. This dialog has two options for updating the blueprint.
 - **Update:** Clicking on Update button updates the selected blueprint and displays the following success message:




Figure 431 - Success Message for Update

- **Publish New Version:** Selecting this option creates a new version of the blueprint along with all the changes and saves it in the table with the new version number with column 'ispublished' as 'Y'. The old copy of the blueprint is marked 'ispublished' as 'N' in the table.




Figure 432 - Success Message for a New Version Update

1.6.1.3.1.2 Change Status

The option is to mark the listed blueprint status as **Active/Inactive**.

1. Click on the **gear icon** corresponding to the desired blueprint and then click **Change Status** icon (⚙️).
2. A confirmation dialog appears to confirm the action.




Figure 433 - Change Status Confirmation

3. On clicking **OK**, the status of the blueprint is changed to **Active** or **Inactive** and a success message appears as follows:




Figure 434 - Success Message for Status Change

- If the status is changed to **"Active,"** it is marked with a green color as shown in the following screen:

The screenshot shows the "Manage Blueprint" page with a table of blueprints. The first column, "Blueprint Id", is highlighted in green for all rows, indicating they are "Active".

Blueprint Id	Blueprint Name	Blueprint Description	Platform	Tags	Action
241	Blueprint_Deploy_Demo	Blueprint_Deploy_Demo	Amazon Web Services	Blueprint_Deplo... Show more	
240	testblueprint00912	desc	Amazon Web Services	mybp	
239	Blueprint_to_test_object_delete	Blueprint_to_test_object_delete	Amazon Web Services	Blueprint_to_te... Show more	
238	RG Deploytest		Microsoft Azure	19jul	
237	VPCEndpointService - Successcase		Amazon Web Services	VPCEndpointserv... Show more	
236	VPC for EKS		Amazon Web Services	vpc,virtual pri... Show more	

Figure 435 - Status Changed to 'Active'

- Similarly, if the status is changed to **"Inactive,"** it is marked with a red color.

The screenshot shows the "Manage Blueprint" page with a table of blueprints. The first column, "Blueprint Id", is highlighted in red for all rows, indicating they are "Inactive".


Blueprint Id	Blueprint Name	Blueprint Description	Platform	Tags	Action
241	Blueprint_Deploy_Demo	Blueprint_Deploy_Demo	Amazon Web Services	Blueprint_Deplo... Show more	
240	testblueprint00912	desc	Amazon Web Services	mybp	
239	Blueprint_to_test_object_delete	Blueprint_to_test_object_delete	Amazon Web Services	Blueprint_to_te... Show more	
238	RG Deploytest		Microsoft Azure	19jul	
237	VPCEndpointService - Successcase		Amazon Web Services	VPCEndpointserv... Show more	
236	VPC for EKS		Amazon Web Services	vpc,virtual pri... Show more	

Figure 436 - Status Changed to 'Inactive'

For an Inactive Blueprint, the Edit, Deploy and Deployment History options are not available under the Action tab.


1.6.1.3.1.3 Download Blueprint Terraform

This option is used to download the blueprint TF file.

1. Click on the **Download Blueprint Terraform** icon () corresponding to the desired blueprint.
2. This downloads a zip file with the blueprint name.
3. For further steps to download Blueprint Terraform, please refer to **Download TF File**.

1.6.1.3.1.4 Export JSON

This option is used to export the blueprint JSON that can be imported later to any other environment.

1. To export the blueprint JSON, click on the **gear icon** corresponding to the blueprint and then click () icon.
2. A single JSON file with the blueprint name is downloaded. It has the blueprint data in JSON format.


```
1 2 "BlueprintName": "Custom Blueprint",
3 "BPDESC": "Blueprint to showcase LB and SG",
4 "BlueprintJSON": "{ \"diagramJson\" : { \"class\": \"GraphLinksModel\", \"nodeDataArray\": [ { \"category\": \"security_group\", \"name\": \"secu",
5 "Platformcode": "AMAZIN",
6 "Platform": "Amazon Web Services",
7 "Tags": "LB,SG"
```

Figure 437 - Exported JSON File

1.6.1.3.1.5 Deploy

Another way of deploying a blueprint is by clicking the Deploy icon under the Action column on the View Blueprint page.

For detailed information about the deployment process of blueprints, refer to Deployment from the View Blueprint Tab.












Blueprint Id	Blueprint Name	Blueprint Description	Platform	Tags	Action
33	VPC Deploy TF		Amazon Web Services		
32	VPC GIT parent		Amazon Web Services		
31	TF Test Dummy		Microsoft Azure		
30	TF Exec Network	test	Microsoft Azure		
29	New ARM Blueprint		Microsoft Azure	arm	
28	TF Exec Network BLOB		Microsoft Azure		
27	TestVPConeTest		Amazon Web Services		
26	RG TF Version Test		Microsoft Azure		

Figure 438 - Deploy Blueprint from View Blueprint Page

This option is used to view the deployment history of the listed blueprints. This option enables the user to view the Deployment History tab of the Manage Blueprint Page. The Deployment History tab cannot be directly accessed. It can be accessed through this action item of listed blueprints.

1. Click on the Gear Icon -> Deployment History icon .
2. This takes the user to the **Deployment History** tab where he/she can view the deployment history of the blueprint.





Figure 439 - Deployment History

3. The **Deployment History** can be filtered by specifying the **Start Date**, **End Date**, and **Status**, then clicking the **Filter** button.
4. Refer the below table to understand the columns in the above figure.

Table 39 - Deployment History Table Columns

Fields	Description
Request ID	Displays the Request ID of the blueprint deployment. On deployment of the blueprint, a request ID is generated.
Action	Displays the actions that can be taken against the listed deployment request ID. E.g.: Rerun.

5. On expanding the listed request ID by clicking on the plus icon () , a drill down table opens. This table displays the deployment request data. All the tasks created for Blueprint Deployment are listed under the given Request ID created for deployment. Tasks are grouped and listed under the Request ID created for deployment.

All dates are in mm/dd/yyyy HH:mm:ss format

Request Id	Action
F8D514D5-664E-4650-A157-1BE4E0B65326	

Request Id	Status	Date Executed	Result
F8D514D5-664E-4650-A157-1BE4E0B65326	Completed	04/07/2022 15:51:39	<pre>[{"Output": [{"OutputVariableName": "output_instance_id1", "OutputVariableValue": "i-0668216c11bc16748"}, {"OutputVariableName": "output_instance_id2", "OutputVariableValue": "i-05966efa75a055291"}, {"OutputVariableName": "output_lb_arn1", "OutputVariableValue": "arn:aws:elasticloadbalancing:us-east-1:016701022611:loadbalancer/app/private-loadbalancer/20cc761f9d15340"}, {"OutputVariableName": "output_sg_id1", "OutputVariableValue": "sg-0d8de90d9ac2f22b6"}, {"OutputVariableName": "output_sg_id2", "OutputVariableValue": "sg-0b22dc5f077e098c1"}, {"OutputVariableName": "output_subnet_id1", "OutputVariableValue": "subnet-0325496b726c00f61"}, {"OutputVariableName": "output_subnet_id2", "OutputVariableValue": "subnet-0c7a89c37ff673220"}, {"OutputVariableName": "output_vpc_id1", "OutputVariableValue": "vpc-0d16e304a329054e5"}]}</pre> Show less
7D568DAC-1ABF-4692-A850-67C91D7D6EC5			
92f3e757-70ea-4ffa-930b-124561179A11			
23531BE3-1B76-4C51-8E68-572C32F677EE			
B87E5DD7-0A3D-4A2A-ABCB-EDCB9D684701			

Figure 440 – Deployment History Drill Down

Refer the below table to understand the columns in the above figure:

Table 40 – Deployment History Drill Down Table Field

Fields	Description
Request ID	Displays the Request ID of the blueprint deployment. On deployment of the blueprint, a request ID is generated.
Status	Displays the status (Completed/inprogress/Error) of the blueprint deployment request.
Date Executed	Displays the Execution Date of the blueprint deployment request.
Result	Displays the Result of the blueprint deployment request.
Action	Displays the actions that can be taken against the listed deployment request ID. E.g.: Rerun.


- Further expanding the listed Request Id by clicking again on the **plus icon** () opens the complete execution log of the blueprint deployment task.

Figure 441 -Deployment Execution Log

Figure 442 – Multiple Tasks Listed under Deployment History Drill Down

To learn more about the Re-Run Blueprint functionality, please refer to the section **Re-Run Blueprint**.

The Delete icon under the Action column in the View Blueprint tab allows users to delete the listed blueprint.

1. Click on the **Gear Icon - Delete** icon () corresponding to the blueprint to be deleted.
2. A confirmation message appears as follows:




Figure 443 - Confirmation Message

3. Click **OK** to confirm. A success message appears as follows:




Figure 444 - Success Message

1.6.1.3.2 Import Blueprint

This tab allows the user to import the exported blueprint JSON. It is useful to migrate the created blueprint from one environment to another.

1. On the **Manage Blueprint** page, click on the **Import Blueprint** tab.
2. Browse for the exported blueprint JSON file by clicking on **Choose a file** button.




Figure 445 - Import Blueprint

3. The following dialog box appears and allows the user to choose the file:




Figure 446 – Import Blueprint Choose File

4. Select the **Blueprint JSON** file.
5. The file gets uploaded for confirmation with the blueprint JSON data, Blueprint Name, Blueprint Description, and Platform.

For some files, the Platform field is disabled. This signifies that the platform for the imported document cannot be changed while importing the blueprint. It automatically detects and imports the blueprint of the listed platform.

6. Once the user clicks on the **Import** button, the blueprint gets imported successfully and starts appearing in the blueprint list on the View Blueprint page.

Blueprint Id	Blueprint Name	Blueprint Description	Platform	Tags	Status	Action
252	Instance with Multiple NIC 2	Instance with Multiple NIC 2	Amazon Web Services	Instance with M... Show more	●	Edit
251	Instance with Multiple NIC	Instance with Multiple NIC	Amazon Web Services	Instance with ... Show more	●	Change Status
250	EIP with Instance		Amazon Web Services		●	Download Blueprint Terraform
245	standaloneec2coobj		Microsoft Azure		●	Export JSON
244	TestBlueprintAnsibleError	TestBlueprintAnsibleError	Amazon Web Services	TestBlueprintA... Show more	●	Deploy
243	AnsibleBP	here	Amazon Web Services	Mycloud,Ansible	●	Settings
242	CI BP	CI BP	Amazon Web Services	CI BP	●	Settings

Figure 447 – Imported Blueprint listed in View Blueprint

1.6.1.3.3 Deployment History

The Deployment History tab is not directly accessible; however, it can be accessed via the Deployment History action item of listed blueprints in the View Blueprint section of the Manage Blueprint page.

For details, please refer to the **Deployment History** section.

1.6.1.4 Enabling Ansible in Blueprint

The Ansible objects are enabled in Blueprint using the Software Tools option in the Left Object Menu. This software tool is independent of Amazon, Azure, GCP, or VMware and holds the Ansible objects in the blueprint.




Figure 448 - Ansible Object

1. Drag Ansible object to **Diagram Pane** and create the use case.




Figure 449 - Ansible Object on Blueprint Diagram

2. In the Right Attribute Panel, select the Input Attribute tab and populate the fields:
 - **Name:** The name of the object/resource to identify the purpose of the runbook.
 - **Execution Order:** The execution order attribute is used to refer to the execution order of the tasks executed during the deployment process explained under Point no. 3 of section Deployment History.

- **Runbook ID:** It is the id of the runbook provided by the user for post provisioning or day two task.
- **Extra Vars:** A new type of variable (Ansible) can be created from variables window. For the details about Ansible variables, please refer to the section Variables.




Figure 450 – Extra Vars in Ansible Object

3. Click on the **deploy blueprint icon** (🚀). For details on how to deploy the Ansible type object from the Design Blueprint page, please refer to the section **Deployment from the Design Blueprint Page**.

1.6.1.5 Enabling Cisco Intersight in Blueprint

The Cisco Intersight objects are enabled in Blueprint using the **Software Tools** option in the Left Object Menu. This software tool is independent of Amazon, Azure, GCP, or VMware and holds the Cisco Intersight objects in the blueprint.




Figure 451 – Cisco Intersight Object

1. Drag **Cisco Intersight** object to **Diagram Pane** and create the use case.




Figure 452 – Cisco Intersight Object on Blueprint Diagram

2. In the Right Attribute Panel, select the Input Attribute tab and populate the following fields:
 - **Name:** The name of the object/resource to identify the purpose of the Cisco Intersight object.
 - **Virtual Machine:** The Virtual Machine attribute is used to map the Instance.
 - **Execution Name:** It is the Execution name for Cisco Intersight provided by the user for post provisioning or day two task.
 - **Organization Moid:** It is the Organization Moid for Cisco Intersight provided by the user for post provisioning or day two task.
 - **Workflow Moid:** It is the Workflow Moid for Cisco Intersight provided by the user for post provisioning or day two task.
 - **Execution Order:** The execution order attribute is used to refer to the execution order of the tasks executed during the deployment process explained under Point no. 3 of section Deployment History.
 - **Workflow Parameters:** A new type of variable (Ansible) can be created from variables window. For the details about Ansible variables, please refer to the section Variables.

Workflow Parameters

var.civar|

Figure 453 – Workflow Parameter in Cisco Intersight Object

3. Click on the **deploy blueprint icon** (🚀). For details on how to deploy the Cisco Intersight type object from the Design Blueprint page, please refer the section **Deployment from the Design Blueprint Page**.

1.6.2 Deploy Blueprint

There are three ways to deploy a blueprint:

- Deployment from the Design Blueprint page
- Deployment from the View Blueprint tab of the Manage Blueprint page
- Deployment from Process workflow


1.6.2.1 Deployment from the Design Blueprint Page


The Deploy Blueprint option on the Design Blueprint page is to deploy the created blueprint to do provisioning of the objects configured in the blueprint.

The deployment can be categorized into two types:

- Deployment without Ansible objects
- Deployment with Ansible objects

For deployment without Ansible Objects:

1. Click on the **Deploy icon** () on the bottom right of the page.
2. The **Blueprint Deployment** window appears.



Parameter Name	Parameter Value
mytags	Key : owner Value : abhishek
	Key : purpose Value : testing
	Key : exp Value : 1april22
Organization	--Select--
Provisioning Endpoint	--Select--

Figure 454 – Blueprint Deployment

3. The user has the option to change the mapped variable values if desired.
4. Select the Organization and Provisioning Endpoint.
5. Click on **Deploy** button.
6. A Provisioning window appears and shows the real-time provisioning logs.




Figure 455 – Provisioning Window for Blueprint


7. On successful completion of provisioning, the output result is displayed in green color. The blueprint objects are successfully provisioned on the selected cloud platform.



Figure 456 – Successful Provisioning of Blueprint Objects

8. In the case of any error in processing, it shows it in red color.

For Deployment with Ansible Objects:

1. Click on the **Deploy icon** () on the bottom right of the page.
2. The **Deployment** window appears.

Note: All the fields are mandatory.

Provisioning Environment

Parameter Name	Parameter Value
instancename	Instance08
label3	Key : qa Value : testing
metadatavaiable3	Key : keymetadat1 Value : valuemetada1 Key : keymetada2 Value : valuemetada2
Organization	--Select--

Deploy Cancel

Figure 457 – Blueprint Deployment Window from Ansible Object

- On the **Blueprint Deployment** window, the Ansible Extra Vars will be displayed under **Ansible Environment** section.

Provisioning Environment

Ansible Environment

Parameter Name	Parameter Value									
myansible	<table border="1"> <thead> <tr> <th>Serial No.</th> <th>Name</th> <th>Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Hostname</td> <td></td> </tr> <tr> <td>2</td> <td>test</td> <td>output_instance_id1</td> </tr> </tbody> </table>	Serial No.	Name	Value	1	Hostname		2	test	output_instance_id1
Serial No.	Name	Value								
1	Hostname									
2	test	output_instance_id1								
EndpointURL	--Select--									

Deploy Cancel

Figure 458 – Extra Vars in Ansible Object

- Change the Extra Vars values if required.
- Select the **endpointurl**, populate all the required fields, and click on **Deploy** button.
- The further steps are same as described in the section Deploy Blueprint.
- On successful deployment, the configured ansible task is run.

For Deployment with Cisco Intersight Objects:

- Click on the **Deploy icon** (🚀) on the bottom right of the page.
- The **Deployment** Window appears.

Note: All the fields are mandatory.

Provisioning Environment

Parameter Name	Parameter Value
tags	Key : <input type="text" value="Name"/> Value : <input type="text" value="mycloud"/>
Organization	--Select--
Provisioning Endpoint	--Select--

Cisco Intersight Environment

Figure 459 – Blueprint Deployment Window from Cisco Intersight Object

- On the **Blueprint Deployment** window, the Cisco Intersight Workflow parameters will be displayed under **Cisco Intersight Environment** section.

Note: All the fields are mandatory.

Provisioning Environment


Cisco Intersight Environment

Parameter Name	Parameter Value												
civar	<table border="1"> <thead> <tr> <th>Serial No.</th> <th>Name</th> <th>Type</th> <th>Value</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>Name</td> <td>object</td> <td><input type="text" value="output_instance_id1"/></td> </tr> <tr> <td>2</td> <td>Host1</td> <td>string</td> <td><input type="text" value="host"/></td> </tr> </tbody> </table>	Serial No.	Name	Type	Value	1	Name	object	<input type="text" value="output_instance_id1"/>	2	Host1	string	<input type="text" value="host"/>
Serial No.	Name	Type	Value										
1	Name	object	<input type="text" value="output_instance_id1"/>										
2	Host1	string	<input type="text" value="host"/>										
Endpoint Name	--Select--												

Figure 460 – Workflow Parameter in Cisco Intersight Object

- Change the Workflow Parameter values if required.
- Select the **endpointurl**, populate all the required fields, and click on **Deploy** button.
- The further steps are same as described in the section Deploy Blueprint.
- On successful deployment, the configured Cisco Intersight task is run.

1.6.2.2 Deployment from the View Blueprint Tab

Another way to deploy the blueprints is from the View Blueprint tab. The deploy button () available on this screen allows users to deploy a blueprint from here. Clicking on the deploy button opens the deploy

dialog box. Follow the similar steps as described in the section “Deployment from the Design Blueprint Page.”

1.6.2.3 Deployment from Process Workflow

In this method, the blueprints are deployed through process workflow. The section “Execution of Blueprint by Creating UI and Process Template” contains detailed information on deployment from process workflow.

1.6.3 Re-Run Blueprint

This option is used to re-run the deployment request. By using Re-run, a user can again request the deployment of the same blueprint request and can change the existing machine attributes values which are mapped to variables. For the attributes which are not mapped with the variables, the user will not be able to change values on re-run.

If the deployment request is not decommissioned, this option does not create new cloud objects; it makes modifications to the existing cloud objects that were created during the deployment request.

If the deployment request has been decommissioned and then re-run is used, it creates the new cloud object mentioned in the deployment request.

The user cannot change the platform or environment in the case of re-run.

The Re-Run action does not appear in the case of an InProgress or Error status of the deployment request. It appears only in the case of the Success status of the deployment request.

For a new deployment, it creates the new request ID in the deployment history but for the re-run case, it runs the execution under the same request ID. It does not create the new request ID. It uses the same terraform state file for task execution.

1.6.3.1 Terraform State File

Terraform must store information about your managed infrastructure and configuration. This information/state is used by Terraform to map real-world resources to your configuration, to keep track of metadata, and to improve performance for large infrastructure.


This state is stored by default in a local file named "terraform.tfstate", but it can also be stored remotely, which works better in a team environment.


Terraform uses this local state to create plans and make changes to your infrastructure. Terraform performs a refresh prior to any operation to update the state with the actual infrastructure.

The primary purpose of Terraform state is to store bindings between objects in a remote system and resource instances declared in your configuration. When terraform creates a remote object in response to a change in configuration, it records the identity of that remote object against a particular resource instance and then potentially updates or deletes that object in response to future configuration changes.

Terraform stores information about your infrastructure in a state file. This state file keeps track of resources created by your configuration and maps them to real-world resources.

Terraform compares your configuration with the state file and your existing infrastructure to create plans and make changes to your infrastructure. When you run terraform apply or terraform destroy against your initialized configuration, terraform writes metadata about your configuration to the state file and updates your infrastructure resources accordingly.

1. Click on **Re-Run** () icon listed in the action column.
2. The **Blueprint Deployment** window appears.



Parameter Name	Parameter Value
lbtarg	Key : Type Value : LB
	Key : Owner Value : mycloud
	Key : creationdate Value : 05Apr22
vtgname	MyCldTG
targetgroup	Key : Type Value : TargetGroup

Figure 461 – Blueprint Deployment on Re-Run

3. The user has the option to change the variable values mapped to the object attributes.
4. Click on the deploy button and perform the similar steps as described in the section "Deployment from the Design Blueprint Page".

1.6.4 Execution of Blueprint by Creating UI and Process Template

The section covers information about the deployment of blueprint through process workflow. This is one of the three methods of blueprint deployment.

To deploy the blueprints through process workflow, the user first needs to create a new blueprint through the Design Blueprint page. (Refer to the section Create New Blueprint to create a new blueprint).

In the example below, the workflow blueprints are created for all three platforms. As already discussed earlier, the listed blueprint can be filtered by typing the tag name in the Tags section.

Blueprint Id	Blueprint Name	Blueprint Description	Platform	Tags	Action
241	Blueprint_Deploy_Demo	Blueprint_Deploy_Demo	Amazon Web Services	Blueprint_Deplo... Show more	
240	testblueprint00912	desc	Amazon Web Services	mybp	
239	Blueprint_to_test_object_delete	Blueprint_to_test_object_delete	Amazon Web Services	Blueprint_to_te... Show more	

Figure 462 – Blueprint Created for Process Workflow

For executing the created Blueprint from Process Workflow, the user needs to do the following:

1. Create the **UI Template**.
2. Create the Process template.
3. Create the Cloud template.
4. Create **Catalog**.
5. Publishing the **Service Catalog**.
6. Execution of Blueprint through **Requester**.
7. Viewing the Request processing on the **Request Task Management**.

1.6.4.1 Creating UI Templates

For processing requests from the process template, the user needs to create a UI template where any blueprints can be deployed. The user provides input attributes and after completing the deployment task the output attributes are returned. These output attributes are passed to the process workflow to run the tasks. So, the UI templates are the medium to pass these output values from blueprint deployment output to process workflow execution.

1. Click on Manage UI Template under Workflow Management menu.




Figure 463 – Create UI Template Menu

2. Go to **Create UI Template** tab and create a UI template. For details on How to create a UI template, please refer to the section **"Manage UI Template● Create UI Template"** in the *MyCloud Configuration Guide – Provider Module – Part 1*.

The screenshot displays the 'Manage UI Template' interface with the 'Create UI Template' tab selected. The form contains the following fields and sections:

- Organization:** HCLorg
- Platform:** Amazon Web Services
- Template Name:** AWS Workflow Blueprint
- Template Description:** Test Ansible Blueprint - AWS Workflow Blueprint
- Number of Tabs:** 1
- Approval Type:** Static Approval
- Approval Templates:** BA Approval (Version 1)
- Request Item Mode:** Multiple Item View

Below the form are two sections:

- Controls:** A list of control types with add icons: Text Box, Text Area, Select, Date, Hidden Field, Key Value Pair, and Addl. Storage.
- Tabs:** A section with an 'Add Tab' button. It contains a 'General Information' tab with a list of inputs: Key Value Pair, Rbremarks1, Rbremarks2, Rbremarks3, and mabpout.

Figure 464 – UI Template Creation for Blueprint Deployment

The following five inputs have been created for the UI template as the blueprint to be executed expects these values from the user input:

- Key Value Pair
- Rbremarks1
- Rbremarks2
- Rbremarks3
- mabpout

To pass the inputs to the process workflow through the UI template, the user needs to create all the input and output parameters in the UI template to map.

1.6.4.2 Create Process Template

After creating UI template, we need to create process template.

1. Click on Manage Process Template under Workflow Management menu.




Figure 465 – Create Process Template Menu

2. Go to **Add Template** tab and create process template for the UI template. For details on How to create a Process template, please refer to the section “**Manage Process Template -> Add Template**” in the *MyCloud Configuration Guide – Provider Module – Part 1*.

Figure 466 – Process Template Creation for Blueprint Deployment

3. Add the Task to Process template to be used to run the process workflow.

S.No.	Task Type	Task Code	Task Name	Notify Success	Notify Failure	Move Group	Group Sequence	Move Task	Action
1	Custom	POWERSHELL	GetVMName	<input type="checkbox"/>	<input type="checkbox"/>	↓	1	↕	🔍 📄 🗑️
2	Generic	CLONE20	NewClone	<input type="checkbox"/>	<input type="checkbox"/>	↕	2	↕	🔍 📄 🗑️
3	Generic	INSERTCI	InsertCI	<input type="checkbox"/>	<input type="checkbox"/>	↑	3	↕	🔍 📄 🗑️

Update

Figure 467 – Add Task for Process Template

- Here the DEPLOYBL tasks have been created for the execution of the blueprint. It is a generic type of task. Different tasks are created for different platform workflows.
- Click on **Manage Task** action on the created task table list.




Figure 468 – Manage Task Action

- The **Manage Task** window appears.

MyCloud

Manage Generic Task [DPBL - DEPLOYBL]


Parameters mapping


Parameter Name	Parameter Description	Data Type	Parameter Value
BlueprintId	Unique Id of blueprint created by Provider	Static	111
OutputBlueprint	Output Variable name, to capture blueprint execution result	Static	mabpout
TerraformVariable	Key Value Pair variables mapping required for terraform task exec...More	tfkeyvalue	Map Key Value
AnsibleVariable	variables mapping required for ansible task execution	ansibledeployn	Ansible Configuration

Submit Close

Figure 469 – Manage Task Action Window

- Under the task, the user needs to map the input parameters to the process workflow. In the given example, there are four parameters mapped for the Deploy Blueprint task (deploybl) as shown in the above screenshot.
- All the parameters can be managed by selecting an option from the dropdown menu.
- Blueprint ID:** This is the Blueprint ID created for deploying the blueprint from the process workflow. Refer to the **Table 38 – View Blueprint Table Columns**.
- Output Blueprint:** Created to capture the output parameter value. There should be the same value of the output attribute created on the UI for the value provided here. And if there is no output attribute created in the UI, it creates a new key with the provided output value here.


11. **Terraformvariable:** It takes key value pair type variables. Click on the **Map Key Value** () button to map the key value for this parameter.



Parameter Name	Parameter DB Type	Parameter Value
mytag	String	tag
awssecretkey	Sql Functions	@@fnGetAWSecretKey
awsaccesskey	Sql Functions	@@fnGetAWSAccessKey

Save Close

Figure 470 – Map Key Value of Manage Task Action

12. The above screen allows you to map the subscription details for which the blueprints are deployed by selecting the respective credentials of that environment. This window displays platform-wise parameters and subscription-wise parameters. For AWS, the access key and the security key are platform specific. The user needs to provide credentials to access the provisioning environment. For GCP, provide the project id and for ARM, provide four keys to access the environment.
13. The window also allows users to map the key-value pairs. The following pairs are available:
- Parameter Name
 - Parameter DB Type
 - Parameter Value.
14. In the case of Blueprint Deployment, the user needs to pass the Access Key and Security Key from the configured values during the execution but in case process workflow, he/she needs to pass it thorough predefined SQL functions. This value is used to decide on which subscription the user deploys the blueprint. This depends on the selected platforms such as AWS, ARM and GCP.
15. For Ansible, there is an option to configure Ansible variables by clicking on **Ansible Configuration** () button.

Blueprint Deployment

Ansible End Point: MyCloud Ansible

Parameter Name	Parameter DB Type	Parameter Value
myextravar1.test	String	Rbremarks1
myextravar1.Hostname	Static	output_subnet_id1
myextravar2.test	String	Rbremarks2

Save Close

Figure 471 – Ansible Configuration of Manage Task Action

- The user selects the Ansible endpoint, and all the key values mentioned in Ansible variables are listed here.

Blueprint Deployment

myextravar2.test	String	Rbremarks2
myextravar2.Hostname	Static	output_vpc_id1
myextravar3.Hostname	Static	output_subnet_id1
myextravar3.Hostname2	Static	output_vpc_id1
myextravar3.testing	String	Rbremarks3

Save Close

Figure 472 – Ansible Configuration of Manage Task Action (Cont.)

1.6.4.3 Create the Cloud Template

To process the requests from the process template, the user needs to create a cloud template.

- Click on the Manage Cloud Template in the Workflow Management menu.




Figure 473 – Manage Cloud Template Menu

2. Select the Platform and the Provisioning Endpoint.

 A screenshot of the 'Manage Cloud Templates' web interface. It features a header with 'Manage Cloud Templates' and two tabs: 'Manage Template' (active) and 'Create Template'. Below the tabs are two dropdown menus: 'Platform' with a '--Select--' option and 'Provisioning Endpoint' with a '--Select--' option. A blue 'Go' button is positioned below the dropdowns.

Figure 474 – Manage Cloud Templates

3. Select the **Create Template** tab and create a cloud template. For details on How to create a Cloud template, please refer to the section “**Manage Cloud Template -> Create Template**” in the *MyCloud Configuration Guide – Provider Module – Part 1*.

 A screenshot of the 'Create Template' form within the 'Manage Cloud Templates' interface. The form is divided into several sections with input fields and dropdowns. Fields include: 'Platform' (Amazon Web Services), 'Provisioning Endpoint' (AWSProvisioning), 'Image Type' (Market Place), 'Image/Template URL' (Image), 'AMI ID', 'Template Name' (Manage Cloud Template - Window Server), 'Product Type' (Windows and Web SQL Server), 'OS Name' (Windows), 'OS Version' (Windows Server 2016 Datacenter Editi...), 'Machine Username' (mycloud), 'Machine Password' (with a search icon), 'Region' (US East (N. Virginia)), and a 'Description' text area.

Figure 475 – Create Cloud Template

1.6.4.4 Create Catalog

To process the request from the process template, the user needs to create a catalog.

1. Click on Manage Catalog in the Service Catalog menu.




Figure 476 – Create Catalog Menu

2. Select the Platform and Provisioning Endpoint.




Figure 477 – Manage Catalog

3. Create a Catalog from the **Create Catalog** tab. For details on How to create a catalog, please refer to the section "**Manage Catalog -> Create Catalog**" in the *MyCloud Configuration Guide – Provider Module – Part 1*.




Figure 478 – Manage Catalog (Cont.)

1.6.4.5 Publish Service Catalog

To process the request from the process template, the user needs to create a catalog.

1. Click on Publish Service Catalog in the Service Catalog menu.




Figure 479 – Publish Service Catalog Menu

2. Select the Organization, Platform, and Provisioning Endpoint.

A screenshot of the 'Publish Service Catalog' form. The form has a header with three tabs: 'View Service Catalog', 'Publish Service Catalog', and 'Import Service Catalog'. Below the tabs are four dropdown menus: 'Organization *', 'Platform *', 'Provisioning Endpoint *', and 'Service Type'. Below these are two text input fields: 'Service Name' and 'Tags'. At the bottom right is a blue 'Go' button.

Figure 480 – Publish Service Catalog

3. Create a **Service Catalog** from the Publish Service Catalog tab. For further steps to create a Service catalog, please refer to Section - **Publish Service Catalog** in the *MyCloud Configuration Guide – Provider Module – Part 1.5.3.2*

A screenshot of the 'Publish Service Catalog' form, showing more detailed configuration options. The form has a header with three tabs: 'View Service Catalog', 'Publish Service Catalog', and 'Import Service Catalog'. Below the tabs are several fields: 'Organization *' (dropdown), 'Platform *' (dropdown), 'Provisioning Endpoint *' (dropdown), 'Catalog *' (dropdown), 'Service Type' (dropdown), 'Service Name *' (text input), 'Object Type *' (dropdown), 'Short Description *' (text input), 'Description *' (text input), 'Process Template Workflow *' (dropdown), 'Maximum number of Instances *' (dropdown), 'Image' (file upload), 'Draft Applicable' (checkbox), 'Request For Applicable' (checkbox), 'IT Validation Applicable' (checkbox), 'Cost Applicable' (checkbox), 'SLA Applicable' (checkbox), 'Generate API Join Applicable' (checkbox), and 'SLA (In Mins) *' (text input). At the bottom right are 'Create' and 'Cancel' buttons.

Figure 481 – Publish Service Catalog (Cont.)

1.6.4.6 Execution of Blueprint through Requester

To create requests for workflow execution, the user needs to create a service catalog. This is done similarly to the existing UI and process template creation process. The following are the steps to explain one of the cases of deploying the blueprint through the process workflow.

1. Login to MyCloud as a **Requester**.
2. Click on Request Service Catalog under the Request Menu.



Figure 482 – Request Service Catalog Menu

3. Select the Environment Type, Purpose, and OS Type. Click on Proceed.

The screenshot shows a form for creating a service catalog request. It has three dropdown menus: 'Environment Type' with 'Production' selected, 'Purpose' with 'Internal POCs' selected, and 'OS Type' with 'Windows' selected. A 'Proceed' button is located at the bottom right of the form.

Figure 483 – Request Service Catalog

4. Select the **Platform** for which you want to create a request and click on **Proceed**.




Figure 484 – Request Service Catalog (Cont.)

5. Click on the Created Service Request.




Figure 485 – Request Service Catalog (Cont.)

6. Select the Number of Instances and click Proceed.

Figure 486 – Request Service Catalog (Cont.)

7. The UI template for requesting appears.

Figure 487 – Request Service Catalog (Cont.)

8. Input the values and click on **Submit** to raise a new request.

- The request can be seen by clicking on **My Request** under **My Account** menu.

Request ID	Platform	Provisioning Endpoint	Request Date (mm/dd/yyyy)	Service Catalog	Requested Action	Object Type	Status	Comments	Action
SRREQ000495	Microsoft Azure	ARMprovisioningProvider	07/19/2023	NA	Resize Server	Virtual Machine	Fulfillment In-Progress		
SRREQ000494	Google Cloud Platform	GCPProvisioning	07/19/2023	GCP_Service_Catalog_New	Request Provisioning	Virtual Machine	Fulfillment Completed		
SRREQ000493	Microsoft Azure	ARMprovisioningProvider	07/19/2023	New Service Azure	Request Provisioning	Virtual Machine	Pending Approval		
SRREQ000492	Microsoft Azure	ARMprovisioningProvider	07/17/2023	New Service Azure	Request Provisioning	Virtual Machine	Fulfillment Completed		
SRREQ000490	Microsoft Azure	ARMprovisioningProvider	07/17/2023	New Service Azure	Request Provisioning	Virtual Machine	Fulfillment In-Progress		
SRREQ000489	Microsoft Azure	ARMprovisioningProvider	07/17/2023	New Service Azure	Request Provisioning	Virtual Machine	Fulfillment In-Progress		
SRREQ000488	Microsoft Azure	ARMprovisioningProvider	07/17/2023	New Service Azure	Request Provisioning	Virtual Machine	Fulfillment In-Progress		

Figure 488 – Request Under My Request

- Clicking on the request displays the further details related to the task.

Request No	SRREQ000691	Location Name	vCenter Location
Request Date (mm/dd/yyyy)	04/15/2022	Catalog Name	vCenter SCSI Publish Service Catalog
Region Name	vCenterRegion	Requester Name	HCL Requester
Platform	Compute on Demand-vCenter	Provisioning Endpoint	vCenterProvisioning
Request Type	Virtual Machine Provisioning	Request for (Email)	

Item : 1

General Information	Compute	Additional Information	Tags	TestingOnly	Disk	Network
Period	1	Cost Type	Allocation based model			
Service Plan	Private Cloud master-data	Provision Date	04/15/2022			
Period Value	Day(s)	Decommission Date	04/15/2022			
Region	vCenterRegion	Location	vCenter Location			
VM Display Name	Test-Vcenter-Tag	Remarks				
Size	Small (vCPU : 1, Memory : 2 GB)	Cluster	SB-Compute-Cluster			
Os Disk Storage	SharedDatastore04	CLUSTERTEST				

Figure 489 – Request under My Request (Cont.)

1.6.4.7 Viewing the Request Processing on Request Task Management

To check the task execution status, the user needs to take the following steps:

- Login to MyCloud as a **Provider User**.
- Click on Request Task Management under the My Report menu.




Figure 490 – Request Task Management Menu

3. The **Request Task Management** page appears, displaying the list of requests.

Request No	Service Catalog	Requested Action	Platform	Provisioning Endpoint	Request Status	Request Date	Requester Name
SRREQ000495-1	NA	Resize Server	Microsoft Azure	ARMprovisioningProvider	Fulfillment In-Progress	07/19/2023 18:32:01	HCLRequester
SRREQ000494-1	GCP_Service_Catalog_New	Request Provisioning	Google Cloud Platform	GCPProvisioning	Fulfillment Completed	07/19/2023 16:03:39	HCLRequester
SRREQ000492-1	New Service Azure	Request Provisioning	Microsoft Azure	ARMprovisioningProvider	Fulfillment Completed	07/17/2023 18:16:31	HCLRequester
SRREQ000490-1	New Service Azure	Request Provisioning	Microsoft Azure	ARMprovisioningProvider	Fulfillment In-Progress	07/17/2023 18:03:15	HCLRequester
SRREQ000489-1	New Service Azure	Request Provisioning	Microsoft Azure	ARMprovisioningProvider	Fulfillment In-Progress	07/17/2023 17:52:59	HCLRequester
SRREQ000488-1	New Service Azure	Request Provisioning	Microsoft Azure	ARMprovisioningProvider	Fulfillment In-Progress	07/17/2023 17:49:36	HCLRequester
SRREQ000486-1	New Service Azure	Request Provisioning	Microsoft Azure	ARMprovisioningProvider	Fulfillment In-Progress	07/17/2023 17:05:27	HCLRequester
SRREQ000472-1	tagtag	Request Provisioning	Compute on Demand-vCenter	vCenterProvisioningProvider	Fulfillment Completed	07/14/2023 15:21:35	HCLRequester
SRREQ000472-2	tagtag	Request Provisioning	Compute on Demand-vCenter	vCenterProvisioningProvider	Fulfillment Completed	07/14/2023 15:21:35	HCLRequester

Figure 491 – Request Task Management

4. Expand your request by clicking on the **plus icon** (+).




SRREQ000482-1		Workflow AWS Blueprint	Amazon Web Services	AWSProvisioning	Fulfillment Completed		03/14/2022 18:14:30		HCL Requester	
Task Name	Task Status	Plan Execution Date	Task Start Date	Task End Date	Exec Plan Id	Execution Type	Sequence	Group Sequence	Retry Count	Action
DPBL	Task Success	03/14/2022 18:17:29	03/14/2022 18:17:29	03/14/2022 18:27:11	974	AUTO	1	1	0	
clinsert	Task Success	03/14/2022 18:17:29	03/14/2022 18:27:37	03/14/2022 18:29:20	974	AUTO	2	2	0	

Figure 492 – Request Task Management (Cont.)


- The Task execution list is displayed.
- The user can view the Request XML of the task by clicking on the **View Message XML** icon () under the action column.

Message XML

```

<Azure>
  <Request>
    <OrderNo>1409</OrderNo>
    <ItemNo>1</ItemNo>
    <TaskCode>POWERSHELL</TaskCode>
    <Script>ikOF4eyiYOQw7FnnUOGvK4hVOqU6NsBW/txSZFFbavz1SK3VFXk7PlsMmfu0lLoFa0xBKW021k6dQbcXCkgKg==</Script>
    <CommandFileName>ARM_1409_1_POWERSHELL_1.PS1</CommandFileName>
    <CommandFolder>C:\Program Files\MyCloud\PS</CommandFolder>
    <Command>& "C:\Program Files\MyCloud\PS\ARM_1409_1_POWERSHELL_1.PS1" -VMName 'MCLD-1409-1' </Command>
    <Configuration>
      <LogFilePath>C:\Program Files\MyCloudLog\ORCSERVICE</LogFilePath>
      <SQLLogAPIEndpoint>Log/CreateLog</SQLLogAPIEndpoint>
      <EnableLog>1</EnableLog>
      <DeleteCommandFile>Y</DeleteCommandFile>
      <ProxyURL />
      <ByPassProxyforLocal>true</ByPassProxyforLocal>
      <ProxyByPassList />
      <RestAPIBaseUrl>https:// /WebAPI</RestAPIBaseUrl>
      <ResponseAPIEndpoint>workflow/ProcessResponseMessage</ResponseAPIEndpoint>
      <ResponseAPIUserName> </ResponseAPIUserName>
      <ResponseAPIPassword> </ResponseAPIPassword>
      <IsAsyncTask>false</IsAsyncTask>
      <ProcessRequestDetailId>2873</ProcessRequestDetailId>
      <OrgEntityId> </OrgEntityId>
      <ResultFieldSeparator>|</ResultFieldSeparator>
      <ResultKeySeparator>:</ResultKeySeparator>
      <AzureAuthURL>https://login.microsoftonline.com</AzureAuthURL>
    
```

Figure 493 – Request Task Management (Message XML)

- Click on the **View Response** icon () under the action column to view the response.

Response

```

<ErrorCode>0</ErrorCode>
<ErrorDescription>&lt;![CDATA[]]&gt;</ErrorDescription>
<Result>hdmMachineName:MCLD-1409-1
</Result>

```

Figure 494 – Request Task Management (View Response)

- To view the detailed logs, click on the **Detailed Log** icon () in the action column.




Figure 495 – Detailed Logs

1.6.5 New Resource in Blueprint to Execute Terraform File from GIT Repository

A new resource onboarded with name “Execute terraform file” under software tools like in below diagram-





Figure 496 – Execute Terraform File from Git Repository


These new resources will have below attributes:

Table 41 – Input Attributes in Git Repository

Field	Description
Name	Name of Execution
Git Branch Name	Git Branch name
Git TF Source Folder	Folder name of that git branch
TF Variables	Variables are require to execute Git terraform files. With the help of  icon user can create variable of type “Git terraform variables” It is a key value pair of all variables used execute git terraform files.

TF backend Config

These configurations will define the location to save state files created during terraform execution.

With the help  icon user can define TF backend config. Variable type is "Terraform Backend config" on the change of variable type backend type will populate

Possible values of backend type are:

- For Amazon platform it is "S3" it will populate to save information of bucket to save state file created during terraform execution.
- For ARM it is "blob" it will populate to save information of bucket to save state file created during terraform execution
- For others it will be local.

Add Variable

Variable ListView Variable

Variable Type

GIT Terraform Variable

Variable Name *

tfvar

Value

Serial No.	Key Type	Name	Value	Action
1	String	securitygroupid	sg-0860ac55c2777a340	

Update

Close

Figure 497 – Terraform Variables

Add Variable

Variable List [Add Variable](#)

Variable Type: Terraform Backend Config

Variable Name*

Backend Type: s3

Value

Serial No.	Name	Value
1	Bucket	
2	Region	
3	Access_Key	

Save Close

Figure 498 – TF Backend Config with S3 Backend Type

Add Variable

Variable List [Add Variable](#)

Variable Type: Terraform Backend Config

Variable Name*

Backend Type: blob

Value

Serial No.	Name	Value
1	StorageAccountName	
2	ContainerName	
3	Key	

Save Close

Figure 499 – TF Backend Config with Blob Backend Type

Add Variable

Variable List [Add Variable](#)

Variable Type: Terraform Backend Config

Variable Name*

Backend Type: local

Value

Serial No.	Name	Value
1	StorageAccountName	
2	ContainerName	
3	Key	

Save Close

Figure 500 – TF Backend Config with Local Backend Type

After filling all the mandatory fields click on  icon to save blueprint, below message appears–




Figure 501 – Success Message

Once blueprint saved successfully then deploy blueprint as mentioned in section "[Deploy Blueprint](#)"

3. Support

To get support for this product, drop a mail to MyCloud-ProdSupport-Team@hcl-software.com.

HCLSoftware

hcltechsw.com